VILLAGE OF MILLBROOK, NEW YORK WATER SYSTEM IMPROVEMENTS

PRELIMINARY ENGINEERING REPORT

Prepared for:

The Village of Millbrook

35 Merritt Avenue PO Box 349 Millbrook, New York 12545,

Prepared by:



February 2014

~		 	A CONTRACTOR OF THE PROPERTY O	- Company Control of C
				-
				
				Althour
				- WOODER!

				•
				· ·
				, parents
				· Agamen
				,
				, & polyments
				N,
				n _i ng _{grande} h
				بمعييه
				Autorite
				MAL—A
				**Mary##/
i .				
	•			
				Jugopa.

TABLE OF CONTENTS

Contents

<u>1.0</u>	INTRODUCTION	2
<u>2.0</u>	REGULATORY STANDARDS	2
<u>3.0</u>	EXISTING FACILITIES	2
<u>4.0</u>	PROPOSED IMPROVEMENTS	4
<u>5.0</u>	PROJECTED PROJECT COSTS	4
<u>6.0</u>	PLANNING CONSIDERATIONS	5
<u>7.0</u>	SUMMARY	5
Figu	ures	
Prop	posed Water Treatment Facility Site Location Map	1
Prop	posed Water Treatment Facility Building Plan and Elevations	2-4
Prop	posed Water Treatment Facility Site Plan	5
Tab	oles	
Prel	iminary Cost Estimates	1
App	pendices	
Vill	age of Millbrook Water Supply Permit	A
Moı	nthly Operation Reports	В
Wat	ter Storage Tank Inspection Report	C
Con	respondence between Village of Millbrook and Dutchess County Health Department	D
CT	time Calculations, EPA Tables and Filter Cartridge Information	E
Pun	np Curves for Booster and Supply Pumps	F

1.0 INTRODUCTION

The Village of Millbrook located in Dutchess County, New York owns and maintains a water supply and distribution system that delivers potable water to approximately 1,400 customers within the Village of Millbrook and the Town of Washington. Raw water to the Village water supply system is provided by a series of infiltration galleries installed within a gravel aquifer adjacent to Shaw Brook and Mill Brook. Based on microscopic particulate analysis (MPA) testing, it has been determined that by the Dutchess County Health Department that source water from these infiltration galleries is under the influence of surface water. As a result, the Village intends undertake a project to construct a new water treatment facility to provide the level of treatment required, as well as address other existing deficiencies within the water supply, treatment, and storage system.

It is the intent of this document to serve as an Engineering Report detailing both the existing conditions of the Village of Millbrook water supply, treatment, and distribution system and make recommendations for needed improvements.

2.0 REGULATORY STANDARDS

This Engineering Report is prepared in conformance with Recommended Standards for Water Works - Great Lakes Upper Mississippi River Board of State Public Health & Environmental Managers, dated 2007 and commonly referred to as the Ten States Standards, and applicable NYSDEC Design Standards. Additional site-specific standards specified and recommended by applicable reviewing agencies will be utilized as necessary.

The project described in this Engineering Report was developed in accordance with all applicable state and federal requirements and the project is sufficiently complete in accordance with all project contracts and the project can be utilized for its intended purpose.

3.0 EXISTING FACILITIES

The Village of Millbrook water treatment and distribution system serves approximately 1,400 customers through approximately 720 service connections in the Village of Millbrook and the Town of Washington. The system was originally constructed in approximately 1931, though many expansions and improvements have been made to the system since that time. As specified in the Water Supply Permits for the system (Appendix A), the supply capacity of the system is 374,400 gallons per day (gpd). Average and peak day demands within the system for 2011 and 2012 are as summarized below (for additional usage information, see Appendix B):

Year	Avg. Daily Demand (gpd)	Peak Daily Demand (gpd)
2011	196,000	445,000
2012	215,000	370,000

Source water for the Village of Millbrook water system is provided by a series of infiltration galleries located in the Town of Washington on Route 44. These infiltration galleries are approximately 12 to 15 feet deep and are located within a gravel aquifer adjacent to Shaw Brook and Mill Brook. Raw water from the galleries is collected by 12-inch diameter clay tile pipe and flows via gravity through a series of concrete block bunkers before flowing to a 45,000 gallon clear well located beneath the existing treatment building. The conditions of these bunkers vary, with some being replaced within recent years, and others remaining in need of replacement or repair. The high water level in the clear well is at the same elevation as the static hydraulic grade of the infiltration galleries; when the clear well is full, flow from the galleries ceases, and no overflow line is provided or necessary.

Treatment to raw water from the infiltration galleries is provided by the injection of sodium hypochlorite for disinfection (contact time is provided by the 45,000 clear well), caustic soda for pH control, and zinc orthophosphate for corrosion control, as per the Water Supply Permit and Corrosion Control Plan for the facility. Following contact time in the clear well, finished water is pumped by two vertical turbine booster pumps into the distribution system. Storage volume and distribution system head is provided by a 90-foot tall, 500,000 gallon steel water storage tank constructed in approximately 1930 and located on Haight Avenue in the Village of Millbrook. The booster pumps are started and stopped based on water levels within the 500,000 gallon storage tank. An inspection of the tank performed in 2010 recommended sandblasting, spot rust repair, and painting of both the internal and external surfaces of the tank (See Appendix C). An emergency generator is provided at the existing facility to allow operation during periods of interruption of electrical service, though this generator is approaching the end of its service life and requires replacement.

The distribution system is comprised of mains between 4-inches and 12-inches in diameter, and consists of a variety of piping materials, including cast iron, ductile iron, PVC, and asbestos cement pipe, as well as copper service lines. The distribution system undergoes regular flushing and deficient line valves and hydrants are replaced in conjunction with local paving work on an as needed basis.

As a result of MPA sampling and site inspections, the Dutchess County Health Department has determined that the infiltration galleries are under the influence of surface water and, in addition, are at risk of contamination from flooding of the adjacent streams. As such, the Department has directed the Village of Millbrook to install filtration equipment in accordance with the Long Term 2 Enhanced Surface Water Treatment Rule (ESWTR). For correspondence between the Village of Millbrook and the Dutchess County Health Department, please see Appendix D.

There are no redundant water sources in addition to the infiltration galleries. The Village has investigated the feasibility of incorporating two existing wells at the former Bennett College site (which have been pump tested and had water quality testing performed upon the raw water) but more analysis is necessary before these wells could be considered as acceptable additional sources.

4.0 PROPOSED IMPROVEMENTS

In order to provide the treatment required, it is recommended that new water treatment facility be constructed. The proposed building will be located at the site of the existing water supply and treatment facility, northeast of the existing fenced-in area on the east side of the entrance road. The building will be constructed at an elevation necessary to prevent flooding from the adjacent streams during extreme wet weather. The treatment building will include filtration equipment, a chemical storage and feed room, a loading dock for delivery of chemicals and process equipment, and a new emergency generator to allow complete operation of the water supply and treatment system during periods of loss of electrical service.

Raw water will be pumped from the existing infiltration galleries bunker system through the new filtration system via low-head pumps. As raw water enters the treatment building, it will flow successively through a 25 micron bag filter, a 5 micron cartridge filter, and a 1 micron absolute cartridge filter, as manufactured by Harmsco Industrial Filters, Inc. The proposed filtration sample will provide 4-log inactivation of Cryptosporidium (3.2-log removal by filtration and a 2log credit for chlorination see Appendix E) in accordance with the Long Term 2 Enhanced Surface Water Treatment Rule and Part 5 of the New York State Sanitary Code. To provide redundancy, two filtration trains will be installed at the proposed facility; each sized to handle 100% of the permitted capacity. Filtered water will be injected with sodium hypochlorite via a new chemical feed system which will be based on maintaining a set residual as determined by a probe downstream of the booster pumps. Caustic soda and zinc orthophosphate will be added to finished water by means of a new flow-paced chemical feed system. A new 150,000 gallon baffled and or mixed contact/storage tank will be constructed adjacent to the proposed filtration building, and new booster pumps controlled by water levels in the 500,000 gallon storage tank will pump water into the distribution system as needed. The proposed storage/contact tank will provide the required contact time for the first users in the distribution system and will provide additional storage capacity for the system. As part of the work performed at the water treatment facility, existing infiltration bunkers which have been observed to be deficient will be repaired or replaced. A proposed site plan, proposed water treatment facility plan, and site location map have been attached in Figures 1, 2, and 3 respectively.

In addition to the construction of the above detailed water treatment facility, the Village is reviewing the cost and feasibility of cleaning and painting the existing 500,000 gallon storage tank. Construction of the proposed 150,000 gallon contact/storage tank will allow the 500,000 gallon tank to be taken offline while this work is performed at a future date.

5.0 PROJECTED PROJECT COSTS

Preliminary construction costs, including all material, labor, engineering, legal, and administration costs for the proposed improvements to the Village of Millbrook water supply and treatment system have been estimated and are as given below:

New Water Treatment Facility - Construction	\$ 1,373,000
Rehabilitation of Collection Bunker	\$ 45,000
Engineering Services	\$ 287,900
Legal Fees	\$ 25,000
Financing Costs	\$ 35,000
Village Administration Costs	\$ 10,000
Contingency (10%)	\$ 177,590
Total Project Cost	\$ 1,953,490

Detailed costs estimates for each of the items listed above have been attached to this report in Table 1.

6.0 PLANNING CONSIDERATIONS

In addition to project funding and financing considerations, the following is a summary of steps, in approximate chronological order, necessary to bring the proposed Village of Millbrook water filtration facility into operation:

- Seek and secure project financing
- Conduct SEQRA review
- Site studies to address wetlands, archeology, and other environmental considerations, as necessary
- Prepare and submit Water Supply Application
- Final Facility Plan and Design for NYSDEC and Dutchess County Health Department review
- Bid and award construction contracts
- Employee training and licensing or contract operation procurement
- System start-up.

Considering the scope of the project, it is estimated that construction of the proposed work could begin in May 2015, with substantial completion and system start-up scheduled for Fall 2015.

7.0 SUMMARY

In conclusion, it has been determined that the construction of a new water treatment facility, along with improvements to the existing raw water supply system, would allow the Village of Millbrook to comply with both the requirements of the Dutchess County Health Depart and the Long Term 2 Enhanced Surface Water Treatment Rule, as well as provide quality water to the users within the distribution system. Furthermore, when the Village conducts cleaning and repainting the existing 500,000 gallon water storage tank will help provide water of acceptable quality to users as well as extend the service life of the tank. While a determination of available funding needs to be conducted to fully assess the financial impact of the proposed improvements


upon water user rates, low-interest financing and grants are available to help minimize any potential rate increases.

				_
				Vomasu-
				-
				monature:
	•			Manager -
				Program
		-		Table 1

				-
				-
				-

FIGURES


			_
		180	
			_
			J.HT U



Colorer
dram.
-
homeon

•
Waterpare .


-



2110	DRAWING TITLE:							
	FLOOR PLAN							
XGUNDAT IO A VIOLATION SATE EDUCATION LAW,	CLIENT: VILLAGE OF MILLBROOK WTP UPGRADE - GWUDI AND TANK							
IG. D.P.C. IL ENGINEERING 13820 - 607 A32,8073 IY 12203 - 518,452,1280 07,865,9235	DESIGNED BY: DPWJEF DRAWN BY: JDG REVIEWED BY: DRO CHECKED BY: DRO	APPROVED BY:	GRAPHIC SCALE SCALE: 3/8" = 1-0" DATE: FEBRUARY 2015 FILENAME: Visys of Michielle Winer Point Demokracking	SHEET NO.				

				rommon tronsmood stage
				(Marino)


				194000000
			•	
				Althous
		•		*****
				ميشيد
				Adjusting 2
				White
				evenue/s
				MANNET
				ADDRES
				-mand-
				'honouer-
				ANGESTS.
				410000
				Same,
				weeker
				*xoom?
	*			



ONS	DRAWING TITLE:			
		EAST	TELEVATIONS	
	CLIENT:			
VILLAGE OF MILLBROOK WATER TREATMENT PLANT UPGRA				
COMENT IS A VIOLATION TATE EDUCATION LAW.	447	TEN INCATI	WENT FLANT OF GRADE	
	DESIGNED BY: DPW/JEF DRAWN BY:	APPROVED BY:	GRAPHIC SCALE 0	
IG, D.P.C.	JDG		SCALE: SHEET NO.	
AL ENGINEERING / 13820 - 607.432.8073 4Y 12203 - 518.452.1290 507.865.9235	REVIEWED BY: DRO		DATE: FEBRUARY 2015	
	CHECKED BY: DRO		FILENAME: Vibrae of Milibraek Water Plant Drawson a due	

 	 	THE PERSON NAMED OF THE PERSON			***************************************		
					W-Design Market		WCD Group Tra-
							*Outside 2 -
							MAKKAO :
						-	
						-	_
						-	
			•				
						-	
						•	
						•	_
						•	
						•	
						•	
						-	
						۳	NAVANA-

							~/NOOL-




ONS	DRAWING TITLE:		
		WEST	ELEVATIONS
CUMENT IS A VICLATION FATE EDUCATION LAW.	CLIENT:		E OF MILLBROOK DE - GWUDI AND TANK
VG, D.P.C. AL ENGINEERING 1 13920 - 607 A32.8073 NY 12203 - 518 A52.1290 307.865.9235	DESIGNED BY: DPW/JEF DRAWN BY: JDG REVIEWED BY: DRO CHECKED BY: DRO	APPROVED BY:	SCALE: 1/4" = 1"-0" SHEET NO. DATE: FEBRUARY 2015 FILENAME: Vibige of latitives a visit First Drawlings.day.

OCCUPANTAL SANCES	A CONTRACTOR OF THE PROPERTY AND ASSESSED.			
Name:				
Access				
498600 (-				
vocani				

13400001				
weezeer-				
Separate.				
MARKET .				
_				
				1
_				

WARE				
Material .		•		
MANUTE.				

wipper.				



 			www.mwa			
	•					
						~~~
						******
						-
					•	
						Palena
						·
						******
						****
						Palderer
						Masso
		,				*woman-
						**************************************
						. HARRY
						*170000.0.*

## **TABLES**

				_
하는 것이 있는 것이 없는 것이 되는 것이 되었다면 되었다면 보고 있는데 보고 있다면 되었다면 되었다면 되었다. 그는 그는 것이 없는데 보고 있다면 되었다면 되었다면 되었다면 보다면 되었다면 보다면 다른데 보다면 되었다면 되었다면 보다면 보다면 되었다면 보다면 보다면 보다면 되었다면 보다면 되었다면 보다면 보다면 보다면 보다면 보다면 보다면 보다면 보다면 보다면 보				_
				_
				_
그 사람이 없는 것이 없는 것이다.				_
				J

#### Table 1 Millbrook, NY Water System Upgrade Project Project Cost Estimate - February 2015

			12/3/2014	
<u>ltem</u>	<u>Unit</u>	Р	ER Est. Cost	<u>Comments</u>
A. Construction				
1. GENERAL CONTRACT				
Sitework:	lump sum	\$	50,000	Includes tank sitework & restoration
Yard Piping:	lump sum	\$	30,000	
Excavation & Backfill:	lump sum	\$	45,000	
150,000 gallon Water Storage	lump sum	\$	250,000	Est. \$158,011, tank and coating only
Tank Construction/Installation:				
Accessories:	lump sum	\$	20,000	
Site Restoration:	lump sum	\$	20,000	
Stormwater Facilities				
(per NYSDEC General Permit):	lump sum	\$	5,000	
Mobilization/Demob/Bonds/insurance:	lump sum	\$	20,000	
New Water Treatment Building:	sq ft	\$	•	1,200 sq.ft @ \$250/sqft
Filtration Equipment (Filters):	lump sum	\$	200,000	, , , , ,
Chemical Feed Equipment:	lump sum	\$	20,000	
New WTP Pumps:	lump sum	\$	50,000	
Process Piping and Valves:	lump sum	\$	40,000	
Existing Retrofit WTP Pumps:	lump sum	\$	50,000	
Existing herionit wir runips.	iump sum	٧	30,000	
SUBTOTAL GENE	RAL CONSTRUCTION:	\$	1,100,000	
2. ELECTRICAL CONTRACT - Water Treatment Plant				
Mobilization/Demob/Bonds/insurance:	lump sum	\$	15,000	
Sitework (New Service, etc.):	lump sum	\$	15,000	
Site Restoration:	lump sum	\$	,000	
	•	\$	50,000	
Electrical Work:	lump sum		•	
SCADA System Work:	lump sum	\$ \$	40,000 100,000	Generator
New Emergency Generator:	lump sum	<u>&gt;</u>	100,000	Generator
SUBTOTAL ELECTRI	CAL CONSTRUCTION:	\$	220,000	
3. HVAC CONTRACT - Water Treatment Plant				
Mobilization/Demob/Bonds/insurance:	lump sum	\$	3,000	
Sitework (New Service, etc.):	lump sum	\$	3,000	
Site Restoration:	lump sum	\$	_	
HVAC Work:	•	\$	50,000	
HVAC WORK:	lump sum	?	30,000	
SUBTOTAL HV	AC CONSTRUCTION:	\$	53,000	
4. EXISTING WATER STORAGE TANK REHABILITATI	በለ ርብለፐዩልርፕ አነባፕ ።	утыч	S PROJECT	
Mobilization/Demob/Bonds/insurance:	lump sum	\$	20,000	
Sitework (Scaffolding, Tenting, etc.):	lump sum	\$	100,000	
Site Restoration:	lump sum	\$	20,000	
Tank Recoating Work:	lump sum	\$	600,000	Includes Lead Remediation
Tank Recoating Work.	iump sum	<u> </u>	000,000	Standard Coating System
				outhdard Codding System
5. REHABLITAION OF THE TWO EXISTING BUNKERS	ON THE EAST SIDE O	F THE	STREAM	
Cost Based on previuos bunker rehab cost plus a a		\$	45,000.00	
•	ABILITATION WORK:			
333.3		τ.		
SUBTOTAL CONST	RUCTION (1+2+3+5):	\$	1,418,000	
	***			

mirovovana ana		
	The state of the s	The state of the s
		-
		Rango,.
		····
		***************************************
		_
		*****
		76-0-
		Norman
		-
		**************************************
		140100-

#### Table 1 Millbrook, NY Water System Upgrade Project Project Cost Estimate - February 2015

		12/3/2014	
<u>Item Unit</u>	F	PER Est. Cost	<u>Comments</u>
B. Other Costs			
1) Professional Services			
a. Site Surveying:			
- Topo Survey	\$	8,000	
- Construction Layout & As-Built Survey	\$	3,500	
b. Geotechnical Investigation:	\$	9,500	
c. Engineering			
-Preliminary Engineering Report:	\$	40,000	
-Preliminary Design:	\$	10,000	
-Stormwater Pollution Prevention Plan (SWPPP):	\$	20,000	
-Final Design:	\$	80,000	
-Bidding/Award:	\$	8,000	
-Construction Administration:	\$	50,000	Based on 6 months construction
-On-Site Inspection (2 months full time	\$	45,900	
2 months part time)			
-As-Built Drawings:	\$	3,000	
d. SEQR/Environmental Review	\$	10,000	Uncoordinated review
			Short EAF no SHPO
SUBTOTAL PROFESSIONAL SERVICES	S: \$	287,900	
2) Legal & Misc.			
-Legal:	\$	15,000	
-Financing Cons./Bookkeeping & Reporting Admin.:	\$	10,000	
-Single Audits:	\$		
SUBTOTAL LEGAL & MISC	.: \$	25,000	
3) Project Financing		45.555	TOP
-Bond Counsel	\$	15,000	
-Short Term Financing/Net Interest	\$	20,000	IRD
SUBTOTAL PROJECT FINANCING	S: \$	35,000	
4) Village Administration Costs	\$	10,000	
SUBTOTAL VILLAGE ADMINISTRATION COST:	S: \$	10,000	
SUBTOTAL OTHER COST:	S: \$	357,900	
C. Contingency (10%) Contingency (10%)	): \$	177,590	
Village of Millbrook Water System Rehabilitatio Estimated Project Budget Cos		1,953,490	

		***************************************
		-
		_
		_
		<del></del> .
		·· <del>··</del>
		V49404-1
		•
		<del></del>
·		
		** none
		WA
		=140000.
		TYME

## APPENDIX - A

	m 7 = -dit U
	- '

State of New York

Department of Conservation

WATER POWER AND CONTROL COMMISSION

#### Water Supply Application No. 592

In the Matter of the Application - of the -

VILIAGE OF MILLBROOK

for approval of its acquisition

of a source of water supply and

of its financial and engineering

plans for the construction of a

water supply system.

#### DECISION

Application filed December 18, 1930
Hearing held in Millbrook,
February 13, 1931
Decision February 19, 1931

APPROVED

#### DECISION ON WATER SUPPLY APPLICATION NO. 592

Elbert A. Burch, Mayor of the incorporated village of Millbrook, acting on behalf and in the name of said municipality, on December 17, 1930, made application to the Water Power and Control Commission for approval of the plans of said village for the acquisition or taking of a water supply, the taking or condemnation of lands for a new or additional source of water supply and of the construction of a water works system in said municipality. This application was filed in the office of the Commission on December 18, 1930.

After due notice, published in the Millbrook Mirror and Round Table, the hearing on this application was held in the Village Hall on said village of Millbrook on February 13, 1931, at one o'clock in the afternoon. At this hearing the Commission considered the petition, maps and plans submitted, examined witnesses and heard arguments for and against the project. The petitioner was represented by Messrs. Russell, Jacobs and Brevoort, its attorneys (Elijah T. Russell, Esq., of counsel). Objections were filed by Silas Wodell, who appeared at the hearing in person, and was represented by R. A. Wodell, Esq.; by Katharine Lanier Standish, who was represented at the hearing by Harlan S. Perrigo, Esq. (Walter J. McNichols, Esq., of counsel); and by Andrew Haight and others, who did not appear at the hearing.

On February 13, 1931, the Commission caused an engineering inspection to be made of the sites of the proposed works and of the proposed source of water supply.

It is proposed to install a publicly owned water works system in the village of Millbrook, which is to supply water for domestic use and fire protection to the more thickly populated section of that village. This system is to consist of 11,100 feet of 6-inch, 12,500 feet of 8-inch, 12,300 feet of 10-inch east iron pipe, 40 fire hydrants, a 500,000 gallon steel standpipe, 31 feet in diameter by 90 feet high, and the other usual accessories. Water is to be obtained from a well and infiltration galleries to be constructed at a point about 1.5 miles east of the center of the village and about 1,000 feet south of the highway, running from Millbrook to Mabbettsville. The well is to be 19 feet deep, formed by a reinforced concrete caisson, 20 feet 6 inches square in outside dimensions. This caisson is to have a reinforced concrete floor, in which seven 4 foot by 4 foot and two 4 foot by 2 foot 6 inch holes are to be left to allow the ground water to enter the well. A fire-proof pumping station is to be constructed on top of this well. In this station are to be installed two electric motor operated 250 gallons per minute pumps, which are to lift water from the well and force it into the village distribution system and standpipe. Provision is to be made for the installation of apparatus for sterilizing this water with liquid chlorine, but such installation is not to be made unless it is found to be necessary. In the event that sufficient water is not obtained from this well, it is proposed to construct two infiltration galleries, running respectively north and west

from it. These are to consist of trenches about 12 feet deep and as long as may be found to be necessary. In each trench three lines of collecting pipe are to be laid. These are to be of 18 inch vitrified tile with open joints or 15 inch porous wall pipe. The trenches are to be backfilled with sand and gravel to the level of the water table. The last three feet of fill is to be made of clay and sod. These underdrains are to discharge into a 7 foot by 7 foot reinforced concrete sand trap, to be constructed adjacent to the above mentioned well. The total cost of this project is estimated at \$160,000.

Mr. Wodell stated that he is the owner of the land immediately west of and downstream from the property proposed to be acquired by the village. On this land is an artifical pond formerly used to operate a mill. He stated that the pumping of water as proposed by the village would divert water from his property and pond and in the event that this diversion should be found seriously to affect his property, his claim for resultant damages would be large. He also called attention to the fact that the force main to be laid in the highway in front of his dam, unless properly located, may jeopardize the safety of that structure.

Mrs. Standish objected on the grounds that as a large proportion of the taxpayers and residents of Millbrook now have a satisfactory water supply, the project is not justified by public necessity and that the project is unjust,

There is no public water supply system of any sort in the village of Millbrook. Water for all purposes is obtained from individually owned dug and driven wells of the ordinary types. There is no sewerage system in the village. From this it follows that in the congested areas wells and cesspools are near together and the quality of the well water is doubtful. In addition, practically no water is available for fire fighting purposes, with the result that the fire hazard is great and insurance rates high. question of installing a water supply system in this village has been under discussion for many years. On February 21, 1906, a water supply application was made to our predecessor, the State Water Supply Commission, (Water Supply Application No. 7) but this was withdrawn on the 5th of March following. At the request of the village authorities, the Conservation Commission investigated various prospective sources of supply for this village in 1912. On December 20, 1929, another water supply application was made to us (Water Supply Application No. 543) but upon examination it was found that this project had not been authorized and it was, therefore, dismissed on January 24, 1930. The installation of a sanitary sewerage system in the thickly built up part of this village has been authorized; such system cannot be fully effective without a water supply system. We are of the opinion that urgent public necessity exists for the installation of a suitable water supply system in this village.

inequitable and in violation of constitutional rights in that it would place an unreasonable burden of the cost of the project on certain taxpayers without any corresponding benefits to them.

Mr. Haight and his associates state that they are owners of property upstream from the proposed well and objected to the restriction of the use of their property without due compensation.

After due study of the petition and its exhibits, the evidence and arguments given at the hearing and the report of the engineer of the Commission on this application, it appears as follows:

Millbrook is an incorporated village, situated in the town of Washington, Dutchess county, about 13 miles east of Hudson river and in a latitude slightly north of that of Poughkeepsie. It is served by that branch of the New York, New Haven and Hartford railroad, which runs from Beacon to This is almost entirely a residence community. Pine Plains. It is surrounded by large estates and has an irregular outline, so drawn as to include certain houses on the estates but not the estates themselves. In this village is the Bennett School, a boarding school for girls with 190 pupils. The population of Millbrook by the last census was 1,295. This is said to be increased by perhaps 200 during the summer. assessed valuation of all taxable property in the village was shown by the last roll to be \$1,177,512. The village has no bonded indebtedness.

The Board of Trustees of the village of Millbrook by resolution adopted November 21, 1930, appropriated the sum of \$160,000 (of which amount the sum of \$150,000 is to be raised by a bond issue) to defray the cost thereof and submitted all these matters to vote at a referendum election. This election was held on December 12, 1930 and carried in the affirmative by a vote of 144 to 6. The making of this petition to us was authorized by resolution of said Board of Trustees, adopted at a meeting held December 16, 1930.

Messrs. Sanborn and Bogert, civil engineers, with an office in the city of New York, have prepared the plans, reports and estimates submitted with this application and are to have charge of the construction of this system, if it is built.

The proposed source of water supply, as above stated, is to consist of a well and infiltration galleries. These are to be put down in a water-bearing deposit of coarse sand and gravel. The surface drainage basin tributary to the stream nearest to the site of this well has an area of 11.5 square miles. The present demands of the village are estimated as between 60,000 and 110,000 gallons per day, depending on whether or not the Bennett School is supplied. A test pit was put down at the site of the proposed well and a pumping test made on it during the extreme dry weather of the past summer. Although it is impossible to make confident prediction of the amount of water obtainable

from any unused subterranean source of water supply, there seems reasonable assurance that sufficient water will be made available by the proposed development to meet the present needs of this village.

There are now no dangerous sources of pollution near the proposed well and the village proposes to maintain this condition. Results of analyses of water taken from the above mentioned test pit are not entirely favorable, but we believe that the sample analyzed was not representative of the water as it will be collected by the proposed works. It is probable that this water will be of good sanitary quality without treatment, but in order to assure that quality we should reserve the right to require purification or additional precautions, if future developments show need for so doing. The village authorities propose to erect a manproof fence about all land within 100 feet of the well or any infiltration gallery; this should be required. In addition, a further strip of 100 feet should be protected by restrictions which will prevent pollution of the soil or ground water.

At this time we should authorize the village to sink the proposed well and to construct such infiltration galleries as it may find to be advisable, provided that these galleries be not extended beyond the limits of the land now proposed to be purchased and subject to the restrictions here imposed for the sanitary protection of the surroundings thereof.

We are of the opinion that sufficient funds are available to meet the probable cost of constructing these works and the purchase of the necessary land. It is our opinion that the total cost of the project should not exceed the appropriation. This total cost cannot confidently be predicted, as it includes compensation for damages which may hereafter be determined by the courts.

As the plans filed with the application are not complete as to all details, we cannot now make final determination as to the safety and suitability of the proposed structures. We should require that completed plans be filed for approval and that work be done only in conformity with approved plans.

The village of Millbrook is to acquire the entire area of the so-called Merritt farm, which contains 101.25 acres. The well and infiltration galleries are to be constructed on this property. In addition it will be necessary for the village to acquire certain rights of way for pipe line and a plot on which to erect the standpipe.

This Commission lacks power in any way to change the legal rights of the objectors or to authorize the village of Millbrook to infringe upon such rights except by due process of law and with just compensation. The objections of Mrs. Standish appear to be based on the fact that the proposed water works system is not to cover or to serve the entire area of this village. It was admitted by the applicant

that due to high elevation and scattered settlement, no attempt was to be made to supply some 25 dwellings in the village. Some of these houses, being those connected with neighboring estates, have satisfactory water supplies at present. It also appears that if such work is authorized, the proposed system readily can be extended to supply these other dwellings, although additional pumping may be needed. We believe that this is a question to be decided by the people of the village and they seem to have authorized this project by an overwhelming majority. The other point raised, that of taxation of property not directly supplied with water, appears to be a matter treated in the village and other laws not directly under our jurisdiction. The question of damages must be considered by us, but it is not within our power to decide specifically who are damaged or the amount of such damages. That being the case, it is impossible for us now to make definite determination of the total cost of this project. We can only be guided by our experience with similar cases, and this experience leads us to believe that the appropriation for this work is reasonably adequate and that the applicant is in financial condition such that it can pay such awards for damages as may reasonably be expected.

Numerous alternative sources of water supply for the village of Millbrook exist. These have been studied. We know of none of these that offer advantages superior to

that now proposed to be used.

The carrying out of this project will have no effect on the water supply interests of any other municipality or civil division of the state.

The legal damages which may be caused by the execution of the plans of the petitioner do not appear to be such as to require any special consideration or legislative enactment in order that they may be equitably determined and paid.

The Commission finds it to be necessary to protect the water supply and the interests of the applicant and of the inhabitants of the territory to be supplied by it with water and to protect the water supply and interests of other municipal corporations and other civil divisions of the State and the inhabitants thereof and to make safe all dams or reservoirs to be constructed by said plans, that the application, maps and plans submitted should be modified to conform to the following:

well or infiltration gallery constructed by authority of this decision shall be used solely for water supply purposes, shall be securely fenced and the entrance of animals and unauthorized persons within the enclosure prevented as far as possible. All land within 200 feet of such well or galleries shall be kept free from pollution of the soil or ground water. Any sources of pollution which may exist or be installed outside of the fence but within the 200 foot area shall be so equipped that all

polluting material will be removed therefrom in tight containers or by east iron sewers or drains with tight lead joints.

- 2. This Commission reserves the right to require the taking of additional precautions to preserve the purity of this water, the enactment of sanitary rules and regulations for that purpose by the State Commissioner of Health or the sterilization or other treatment of all water pumped, if future analyses or inspections shall show necessity for so doing.
- 3. Under authority of this decision and approval the proposed infiltration galleries may now or later be extended to whatever length may be required; provided that these extensions are confined to the Merritt farm and subject to compliance with conditions 1 and 2 above.
- 4. The proposed works shall be completely constructed in strict accordance with plans thereof and specifications therefor which have previously been submitted and approved by this Commission.
- 5. These works shall be completely constructed within three years of the date of this decision.

The Water Power and Control Commission, having given due consideration to the said petition and its exhibits, the proofs and arguments submitted at the hearing and the reports of its engineers thereon, determines and decides as follows:

First. That the application, maps and plans submitted are modified as set forth above and, as so modified,

are the plans hereinafter mentioned.

Second. That the plans proposed are justified by public necessity.

Third. That said plans provide for the proper and safe construction of all work connected therewith.

Fourth. That said plens provide for the proper protection of the supply and the watershed from contamination and that filtration is at the present time unnecessary.

Fifth. That said plans are just and equitable to the other municipalities and civil divisions of the State affected thereby and to the inhabitants thereof, particular consideration being given to their present and future necessities for sources of water supply.

Sixth. That said plans make fair and equitable provisions for the determination and payment of any and all legal damages to persons and property, both direct and indirect, which will result from the execution of said plans or the acquiring of said lands.

State of New York

Department of Conservation
WATER POWER AND CONTROL COMMISSION

Water Supply Application No. 1405

In the Matter of the Application

- of the -

VILLAGE OF MILLBROOK

for the approval of the extension of its water supply and of the engineering plans for the construction of the works necessary to effect such extension.

## Fourth Application

## DECISION

Application filed February 15, 1940
Hearing held in Millbrook,
March 5, 1940

Decision

March 26, 1940

#### APPROVED

# DECISION ON WATER SUPPLY APPLICATION NO. 1405

Irving J. Hicks, Mayor of the incorporated village of Millbrook, in the town of Washington, Dutchess county, acting on behalf and in the name of said village, on February 14, 1940, made application to the Water Power and Control Commission for approval of the plans of said village for the acquisition or taking of an additional water supply and of the construction proposed in connection therewith. This application was filed in the office of the Commission February 15, 1940.

After due notice, published in the Millbrook Mirror and Round Table, the hearing on this application was held in the Village Hall in the village of Millbrook, on March 5, 1940, at 1:00 o'clock in the afternoon. At this hearing the Commission considered the petition, maps and plans submitted, examined witnesses and heard arguments in favor of the project. The petitioner was represented by Messrs. William P. Talbot and Vincent Sepe, Village Trustees. No objections were filed and no one appeared in opposition.

On March 5, 1940, the Commission caused an engineering inspection to be made of the site of the proposed works and of the proposed additional sources of water supply.

Millbrook now proposes to augment its water supply collecting system by the construction of additional infiltration lines in an area east of its existing similar development. These new lines are to consist of over 1,000 feet of

15-inch "Poroswall" pipe, which are designed to collect water throughout the extended area and to transport the water thus collected to the main collecting well at the existing pumping station. At this point the water is to be chlorinated and is then to be pumped by means of existing pumping equipment to the distribution system and to storage. Where this line from the new collecting area to the pumping station crosses Shaw's Pond stream, a small brook passing through this area, it is to be constructed for a distance about 50 feet either side of the stream of tight joint vitrified tile pipe. For the most part the work contemplated under this project has already been completed, having been undertaken during the late fall of 1939. In addition, at the hearing the Commission was asked to ratify the sale of water to certain present consumers located outside of the village limits but now being supplied with water by the village. This includes service to the County Welfare Home, which is located about 1.25 miles from the village. The project involving the construction of the new collecting lines has been carried out at no cost to the village, having been entirely paid for by one of the local residents.

After due study of the petition and its exhibits, the evidence and arguments given at the hearing and the report of its engineers on this application, the Commission finds as follows:

Millbrook is an incorporated village situated in the town of Washington, Dutchess county, about 13 miles east of the Hudson river and slightly north and east of the city of Poughkeepsie. It is served by a branch of the New York, New Haven and Hartford railroad, running from Beacon to Pine Plains. It is almost entirely a residential community and has within its limits the Bennett School, a large private boarding school. The village is surrounded by large estates and its boundaries are so drawn as to include some of the houses on the estates but not the estates themselves. According to the 1930 census, the population of the village of Millbrook was 1296 and it is estimated that its present population is in the neighborhood of 1500. total assessed valuation of all taxable real property located within the village is \$1,189,937.00 and the village has bonded indebtedness to the extent of \$164,000, of which approximately \$126,000 was issued for water supply purposes.

A public water supply system was first installed in the village of Millbrook about 1931. Water for this system is obtained from a large collecting well and a series of tile infiltration lines running north and west of this well. This source of water supply is located about 1,000 feet south of the road leading from Millbrook to Amenia at a point about 1.5 miles east of the center of the village. The acquisition of such a source of water supply by the village was

authorized by a decision of this Commission dated February 19, 1931 (Water Supply Application No. 592; completed works approved August 30, 1937).

originally, the water supplied from this source was ample for the needs of the community, but during the summer of 1939 the Bennett School requested that water from the village system be supplied to that institution. Although it appeared that more than sufficient water was available, the village authorities, fearing that this demand which might be quite considerable might cause a shortage in the village supply, caused an investigation to be made of its water supply requirements and of its facilities for meeting this new demand. As a result of this investigation the present project was recommended to insure an adequate supply.

The making of an application to this Commission for approval of this project was authorized by a resolution of the Village Board adopted on January 4, 1940.

Samborn and Bogert, Consulting Engineers with an office in the city of New York, have been retained by the village as its engineers in connection with this project and the construction work has been carried out under the supervision and direction of this firm of engineers.

It is estimated that the additional supply now proposed to be taken by the village will augment the yield of the village waterworks system by more than 200,000 gallons

per day. As the present average demand in the village excluding the water sold to the Bennett School is not over 150,000 gallons per day, the project as now contemplated should make available sufficient water for the village for some time to come.

The quality of the water from the new development, as indicated by analyses filed, is very similar to that from the existing supply and this in the past has always been satisfactory. Although the quality generally is excellent even without treatment, all of the water now used is chlorinated and water from the new infiltration lines will also be so treated. The village now owns all of the land surrounding this development for a considerable distance and a great part of that area has been securely fenced. It should be required that the village continue to own and use for water supply purposes only all of the land within 200 feet of these lines. There is some potential danger of pollution of the water in this collecting system by surface water in the stream passing through the area and adjacent to it and the Commission, therefore, should require that none of the porous pipe lines be at any point closer than 50 feet to any of these streams and that the village shall provide sufficient fill over these lines so that the final elevation of this area will be at least as high as that at the existing station. Although the treatment now proposed should be sufficient to insure a water

satisfactory in quality, the Commission reserves the right to require the taking of additional sanitary precautions or the further treatment or purification of all water derived from this source of supply if in the future analyses or inspections shall show a need for such action.

Such plans and specifications as have been submitted have provided for satisfactory construction and for the most part the work covered by them has been fully completed. Final approval, however, cannot yet be given pending the completion of the grading of the area surrounding the tile lines and the village must secure such final approval when the work is finally completed.

The carrying out of these plans will have no adverse effect on the water supply interests of any other municipality or civil division of the State.

The legal damages which may be caused by the execution of the plans of the petitioner are not such as to require any special consideration or legislative enactment in order that they may be equitably determined and paid.

The Commission finds it to be necessary to protect the water supply and the interests of the applicant and of the inhabitants of the territory supplied by it with water that the application, maps and plans submitted should be modified to conform to the following:

1. The village of Millbrook must continue to own and use for

water supply purposes only all of the land within 200 feet of any of its water supply collecting lines used in connection with its public water supply system.

- 2. Nothing in this decision and approval contained shall be held to authorize applicant to supply, sell or distribute water from this source of supply for any purposes unless all such water shall first have been treated by sterilization in a manner satisfactory to this Commission.
- 3. Satisfactory precautions must be taken to keep the surface streams passing through or adjacent to this area at least 50 feet from any of the porous collecting lines and the entire area within such distance of these lines must be so graded as to facilitate surface drainage away from these lines and so as to prevent any surface water collecting on the ground above them.
- 4. The Commission reserves the right to require the taking of further sanitary precautions or the treatment or purification of the water from this source should future analyses or inspections show a need for so doing.
- this decision shall have been fully completed by April 1, 1942, or within such extended time as may have been applied for and granted by the Commission, then and on that date this decision shall be deemed to have lapsed and to be of no further force and effect.

6. Nothing in this decision and approval contained shall be held to abrogate the provisions of Section 524 of the Conservation Law, which forbid the operation of any of these works until as constructed they have been approved by the Commission. Such final approval will be given only on due petition therefor. In general such approval will not be given except for a fully completed system, and it will never be given until all provisions affecting the quality of the water and the safety of the works have been fully complied with.

The Water Power and Control Commission, having given due consideration to the said petition and its exhibits, the proofs and arguments submitted at the hearing and the reports of its engineers thereon, determines and decides as follows:

First. That the application, maps and plans submitted are modified as set forth above and, as so modified, are the plans hereinafter mentioned.

Second. That the plans proposed are justified by public necessity.

Third. That said plans provide for the proper and safe construction of all work connected therewith.

Fourth. That said plans provide for the proper protection of the supply and the watershed from contamination and that filtration is at the present time unnecessary.

Fifth. That said plans are just and equitable to the other municipalities and civil divisions of the State

affected thereby and to the inhabitants thereof, particular consideration being given to their present and future necessities for sources of water supply.

Sixth. That said plans make fair and equitable provisions for the determination and payment of any and all legal damages to persons and property, both direct and indirect, which will result from the execution of said plans or the acquiring of said lands.

A oder

PERMIT NO.

WSA No. 7715

DEC No. 3086-0369

REC'L

Filed Date April 17, 1986

# PERMIT

NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION

UNDER THE ENVIRONMENTAL CONSERVATION LAW ARTICLE 15, TITLE 15 (WATER SUPPLY)

		,000	
PERMIT ISSUED TO		MATER RESCHIPCE	•
Village of Millbrook - 5th Applica	tion		
ADDRESS DE PERMITTEE		Michael D Murn	hu Mayor
Washington Avenue, P.O. Box 349, M	illbrook, N.Y. Attr	1: MICHAEL F. MULP	ity, PlayOL
LOCATION OF PROJECT			· ·
New well located 1500 feet south o	f the intersection of	of Bangall Road and	U.S. ROULE 44
DESCRIPTION OF PROJECT			•
Take a supply of water for use in	the existing system	by the installatio	n or one (1)
shallow dug well having a capacity	of 25 GPM, to supp	lement the Village'	s existing
	e structures located		
that collect water which is fed by	gravity to the main	n gallery in the pu	mp house.) The
new well will serve totalleviate t	*	•	
new well will serve Eogalleviate	HELLVILLEGE, LION BIO.		
1			, pro-
during drought conditions.	Trous		
COMMUNITY NAME (City, Town, Village)	TOWN	Washington	
Village of Millbrook	,	DAM NO.	PERMIT ISSUE DATE
COUNTY	FLA COMMUNITY NO.	DAM NO.	November 20, 1986
Dutchess		<u> </u>	MOAGUMET SOL TOOR

## GENERAL CONDITIONS

- Prior to starting work on any construction authorized herein, detailed plans of the structures proposed to be built and specifications for such work shall have been submitted to and approved by the Department. Thereafter such construction work shall be entirely completed in full accordance with the plans and specifications which have been so submitted and approved.
- 2. The Department reserves the right to rescind this permit or to take whatever action it may deem suitable and proper if the works authorized to be constructed herein are not initiated by November 30, 1988
- 3. Section 15-1529 of the Environmental Conservation Law forbids the operation of any of these works until, as constructed, they have been approved by the Department. Such final approval will be given only on written request. In general, such approval will not be given until all provisions affecting quality of the water and safety of the works have been complied with in full.
- 4. The Department reserves the right to reconsider this permit at any time and after due notice and hearing at that time to continue, rescind or modify this permit in such a manner as may be found to be just and equitable.
- Granting of this permit does not relieve the applicant of the responsibility of obtaining any other permission, consent or approval which may be required.
- 6. As a condition of the issuance of this permit, the applicant has accepted expressly, by the execution of the application, the full legal responsibility for all damages, direct or indirect, of whatever nature, and by whomever suffered, arising out of the project described herein and has agreed to indemnify and save harmless the State from suits, actions, damages and costs of every name and description resulting from the said project.
- By acceptance of this permit the permittee agrees that the permit is contingent upon strict compliance with the special conditions following.

NOTE: Only those special conditions following which have been marked  $[\overline{X}]$  apply.

#### SPECIAL CONDITIONS

- 8. All land within 200 feet of any well shall be protected and controlled in order to prevent pollution of the ground or groundwater by direct ownership of the land or by the acquisition of protective easements or other appropriate measures.
- 9. This area shall further be protected from pollution by surface waters originating outside thereof by the construction of suitable diversion ditches or embankments and the development of the water sources shall be so carried out that there shall be no opportunity for pollution entering the water sources.
- 10. The physical pumping facilities and controls shall be protected against damage or lampering either by a fence of other suitable enclosure or by their manner of construction and installation.
- 11. Before any water from the well(s) may be used for any purpose, after prolonged pumping test(s), the applicant shall have caused a sample of the water from each to be collected and analyzed, shall have submitted the results of such analyses to the Department and shall have been advised by the Department either that the water is of a satisfactory sanitary quality or that certain specified treatment or purification thereof is necessary. In this last case such water shall be used only after full compliance with all of the requirements of the Department.
- 12. Nothing contained in this permit and approval shall be held to authorize the applicant to supply, sell or distribute water from this source of supply for any purpose unless all such water shall first have been treated and purified by disinfection (and filtralion) in a manner satisfactory to the Department.

95-20-6 (9/85)	NEW YORK STATE DEPARTMENT OF ENVIRONMENT	NE CONSERVATION
DEC PERMIT NUMBER		RESOURCES FFECTIVE DATE
1358-44-1	WATER !	JULY 23,1987
FACILITY/PROGRAM NUMBER(s) WSA # 7876 6th Application	PERMIT Under the Environmental Conservat	ign 8av 287
* *		EIVE   SEE CONSIDEN NO. 12
Article 15, Title 5: Protection of Water	☐ Article 17, Titles 7, \8: SPDES	
Article 15, Title 15: Water Supply	Air Pollution Control  Article 23, Title 27:	Article 27, Title 9:  Hazardous
Article 15, Title 15: Water Transport	Mined Land	Waste Management Article 34:
Article 15, Title 15: Long Island Wells	☐Article 24:	Coastal Erosion Management
Article 15, Title 27: Wild, Scenic and Recreational Rivers	Article 25: Tidal Wetlands	☐Article 36:
□6NYCRR 608:	N—New, R—Renewal, M—Modifica C—Construction, O—Operation, (If	ation Radiation Control
PERMIT ISSUED TO VILLAGE of Millbrook		
ADDRESS OF PERMITTEE Merritt Avenue, Millb	rook, NY 12545	, · ·
AGENT FOR PERMITTEE/CONTACT PER Michael Murphy, Mayor NAME AND ADDRESS OF FACILITY (IF		(914)677-3939
	•	•
LOCATION OF PROJECT		N/CITY/VILLAGE UTM COORDINATES Shington/V-Millbrook
DESCRIPTION OF PROJECT/FACILITY Extend existing water	supply and distribution mains of	of the village of Millbrook
1,500 feet into a new	service area and to take a supp	ply of water for use in 7 single
family homes in amoun	ts up to 4,320 gallons per day i	rom existing sources.
,	GENERAL CONDITIONS	
	ee of this permit, the permittee agrees that the permit i L, all applicable regulations and the conditions sp	
work at least 48 hours in advance of 2. The permitted work shall be subject to in	the time of commencement and shall also notify him/her pr	esignated in the special conditions, a notice of intention to comme comptly in writing of the completion of the work. of Environmental Conservation which may order the work suspende
		or all damages, direct or indirect, of whatever nature, and by whome State from suits, actions, damages and costs of every name and desc
<ol> <li>The Department reserves the right to n         <ul> <li>a) the scope of the project is exceed</li> <li>b) the permit was obtained by misr</li> </ul> </li> </ol>	nodify, suspend or revoke this permit at any time after due ded or a violation of any condition of the permit or provise perseentation or failure to disclose relevent facts; or	ions of the ECL and pertinent regulations are found; or
<ol> <li>The permittee is responsible for keeping by the Department, no later than 30 d.</li> <li>This permit shall not be construed as co</li> </ol>	ays (180 days for SPDES or Solid or Hazarduous Waste Ma inveying to the applicant any right to trespass upon the land:	ng any forms, fees or supplemental information which may be requinagement permits) prior to the expiration date.  To interfere with the riparian rights of others in order to perform
7. The permittee is responsible for obtain 8. Issuance of this permit by the Departme	ing any other permits, approvals, lands, easements and righ	or rescind an order on consent or determination by the Commission
	d by the Department must be in writing and attached heret	o.
	RMIT ADMINISTRATOR ADDRESS Willaam E. Steidle	; 21 South Putt Corners Road New Paltz, New York 12561
AUTHORIZED SIGNATURE X	July Jon	Page 1 of2

#### 95-20-6(10/90)-25c R3

DEC PERMIT NUMBER 3-1358-00032/00002

FACILITY/PROGRAM NUMBER(s) WSA# 9675

#### NEW YORK STATE DEPARTMENT OF ENVIRONMENTAL CONSERVATION



# PERMIT Under the Environmental Conservation Law (ECL)

EFFECTIVE DATE September & , 1999	. <u>-</u>
EXPIRATION DATE None	

				ļ	
	TYPE OF PERMIT (Check All App  Mew   Renewal	•	Permit to Construct	Permit to Operate	
	Article 15, Title 5: Protection of Waters	Article 17 SPDES	, Titles 7, 8:		Article 27, Title 9; 6NYCRR 373: Hazardous Waste Management
X	Article 15, Title 15: Water Supply	Article 19 Air Polluti	on Control		Article 34: Coastal Erosion Management
	Article 15, Title 15; Water Transport	Article 23 Mined Lar	Title 27: nd Reclamation		Article 36: Toodplain Management
	Article 15, Title 15; Long Island Wells	Article 24 Freshwate	: er Wetlands		Articles 1, 3, 17, 19, 27, 37; 6NYCF 880: Radiation Control
	Article 15, Title 27: Wild, Scenic & Recreational F	Article 25 Tidal Wet	lands		Other
	6NYCRR 608; Water Quality Certification	Article 27 Solid Was	, Title 7; 6NYCRR 360 ste Management	):	
Villag	issued to ge of Millbrook	,			TELEPHONE NUMBER (914) 677-3939
	ss of Permittee tt Avenue, Milibrook NY 1	2545			
ONTAC	CT PERSON FOR PERMITTED WORK				TELEPHONE NUMBER
IAME A	or Gary Ciferri no address of project/facility ne Water Supply – infiltratio	on gallery		<del></del> .	
OCATIO	ON OF PROJECT/FACILITY		·		
	Route 44 near Bangall Ro	pad and the Mill Brook	1	10.10	
rrkuo: 1otuc		ington/V/Millbrook	H-101-21-9 MI		NYTM COORDINATES  E: N: 4
ake	пом, ог аитновиzed аститу an additional supply of w. city of the system by up to				

permit.

DEPUTY PERMIT ADMINISTRATOR	ADDRESS	
Alexander F. Ciesluk, Jr.	21 South Putt Corners Rd., New Paltz NY 12561	rs afc
AUTHORIZED SIGNATURE Clerkonder F. Czeslick	Date 9/8/99	Page 1 of 5

#### NOTIFICATION OF OTHER PERMITTEE OBLIGATIONS

## Item A: Permittee Accepts Legal Responsibility and Agrees to Indemnification

The permittee expressly agrees to indemnify and hold harmless the Department of Environmental Conservation of the State of New York, its representatives, employees, agents, and assigns for all claims, suits, actions, damages, and costs of every name and description, arising out of or resulting from the permittee's undertaking of activities or operation and maintenance of the facility or facilities authorized by the permit in compliance or non-compliance with the terms and conditions of the permit.

#### Item B: Permittee's Contractors to Comply with Permit

The permittee is responsible for informing its independent contractors, employees, agents and assigns of their responsibility to comply with this permit, including all special conditions while acting as the permittee's agent with respect to the permitted activities, and such persons shall be subject to the same sanctions for violations of the Environmental Conservation Law as those prescribed for the permittee.

#### Item C: Permittee Responsible for Obtaining Other Required Permits

The permittee is responsible for obtaining any other permits, approvals, lands, easements and rights-of-way that may be required to carry out the activities that are authorized by this permit.

#### Item D: No Right to Trespass or Interfere with Riparian Rights

This permit does not convey to the permittee any right to trespass upon the lands or interfere with the riparian rights of others in order to perform the permitted work nor does it authorize the impairment of any rights, title, or interest in real or personal property held or vested in a person not a party to the permit.

#### **GENERAL CONDITIONS**

#### General Condition 1: Facility Inspection by the Department

The permitted site or facility, including relevant records, is subject to inspection at reasonable hours and intervals by an authorized representative of the Department of Environmental Conservation (the Department) to determine whether the permittee is complying with this permit and the ECL. Such representative may order the work suspended pursuant to ECL 71-0301 and SAPA 401(3).

The permittee shall provide a person to accompany the Department's representative during an inspection to the permit area when requested by the Department.

A copy of this permit, including all referenced maps, drawings and special conditions, must be available for inspection by the Department at all times at the project site or facility. Failure to produce a copy of the permit upon request by a Department representative is a violation of this permit.

## General Condition 2: Relationship of this Permit to Other Department Orders and Determinations

Unless expressly provided for by the Department, issuance of this permit does not modify, supersede or rescind any order or determination previously issued by the Department or any of the terms, conditions or requirements contained in such order or determination.

#### General Condition 3: Applications for Permit Renewals or Modifications

The permittee must submit a separate written application to the Department for renewal, modification or transfer of this permit. Such application must include any forms or supplemental information the Department requires. Any renewal, modification or transfer granted by the Department must be in writing.

The permittee must submit a renewal application at least:

- a) 180 days before expiration of permits for State Pollutant Discharge Elimination System (SPDES), Hazardous Waste Management Facilities (HWMF), major Air Pollution Control (APC) and Solid Waste Management Facilities (SWMF); and
- b) 30 days before expiration of all other permit types.

Submission of applications for permit renewal or modification are to be submitted to:

NYSDEC Regional Permit Administrator, Region 3

21 South Putt Corners Rd., New Paltz, NY 12561, telephone: (914) 256-3042

#### General Condition 4: Permit Modifications, Suspensions and Revocations by the Department

The Department reserves the right to modify, suspend or revoke this permit. The grounds for modification, suspension or revocation include:

- a) the scope of the permitted activity is exceeded or a violation of any condition of the permit or provisions
  of the ECL and pertinent regulations is found;
- b) the permit was obtained by misrepresentation or failure to disclose relevant facts:
- c) new material information is discovered; or
- d) environmental conditions, relevant technology, or applicable law or regulation have materially changed since the permit was issued.

DEC PERMIT NUMBER 3-5128-00032/00002

9/8/99

PAGE 2 OF 5

#### ADDITIONAL GENERAL CONDITIONS FOR ARTICLE 15, TITLE 15 (Water Supply)

9. Prior to starting work on any construction authorized herein, detailed plans of the structures proposed to be built and specifications for such work shall have been submitted to and approved by the Department. Thereafter such construction work shall be entirely completed in full accordance with the plans and specifications which have been submitted and approved. NOTE: Approval by this Department of final plans and specifications, and of completed works, will not be issued until equivalent approvals have been issued by the NYS Department of Health.

é

10. Section 15-1529 of the Environmental Conservation Law forbids

the operation of any of these works until, as constructed, they have been approved by the Department. Such final approval will be given only on written request. In general, such approval will not be given until all provisions affecting quality of the water and safety of the works have been complied with in full.

11. The Department reserves the right to rescind this permit or to take whatever action it may deem suitable and proper if the works authorized to be constructed herein are not initiated by

#### SPECIAL CONDITIONS

- 1. The taking of water by the village from the infiltration gallery approved under this permit is limited to a maximum of 83,520 gallons per day.
- 2. The construction of the infiltration gallery system and connecting water line shall be done in accordance with the plans, sheets 1 and 2 prepared by The Chazen Companies and dated March 9, 1998 and June 22, 1999, and last revised August 6, 1999.
- 3. All the property owned by the permittee that is associated with this water supply shall be protected and controlled in order to prevent pollution of the ground or groundwater.
- 4. This area shall further be protected from pollution by surface waters originating outside thereof by the construction of suitable diversion ditches or embankments and the development of the water sources shall be so carried out that there shall be no opportunity for pollution entering the water sources.
- 5. The physical pumping facilities and controls shall be protected against damage or tampering either by a fence or other suitable enclosure or by their manner of construction and installation.
- 6. Before any water from the infiltration gallery authorized under this permit may be used for any purpose, the applicant shall have caused a sample of the water from this source to be collected and analyzed, shall have submitted the results of such analyses to the New York State Department of Health in Albany and shall have been advised by that Department either that the water is of a satisfactory sanitary quality or that certain specified treatment or purification thereof is necessary. In this last case such water shall be used only after full compliance with all of the requirements of that Department.
- 7. The Department reserves the right to require the taking of further sanitary precautions or the further treatment or purification of the water from this source should conditions in the future indicate a need for such action.
- 8. Nothing contained herein shall be held to authorize the permittee to distribute water to any other district or service area which has not already been approved by the Department or its predecessors without having received a further permit from the Department.
- 9. Provisions shall be made to minimize erosion during the construction of the project and to prevent increased sedimentation in any water body on or adjacent to the project.

DEC PERMIT NUMBER		
3-1358-00032/00002		
PROGRAM/FACILITY NUMBER	7	
WSA# 9675	9/8/99	
<u> </u>	TO THE PARTY OF TH	PAGE 3 OF 5



#### SPECIAL CONDITIONS

#### For Article 15 (Water Supply)

- 10. Water used for disinfecting mains, if discharged to area streams, must have a chlorine residual not exceeding 0.05 mg/l at point of discharge.
- 11. The permittee is hereby prohibited from developing any new sources of water, replacement sources of water, or increasing the pumping rate from existing sources above the levels approved in this permit, without first obtaining a Water Supply permit from this Department.
- 12. The permittee must install a water meter on any new service connection prior to supplying water to that connection. A new service connection means a permanent water service drawing from the permittee's water distribution system, after the issuance date of this permit, and which has had no previous water service from a water purveyor.
- 13. By no later than five years from the issuance date of this permit, the permittee must have meters installed on all existing and new service connections.
- 14. At least once every ten years, the permittee must have all its water meters calibrated for accuracy according to AWWA standards.
- 15. At least once every three years, the permittee must conduct a leak detection program that covers the permittee's entire water distribution system.
- 16. The permittee must repair each leak within one month of the leak having been detected.
- 17. The permittee must maintain records of annual metered water production and consumption. The data in these records must be tabulated according to a system that can be used to identify the water demand by consumption category. Consumption category includes residential, commercial, industrial, public/governmental and institutional accounts. The records must be maintained for at least ten years.
- 18. Prior to water service for a newly constructed building, the permittee must obtain proof that only approved plumbing fixtures, defined in ECL 15-0314, were used. Such proof must be in the form of a building inspector report.
- 19. A minimum water pressure of 20 pounds per square inch shall be provided to customers at all times. An auxiliary source of power shall be provided to assure continued operation of the water supply during periods of electrical power failure.

DEC PERMIT NUMBER  3-1358-00032/00002		đ
FACILITY ID NUMBER	PROGRAM NUMBER	Page 4 of 5
WSA# 9675		1 490 . 0. 0



# SPECIAL CONDITIONS

## For Article 15 (Water Supply)

- 20. An alarm system shall be provided with automatic signaling apparatus which will report when primary source equipment malfunctions
- 21. The permittee must provide the Department with any records required by this permit within two weeks of a written request for such records by this Department.

# STATE ENVIRONMENTAL QUALITY REVIEW

Under the State Environmental Quality Review Act (SEQR), the project associated with this permit is classified as an Unlisted Action and the Department of Environmental Conservation (DEC) has determined that it will not have a significant effect on the environment. Other involved agencies may reach an independent determination of environmental significance for this project.

#### Distribution:

- J. Marcogliese/D. lyekekpolor
- G. Behn (3504)
- J. Dunn, NYSDOH

Dutchess Co. Health Dept.

J. Bodendorf, Chazen Companies



DEC PERMIT	NUMBER
------------	--------

3-1358-00032/00002

9/8/99

FACILITY ID NUMBER

WSA# 9675


PROGRAM NUMBER

Page 5 of 5

# APPENDIX - B

			_

# APPENDIX - B



# Water Systems Operation Report

Burea	u of Public W	ater Supply Pro						For Sysie	ems that freat	with Childrine at	nd/ or Ultraviole	L Natiation	
Public Water System Name						Reporting Month/Year Date Report Submitted				Source Type (s)			
Village of Millbrook							2 0 1 1 V V V V	<u>02/09</u> MM_DD	/ <u>2 0 1 1</u> Y Y Y Y	urchase with	Bround subsequent chlorin t subsequent chlori		
npile	Water System I	D	*************	.per +1pre+p>esriedper	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	M M		County		Town, Village or	City		
۷Y	<u>1</u> <u>3</u>	0 2 7	<u>7 0</u>					Dutch	ness		Millbrool	<	
_				Cl	niorination			Ultr	aviolet Radiation	on / Other Treat	ment		
		T	Ga	seous	Llquid						1		
DATE	Source (s) In Use	Treated Water Volume (1,000 gallons/day)	Cylinder Weight	Chlorina Use (Lbs. /Day)	Hypochlorile added to crock (Gallons )	Free Chlorine Residual (mg/l)	UV Unit Active (Yes/No)	Intensity Meter >70%	Sodium Hydro used (gallor		C-9 used (gallons)	A CONTROL OF THE CONT	
1		150.0		<del></del>		1.2			3.0	7.8	1.5		
2	-	295.0				1.1			5.3	7.8	1.8		
3		145,0			10.0	1.1			3.0	7.6	· 1.8		
4		170.0				1.7			6.8	7.8	1.8	ļ	
Б		250.0	<u> </u>			1.0			5.3	7.3	2,4		
6		150.0	ļ		20,0	1.8			2.6	7.9	1.8		
7		305.0	ļ	ļ		1.9	<u>.</u>		2.6	7.6	3		
8		115.0		[		2.0			3.8	7.4	2.4 1.8		
9		145.0	<del> </del>	<u> </u>		2,0	<del> </del>		3.0	7.8	2.4		
10		175.0	-			1.0			5.3	7.5	3		
11		240.0	<del> </del>		<del></del>	1.0			3.0	7.8	0.6		
12		145.0 180.0	-		15.0	0,5			4.5	7.7	2.1		
13 14		240.0		<b></b>	1000	1.6			4.1	7.7	1,5		
15		220,0	1			1.4			5.6	7.4	2.4		
16		235,0	1	,		1.0			4.6	7.7	1.8		
17		230,0				0.5			3.8	7.8	1.2		
18		265,0			10.0	0.6			7.1	7.8	3		
19		160.0	ļ	ļ		2.0			3.9	7.9	1.2		
20		250.0	<del> </del>	ļ		1.8			3.3	7.7	2.4	<u> </u>	
21		190,0	<del> </del>		12.0	1.0			7.1 4.5	7.3	2.1		
22_		185,0	<del> </del>			9,9			4.6	7.7	3.6		
23		250.0 225.0	1	<del> </del>		1.0		*	4.6	8.0	2.4		
24 25		215,0	1			1.4	<u> </u>	<u> </u>	4.6	7.9	2.1		
25 26		320.0	<u> </u>			0.9			7.5	7.7	3.3		
27		215.0				0.8			3.9	7.6	2,4		
28		230.0				1.9			5.6	7.3	2,4	ļ	
25		225,0				0.9			5.6	7.8	2.1	<b></b>	
30		310.0	<u> </u>			0,9			5.2	7.9	3.3		
31		195,0	m		15.0	0.7	<u> </u>	ļ	3.9	7.8	1.8	<del> </del>	
atel		6645.0		1	82.0		<del>1</del>	-	141.5 4.72	·	67.5 2,25	<del> </del>	
	rine Mix Ratio		30 Scott I		ons/ of	1.2	12 Title	% chlorine adde	ed to	30 Certification N	gallons of v	vater in crock	
cepc	эпеа ру:		DCOIL I	E. Osborn			1466	TICE COOKURIAMI		JOI BIJOGBOTT I			
	nature:						Date	2/9/2011		Operator Grad	la Lavale .	IIA	

DOH 360CUV pg. 1 of 2 (9/04)

TATACTONIONOSICA	i Sampies an	d rree Ch	iintine t	cesiquai		
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	Population Served: 2,100  Number of microbiological monitoring samples required: 2
Stewarts	1/19/2011	1	∐Yes ☑No	Oves 12%	0.8	
Highway Garage	1/24/2011	1	∐Yes ☑No	Dyes 121%	· 1,3	Did an M&R violation occur?
			□res. □No	□res □w		If "Yes," check reason (s) below:
			□Ves □Ma	Dies Du		Did not collect/analyze repeat sample.
Wandari Maria						Did not collect/analyze for E. coll for positive total colliform from multine/repeat sample.
_			DYes DVo	∏Yes ∏No		Did an MCL violation occur?
Parameter and the second secon			□Yes □No	□/es □‰		If "Yes," check reason(s) below (see also Part 5, Table 6 for
Number of microbiological monitoring samples required:   Stewarts   1/19/2011   1				For systems collecting less than 40 samples per month: two or more of the samples (routine and for repeat) are positive for total coliform (= total coliform		
	Sample Location  Date of Sample  2. Report  1. Food Direct 2. Report  1. Close Dec Direct 2. Direct 2. Direct 3. Report  1. Close Dec Direct 4. Report  1. Report					
			□Y≈ □1/0	□Yes □Vo		
			□Yes □No	□res □vo		The original sample was E coll positive and at least 1 repeat sample was
			Dves Dvo	∐Yes ∐No		positive for total coliform ( = <u>E.coli MCI. viplation</u> ).
	(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(1)(		□Yes □Na	Dres Dvo		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
à			□Yes □No	⊡Yes □No		
			□Yes □No	∐Yes <u>No</u>		As required by S-1.72. "Operation of a Public Water System," a copy of this
	And the second s		□Yes □No	∐Yes ∐No		form shall be sent to your local health department by the 10th calendar day
			[]/es []¥o	□Yes □Vo		·
			□Yes □No	∐ke □‰		
			∐Yes ∭No	□yes □v∘		,
Name of NYSDOH Certifi	ied Laboratory:	,				
Did an emergency or low No	pressure problem o	ceur? Did sour	ce water byj	pass an existi	ng treatment process in	n the system? If so, please explain.
		_ <del></del>				
Comments: GWUD! testin	g ongoing. Shoveled s	now from fire hyd	iranis through	out system.		
		····		·		

# Water Systems Operation Report

Burea	u of Public W	ater Supply Pro	etection		************************	·					and/ or Ultraviol	
Public Water System Name						Reporting	Month/Year	Date Report Su	Surface	Source Type (s	□ SWUDI	
	,	Village of	Millbr	ook		02/	2 0 1 1	03/09	/ <u>2 0 1 1</u>	Purchase with	ı subsequent chlorir	ation
				arareades ( ) DDL máreo I H	g/ppy hbbh4dh herennygenghheimen i jug	MM	YYYY	MM DD	YYYY		ut subsequent chlor	iusnon
ublic '	Water System II	Ò						County		Town, Village o	r City	
VΥ	<u>1</u> <u>3</u>	<u>0</u> <u>2</u> <u>7</u>	<u>7</u> <u>0</u>					Dutch	ness		Millbroo	k
				CI	nlorination		· · · · · · · · · · · · · · · · · · ·	Ultr	aviolet Radiation	on / Other Tre	atment	
- 1		Treated Water	Ga	seous	Liquid							
DATE	Source (s) In Use	Volume (1,000 gallons/day)	Cylinder Weight	Chlorine Use (Lbs. /Day)	Hypochloite added	Free Chlorine Residual (mg/l)	UV Unit Active (Yes/No)	Intensity Meter >70%	Sodium Hydro used (gallor		C-9 used (gallons)	
1		145.0				1.2			3,3	7.6	1.5	
2		320.0	<b>T</b>			1.1			8.3	7.4	3.3	1
3		115.0				1.1			2.3	7,6	1.2	<u> </u>
4		265.0			10,0	1.5			3.8	7.6	3	<del> </del>
5		250.0				1.2			6.5	7.9	3	<del></del>
6		190,0	<u></u>			1.5			2.3	8.2	1,8 1.8	
7		160.0	ļ		10,0	1.1			2.6 7.5	7.8	4,2	+
8		270,0	-			1.2		<del></del>	3.9	8.0	1.8	
9		270.0	<del>-</del>	<del> </del>		1.7			3.3	8.0	1.8	
10		175.0	<del> </del>	<del> </del>	800	1.8	· · · · · · · · · · · · · · · · · · ·		9.8	8.1	3	
11		328,0	┼	<del> </del>	20,0	1.7			0.3	7.8	1.2	
12		125.0 330.0	+	ļ		1.5			4.6	7.9	3.3	
13		125.0	<del>                                     </del>			1,4			4.6	6.7	2.1	
15		260,0		<del> </del>	ł	1.0			4.6	8.0	1.8	<u> </u>
16		180.0	1			1.2			2,6	8.0	2.4	
17		220.0				1.0	,		3.3	7.9	1.8	
18		205.0			15,0	1.0			4.6	7.3	2,4	<u> </u>
19		200.0				1.0			3.4	7.2	2.4	
20		195,0	<u> </u>			1.4			4.1	7.7	1.8	-
21		175.0	ļ	ļ		1,1			4.2	7.8	2.4 1.2	
22		175.0	<del> </del>	<b></b>		0,8	1		3.9 6.8	7.6	3	
23		270.0	<del> </del>	<b></b>	-15.0	0,6	<u> </u>	<del> </del>	3.8	8.0	1.8	
24		155.0	<del> </del>	ļ		1.7	<del> </del>	<u> </u>	5.6	8.0	2.4	
25		255.0	-	<del>  -</del> -		1.1			4.1	7.9	1.8	
25 27		195.0 336.0	1-	1	<u> </u>	1.0			7.1	7.8	3.6	
28		125.0	1	1	15.0	0.5			2.3	7.7	1.8	
29			<u> </u>	<del>                                     </del>								ļ
9D												1
31												
Total		6005.0			85.0		<u> </u>		123.5		63.6	
Aver,		214.5	Willi	3		1.2	<u> </u>		4.12		2.12	
Chlor	ine Mix Ratio	) R	30	Gall	ons/ of		12	% chlorine add	ed to	30	gallons of	water in crock
Repo	orted by:	<u> </u>	Scott	E, Osborn	ı <u>.</u>		Title	Area Coordinato	<u> </u>	Certification	Number:	NY003435

DOH 360CUV pg. 1 of 2 (9/04)

Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	Population Served: 2,100  Number of microbiological monitoring samples required: 2
15 Alden Acres	2/9/2011	1	□Yes ☑No	Dres ☑‰	1.0	Number of microbiological monitoring samples taken: 2
Library	2/15/2011	1	∐Yes ☑No	□Yes ☑No	0.9	Did an M&R violation occur?
			□res □vo	□res □No		If "Yes," check reason (s) below:  Actual number of samples is fewer than required.
			□Yes □No	□Yes □‰		Did not collect/analyze repeat sample.  Did not collect/analyze for Ε, coll for positive total colliform from routine/repeat sample.
····			□Yes □No	□Yes □No		Did an MCL violation occur?
		A CANADA	□Yes □No	□res □No		☐/es ☑No If "Yes," check reason(s) below (see also Part 5, Table 6 for
			□/es □vo	Dres Dvo		additional information).  For systems collecting less than 40 semples per month; two or more of the samples (routine and for repeat) are positive for total colliform (= total colliform)
			□Yes □No	□kez □‰		MCL violation).
			□Yes □No	□Yes □No		
	-		∐Yes ∏Va	□res □No		The original sample was E.coli positive and at least 1 repeat sample was
			Dyes Dyo	□res □vo		positive for total coliform (= <u>E.coli MCL violation</u> ).
			□Yes □No	□/es □No		Reminder: System must collect a minimum of five (5) routine microbiologics
			∐Yes ∏Wo	□/es □/ω		monitoring samples during the month following a repeat sample collection.
!	ar Andreas	-	□Yes □No	□Yes □No		1
	and the second		□Yes □No	∐Yes □No		As required by 5-1.72, "Operation of a Public Water System," a copy of thi form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			□res □vo	□res □‰		
			□res □No	□Yes □No	· · · · · · · · · · · · · · · · · · ·	
			□Yes □No	□Yes □No		
of NYSDOH Certin	Scott Osborn and Douglied Laboratory: 5	Smith Laboratory				
y MCL violation of	ceur? If so, please des	scribe: <u>h</u>	No			
emergency or low	pressure problem oc	car? Did sourc	ze water byp	oass an existin	g treatment process in	the system? If so, please explain.
					,	
ents: GWUDI testir	ig ongoing. Shoveled sr	norm from Ero bud				

# **Water Systems Operation Report**

Bure	au of Public W	ater Supply Pro	otection					For Syst	ems that Treat	with Chlorine ar	id/ or Ultraviole	Radiation	
Public Water System Name						Reporting	Month/Year	Date Report Su	ıbmitted	Source Type (s)			
•						ļ					Ground		
Village of Millbrook						03/	<u>2 0 1 1</u>	04/07	/ <u>2</u> <u>0</u> <u>1</u> <u>1</u>	. —	subsequent chlorina		
						мм	Y $Y$ $Y$ $Y$	MM DD	YYYY	Purchase w/out	subsequent chloring	lation	
Public Water System ID								County		Town, Village or (	City		
								D. d.			N ASSIL was del.		
NY <u>1 3 0 2 7 7 0</u>							Dutchess		Millbrook				
									·				
				Ci	hiorination			Uiti	raviolet Radiatio	on / Other Treat	ment		
		Treated Water	Ga	seous	) implied								
	Source (s)	Volume (1,000	<b> </b>	iseous Liquid		Free	UV Unit	Intensity Meter	Sodium Hydro	vida	C-9 used		
DATE	in Use	gailons/day)	Cylinder	Chlorine Use	Hypochlorite added	Chlorine Residual	Active	>70%	used (gallor		(gallons)		
			Weight	(Lbs. /Day)	to crock (Gallons )	(mg/l)	(Yes/No)	i			,	,,,,,	
			<u> </u>		<u> </u>	ļ <u></u>				7,9	2.4		
1		300.0	<u> </u>	<u> </u>	<u> </u>	1.5			4.1 3.8	7.3	1.2		
2		140.0		<u> </u>		1.5		i	2.9	8.0	0.9		
3		130.0 205.0	<del> </del>	<del> </del>	12.5	1.5			4.6	8.0	1.2		
4 5		205,0 155,0			15.3	1.3	<del>                                     </del>		3.3	7.9	1.2		
6		120.0	<u> </u>			1,2			1.3	7.9	0.6	<del></del>	
7		390.0				0,7			1.5	7.8	3.6		
6 B		150.0			12.0	1.0	-		1.9	8.4	2.1		
9		125.0				1.3	<u> </u>		4,1	8.2	2.1		
10		315.0				1.0			6,2	7.2	2.7	·	
31		165.0				1,1	ļ		2.3	8.4	1.8		
12		245.0	ļ			1.0			3.9	0.8	2.4		
13		170.0			<b></b>	1.0	<u> </u>		2,9	7.9	1.8		
14		150.0	<u> </u>		4.0	1.1			3.3	7.8	1.5		
15		270,6		<b> </b>	40.0	1.3			4.6 2.9	8.2 8.1	3 1.5		
18		\$60,0	-		20.0	1.4			2.9	8.0	1.5		
17		150,0	<del></del>	1		2.0 0,6			5.9	6.9	3		
18 19		295.0 110.0	<del> </del>			0.9			1.6	7.4	1.2		
20		145.0	1		<del></del>	0.9			2.3	7.5	1.8		
21		90.0	1		<del></del>	1.4			2.9	7.7	2.4		
22		325.0				0.5			6.5	7.8	3.6		
23		125.0			20.0	1.4			2.0	8.0	1.8	*****	
24		140.0				1.9			2.6	7.9	2.4		
25		280.0	ļ			2.0			4.2	7.9	1.8		
26		155.0	<u> </u>	ļ <u></u>	<u> </u>	1.7		<u> </u>	2.9	7.9	1.8		
27		145.0	<b>ļ</b>	<u> </u>		1.5		<u> </u>	2.6	7.9	1.8		
28	_	290,0				1.0	<del> </del>		4.6 1.3	7.2	3 1,2		
29		120.0 . 255.0		<del> </del>	20.0	0.9	<u> </u>	<del> </del>	4.6	7.9	2.4		
3D_			-	<u> </u>	20,0	2.0		<del></del>	2.0	7.9	1.2		
31 tal		100,0 5995.0		<b></b>	98,5		<del>                                     </del>		102.15		60.9		
er.		190.2			30.0	1.3	·		3.41		2.03		
-71-		100,2						the state of the s					
hlo	rine Mix Ratio	=	30	Gallo	ons/ of		12	% chlorine adde	ed to	30	gallons of wa	ater in crock	
epo	orted by:		Scott E	E. Osborn			Tifle	Area Coordinator		Certification Number: NY00			
Sign	nature:					·····	Date	4/7/2011	<del></del>	Operator Grad	e Level:	IIA	

DOH 350CUV pg. 1 of 2 (9/04)

Muccopiologica	r pampies am	u rree C	uorine r	residuai					
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	Population Served: 2,100  Number of microbiological monitoring samples required: 2			
Stewarts	3/9/2011	1	Dres ؉	□/es ☑No	0.7	Number of microbiological monitoring samples taken: 2			
WWTP Lab	3/14/2011	1	∐Yes ☑No	Dres ☑w	0.5	Did an M&R violation occur? ☐/es ☑No			
			□Yes □No	∐Yes ∐No		If "Yes," check reason (s) below:			
			D. C.			Actual number of samples is fewer than required. Did not collect/analyze repeat sample.			
			∏Yes ∏No	□res □w		Did not collect/analyze for E. coli for positive total coliform from routine/repeat sample.			
GENERAL STATE OF THE STATE OF T			∐Yes □No	□ke≥ □vo		Did an MCL violation occur?			
			□tes □to	□res □No		☐Yes ☑No If "Yes," check reason(s) below (see also Part 5, Table 6 for			
Walker of the Control			□Yes □No	□Nes □No		additional information).  For systems collecting less than 40 samples per month: two or more of the samples (routine and for repeat) are positive for total colliform (= total colliform			
			□res □No	□res □No		<u>MCL</u> viotation).			
			□res □vo	□Yes □No					
		,	□Yes □No	□res □vo		The original sample was Eucli positive and at least 1 repeal sample was			
				⊡res ⊡w		positive for total collform ( = <u>E. coll MCL violation</u> ),			
			∐Yes ∏vo	□Yes □No	·	Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.			
			Dyes Dw	□res □vo					
			□Yes □No	□Yes □No	·	As required by 5-1.72, "Operation of a Public Water System," a copy of this			
			DY≅ Dvo			form shall be sent to your local health department by the 10th calendar day of the next reporting period.			
	7730	To the last of the	□res □No	Dies Di∞					
	0000	900 <del>1</del> 100 1	□\es □\o	Dves Dvo					
-			∐res □vo	□Yes □No					
Sample Collector(s): Scott Osborn and Doug Bright  Name of NYSDOH Certified Laboratory: Smith Laboratory  Did any MCL violation occur? If so, please describe: No									
Did an emergency or low No	pressure problem a	ccur? Did som	rce water by	pass an existi	ng treatment process i	n the system? If so, please explain.			
Comments: GWUDI testir	ig ongoing. Repaired v	/ater break on 3/	15.						
					·				

# Water Systems Operation Report at with Chlorine and/ or Ultraviolet Radiation

uqrea	IL OF PUDIC VI	ater Supply Pro	Nection		Libert Di bir muytir bassana b						d/ or Ultraviole	i i i i i i i i i i i i i i i i i i i	
Public Water System Name						Reporting	Month/Year	Date Report Su	bmitted .	Source Type (s)			
•								10044	□Surface ☑ □Purchase with	Ground subsequent chlodr	Iduwa∐ noite		
Village of Millbrook						2011	0 5 / Q 9 M M D D	1 5 6 1 1 1	Purchase w/ou				
Public Water System ID						ММ	YYYY	County	3 4 1 1	Town, Village or			
ubiib	11000, 0301,111,1	,											
NY	<u>1</u> <u>3</u>	1 3 0 2 7 7 0						Dutchess			Millbroo	k 	
Chlorination					Ultraviolet Radiation / Other Treatment								
1	Source (s)	Treated Water	Gas	seous	Liquid								
DATE	In Use	Volume (1,000 gallons/day)	Cylinder Weight	Chlorina Use (Lbs. /Day)	Hypochlodie added to crook (Gallons)	Free Chiorne Residual (mg/l)	UV Unit Active (Yes/No)	Intensity Meter >70%	Sodium Hydro used (gallor		C-9 used (gallons)	,	
1		225.0				1,5			3.6	7.7	1.8		
2		135,0				1.3			2.3	7.7	1.8	ļ <u>-</u> -	
3		175.0				1.3		<u> </u>	2.0	7.7	1,2		
4		260.0				0.7			2.0	7.2	3	<u> </u>	
5		120,0	ļ			0.9			3.9 3.3	7.5 7.5	1.2		
B.		150,0	<del> </del>	<u> </u>	8,0	0.6			3.3 4.6	7.6	1.8		
7		255.0	<del> </del>	<del> </del>		0,7 1,3	i		2.6	7.8	1.8		
8		145.0 155.0	-	ļ		1.2			2.6	7.7	1.8		
9 10		295.0			-	1,2			4,9	. 7.7	3		
11		130.0			23.0	1.1			2.6	7.5	1.8		
12		200.0				1.5			3.6	7.8	1.8		
13		230,0				1.9			3.6	7.7	3		
14		145.0	<u> </u>	ļ <u> </u>		1.7			2.3	7.8	1.2		
15		195,0	<b></b>	<u> </u>		1.4			2.9 5.2	7.8	2,4		
16		245.0	ļ			1,3	·		3.4	7.7	1.2		
17		125.D	-		14,0	1.2 0.8			0.8	7.4	3		
18 19	·	225,0 140.0	-		14,0	1.6		1	1.1	7.7	1.2		
20.		200.0		<del> </del>		1.5			6.3	7.4	2.4		
21		215,0				1.8			4.2	7.6	1.8		
22		220.0			14.0	1.6			3.8	7.8	3.6		
23		200.0	<u> </u>			1.4		ļ	3.4	7.7	2.4	<u> </u>	
24		120,0	<u> </u>			1.4	<u></u>		1.9	7.8	1.2	<del></del>	
25		240.0	<del> </del>	ļ		1.1		<u> </u>	3.8	7.9 7.5	1.2	1	
28		145.0	<del> </del>	-		1.5			4.1	7.7	2.4		
27		210.0	<del>                                     </del>	<del> </del>	15.0	1.4			3.4	7.6	2.4		
28 29		205.0 275.0	1	<del>                                     </del>	15,0	2.0			4.9	7.9	2,4		
3D		180.0	<del>                                     </del>			1.6			1.9	7.8	1.8		
31												<u> </u>	
Totai		5760.0		1	74.0		1	<u> </u>	97.49		61.5		
Aver.		192.0		1	<u> </u>	1.3			3,25		2.05	<u></u>	
Chlorine Mix Ratio = 30 Gallons/ of				<del></del>	12 % chlorine added to		ed to	30 gallons of water in crock					
Repo	rted by:		Scott I	E. Osborn			Title	Area Coordinator	·	Certification N	lumber:	NY0034351	
Signature:							Date 5/9/2011			Operator Grade Level: IIA			

DOH 380CUV pg. 1 of 2 (9/04)

MICCODIOLOGICA	i Samples an	d Free Cr	ilorine l	Residual		
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E,coli Posilive	Free Chlorine Residual (mg/l)	
Library	4/5/2011	1	∐Yes ☑No	Ores 1214o	0.7	Number of microbiological monitoring samples required: 2
Highway garage	4/12/2011	1	⊡⁄es ☑‰	Dres ☑No	0.5	Number of microbiological monitoring samples taken: 2  Did an M&R violation occur?  Eles Elvo
				□Yes □No		If "Yes," check reason (s) below:
			□/es □No	□res □vo		Actual number of samples is fewer than required.  Did not collect/analyze repeat sample.  Did not collect/analyze for E. coli for positive total coliform from
			□Yes □%o	□res □no		outine/repeat sample.  Did an MCL violation occur?
			∐Yes ∏No	⊡Yes ⊡No		☐res ☐No  If "Yes," check reason(s) below (see also Part 5, Table 6 for
			□res □vo	□Yes □Vo		additional information).  For systems collecting less than 40 samples per month; two or more of the samples (routine and for repeat) are positive for total coliform. (** total coliform.)
			□Yes □Vo	⊡res ⊡vo		MCL violation). (" total collision   "total collisi
			□Yes □No	□Yes □No		
			□r'es □vo	□fes □No		The original sample was E.coli positive and at least 1 repeat sample was
	*		□/es □// ₀	De Do		positive for total coliform (= <u>E.coll M.C.L. violation</u> ).
			□res □‰	∐Yes ⊡vo		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
			□res □No	CMes DNo		monitoring samples during the month tollowing a repeat sample collection.
	Party Company		□Yes □No	□tes □N°		
			□yes □vo	□kes □‰	· · · · · · · · · · · · · · · · · · ·	As required by 5-1.72, "Operation of a Public Water System," a copy of this form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			□/es □\vo	□res □No		,
	-			□Yes □No		
		1	□Yes □vo	□Yes □No		
Sample Collector(s): <u>A</u> Name of NYSDOH Certifi  Did any MCL violation occ	ed Laboratory: <u>S</u>	Smith Laboratory	lo			
Did an emergency or low	pressure problem oc	cur? Did sourc	e water bvo	ass an existin	g tresiment process in	the system? If so, please explain.
Vo					O Pavaous ur	A DO PROBLE CAPITAIRE
			*****			
Comments: GWUDI testing	ongoing_		4			
	-					
						· ····

# Water Systems Operation Report at with Chlorine and/ or Ultraviolet Radiation

Burea	u of Public W	ater Supply Pro	ptection	14 174441114411 <del>1</del>	***************************************	0.11				Source Time Ist			
Publi	c Water Syst	em Name				Reporting	Month/Year	Date Report Su	ibmitted		Source Type (s		
	-	-	2 2401			1				burface	Ground	SWUDI	
		Village of	Milipi	OOK			2 0 1 1	06/09	/ 2 0 1 1		th subsequent chloric out subsequent chlor		
	the teachers		<b>,</b>	****************	d 81 (144 <del>051)14</del> W111 <del>14</del> W644 <del>144</del>	M M	YYYY	M M D D County	Y Y Y Y	Town, Village			
Public	Water System II	ם						County		LOWIT Assurage	A City		
NY	1 2	0 2 7	7 0					Dutcl	hess		Millbroo	k	
148 6	1 2	<u>v</u> <u>z</u> <u>r</u>	<u>,                                    </u>										
			T			_		1 L 11h	raviolet Radiatio	nz / Olber Tre	atment		
					nlorination				MAIOICE FEMALURE	717 Other 170		1	
	Source (s)	Treated Water	Ga	seous	Liquid	Free	UV Unit					ļ.	
	In Use	Volume (1,000		Chlorine		Chlorine	Active	Intensity Meter	Sodium Hydro		C-9 used		
DATE	1	gailons/day)	Cylinder Welght	Use	Hypochlorile added to creck (Gallons)	Residual (mg/l)	(Yes/No)	>70%	used (gallon	is)	(gallons)		
			l rogic	(Lbs. /Day)		(11,12)	(,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,						
1		155,0	<del> </del>			1.5			1.5	7.7	1.8		
2		170.0				0,9			3,8	7,3	1.8		
3		245.0	1		10,0	0.8			4.1	7.5	1.8		
4		150.0	1			1.0			0.8	7.5	1.8		
5		295,0				0,6			3.8	7.3	3.6		
6		215,0				0.7			4.5	7,0	2.4		
7		75.0				1.0			0.4	7.0	1.2		
8		225,0				0,9			4.9	7.2	3.6	<del> </del>	
9		225.0	1		20.0	1.0			2.6	7.2	1.2	ļ	
10		230.0		ļ	<u> </u>	2,0		<u> </u>	3,8	7.5	3		
11		270.0	ļ	ļ		2.0		·	5.3	7.3	2.4 1.8		
12		170.0	_		<u> </u>	2.0			2.3 4.6	7.8 7.6	3	<del> </del>	
13		315,0				1.0			2.6	7.5	1.8		
14		125.0	<del> </del>			1.0		<del>                                     </del>	3.4	7.8	2.4	1	
15		235.0		<del></del>		1.0		<del> </del>	3.8	7.2	2.4	<b>-</b>	
16		220.0			8.0	0.7			2.3	7,1	0,6		
17		135.0 295.0	<del> </del>	<del>                                     </del>		0.8			5.6	7.5	1.8		
18_		293.0 160,0		-		1.0			2,6	7.3			
19		320.0	-	<del>                                     </del>	20.0	0.6			0.8	7.2	2.4		
21		130.0	<del> </del>			1.0			1.9	7.5	1.2		
22		275.0				1.0			4.1	7.7	3		
23		130.0			18.0	1.4			2.6	7.2	1.8		
24		240.0				1.5			4.9	7.5	3	<u> </u>	
25		205.0				1.8			3.0	7.3			
26		175.0				1.0			5.3	7.3	3.6		
27		445.0		<u> </u>	10.0	2.0			8.3	7.8	4.8		
28		130.0	<b></b>	<u>'</u>		1.5			2.3	7.6		<del>                                     </del>	
29		215.0				1,3			3.8	7.7	3	<del>                                     </del>	
30		285,0	<b> </b>		<u> </u>	0.9		<u> </u>	6.8	7.0	0,3	1 -	
31	amenan	250.0	1	<b></b>		0.6	ļ		5.3 111.1	7.1	70.5	<del>                                     </del>	
Total		6690,0	WHIII	<b>}</b>	88.0		1		3.70		2.35	-	
Aver.		215.8	Million .	1	<u> </u>	1.1	i	1	3.10			_1	
Chio	rine Mix Ratio	=	30	Gall	ons/ of		12	% chlorine add	ed to	30	gallons of v	water in crock	
Repo	orted by:		Scott I	E. Osborn		·	Title	Area Coordinato		Certification Number: NY0034351			
Sig	nature:						Date	6/9/2011		Operator Gr	ade Level:	<u>IIA</u>	

		Sample Type	Total			Population Served: 1,450
Sample Location	Date of Sample	1.Routine 2.Repeat	Coliform Positive	E.cali Positive	Free Chlorine Residual (mg/l)	Number of microbiological monitoring samples required: 2
WWTP Bihrm	5/9/2011	1.	□Yes ☑Vo	□res ☑No	0.3	Number of microbiological monitoring samples taken: 2
Stewart's	5/24/2011	1	□res ☑ho	Ches (2No	0.9	Did an M&R violation occur?
-			Dies D\o	□re □vo		IF "Yes," check reason (s) below.  Actual number of samples is fewer than required.
***			□Yes □Vo	□/es □//o		Did not collect/analyze repeat sample.  Did not collect/analyze for E, coll for positive total collform from routine/repeat sample.
				□Yes □No		Did an MCL violation occur?
			∐res □No	□Yes □No		Lives Who If "Yes," check reason(s) below (see also Part 5, Table 6 for
			∐Yes ∐No	⊡r'es ⊡vo		additional information).  For systems collecting less than 40 samples per month: two or more of the samples (routine and for repeat) are positive for total collform. (= total col
			□res □to	□res □No		MCL violation).
			□res □No	□les □lo		
		0.00	∐Yes ∏Wo	D/≈ D/∞		The original sample was E.coli positive and at least 1 repeat sample was
			∐Yes ∐No	D∤es DNo		positive for total coliform ( = <u>E.coli MCL violation</u> ).
!			□ves □vo	□/cs □/vo		Reminder: System must collect a minimum of five (5) routine microbiolog monitoring samples during the month following a repeat sample collection
			□/es □/w	□Yes □No		
;			□Yes □No	□ves □vo		As required by S-1.72, "Operation of a Public Water System," a copy of t
			□Yes □No	□Yes □Wo		form shall be sent to your local health department by the 10th calendar d of the next reporting period.
			□Yes □No	Dres Dvo		
			⊡res (∏w	□Kez □No		
			Dres Dvo	∐Yes □No		
iple Collector(s):	Scott Osbom and Dou	g Bright	-			
	fied Laboratory:					
any MCL violation o	ccur? If so, please de	scribe; <u>t</u>	No			
					•	
an emergency or low					g treatment process in	the system? If so, please explain.
				· · · · · · · · · · · · · · · · · · ·	• • • • • • • • • • • • • • • • • • • •	
		~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~				
 				····		
ments: Finished GW	UDi testing on 5/9/11. Is	nstalled 2 new ga	te valves on f	Front St. Flushe	ed hydrants in system.	

Water Systems Operation Report at with Chlorine and/ or Ultraviolet Radiation

Bureau of Public Water Supply Protection								·		Treat with Chlorine and/ or Ultraviolet Radiation			
ubii	: Water Syst	em Name				Reporting	Month/Year	Date Report Su	bmitted	Source Type (s) Surface /Smooth SWUDI			
	,	Village of	Millbr	ook	•	<u>06</u> / MM	2 <u>0</u> <u>1</u> <u>1</u> Y Y Y Y	<u>0 7 / 0 7</u> M M D D	<i>i</i> <u>2</u> <u>0</u> <u>1</u> <u>1</u> Y Y Y Y	Burface✓ Purchase with s Purchase w/out		ation	
ublic	Water System II))	***************************************		erri (hissociada estrelaristada est	184 181	1 1 1	County		Town, Village or C			
NY	<u>1</u> <u>3</u>	<u>0</u> <u>2</u> <u>7</u>	<u>7 0</u>					Dutci	hess	Millbrook			
			1	Ci	nlorination			ulta	aviolet Radiatio	on / Other Treat	ment		
		Treated Water	Gas	seous	Liquid						,		
DATE	Source (s) In Use	Volume (1,000 gallons/day)	Cylinder Weight	Chlorine Use (Lbs. /Day)	Hypochlonie added to creck (Gallens)	Free Chlorine Residual (mg/l)	UV Unit Active (Yes/No)	Intensity Meter . >70%	Sodium Hydro used (gallor		C-9 used (gallons)		
1		230,0	 		10.0	0.7			0.8	7.4	3		
ż		315.0	 			1.0			3,8	7.2	4.2		
3		150.0				1.0			3.3	6.8	1.8_		
4		320.0				1.0			5.9	7.4	4.2		
5		150.0				1.0			1.3	7.6	1.8		
6		325.0			4,0	0.9			4.5	7.2	4.8		
7		190,0	<u> </u>			1,1		ļ. <u> </u>	3.9	7.0	1.8	<u> </u>	
8		285,0		<u> </u>		0.6	ļ		6.0	7.2	3.6		
9		10.0			15.0	1.4			6.0	7.3	3.6 1.2		
10		355,0	ļ			2.5		<u> </u>	3.6 2.3	7.8	1.8		
11		235.0	ļ <u> </u>	 -	j	2.0	<u> </u>	<u> </u>	2.6	7.6	1.2	 	
12		170.0	 	-		0.5	 -		3.9	7.0	3.6	 	
13		230.0	ļ	ļ	40.0	0.3	 		2.6	6.9	4.8		
-14		220.0	 -	 	10,0	0,2		-	3.8	6.8	1.8		
15		185.0 269.0	 			1.0			4.5	7.2	2.4		
16		215.0	 	<u> </u>		1,0	<u> </u>		2.3	7.2	2.4		
18		235.0	<u> </u>	 		1.1			2.3	7.4	2.4		
19		285.0	T			1.2			2.6	7.4	3		
28		180.0	1		10.0	1.0			4.5	6.5	1,2		
21		310.0				1.4	<u> </u>		4.6	7.0	4.2		
22		135.0			9.0	1.0			0.8	7.6	2.4		
23		200.0		ļ	5.0	1.4	ļ. <u>.</u>		5.3	7.0	2.4		
24		230.0	<u> </u>	<u> </u>		1.3	ļ <u></u>		4.9	7,2	2.4		
25		245,0	ļ	ļ		1.6	<u> </u>		4.2	7.5	2.4		
26		200,0	<u> </u>	 		1.4		1	2.9	7.7	1.2	 	
27		155.Q		 	15.0	1,2	 -		2.0 6.4	7.2	4.2	1	
28		305,0		 		1.0		 	3.4	7.0	1.2		
28		150,0	 	1	<u> </u>	1.0		 	4.5	7.0	1.8		
30		290.0	 	 		1,0							
31 Total		8765,0	William .	-	78.0		d	 	109		79.2		
Total Aver		225,5		1		1.1	1		3.63		2.64		
Aver. (///////) 225.5 (///////////////////////////////////					12	% chlorine add	ed to	30	gallons of v	rater in crock			
Repo	rted by:	·	Scott]	E, Osborn	·		Title	Area Coordinator		Certification N	lumber:	NY003435	
Signature:					Date	7/7/2011		Operator Grad		liΑ			

DOM 36000V pg, 1 of 2 (9/04)

Micropiologica	i Sampies an	d Free Cr	ilorine i	Residual		
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (rag/li)	
Highway Garage	6/7/2011	1	□Yes ☑Yo	□Yes ☑No	0,3	Number of microbiological monitoring samples required: 2 Number of microbiological monitoring samples taken: 2
Stewart's	6/21/2011	1	□Yes ☑No	□Yes ☑No	0,6	Number of microbiological monitoring samples taken: 2 2
			□res □w	□res □rio		If "Yes," check reason (s) below:
			∐Yes □No	□Yes □No		Actual number of samples is fewer than required, Did not collact/analyze repeat sample.
			□Yes □\u0	□res □v₀		Did not collectionalize for E. coll for positive total colliform from routine/repeat sample.
			∐Yes ∐Yo	Dres Dw		Did an MCL violation occur?
777723			□res □vo	□Yes □No		If "Yes," check reason(s) below (see also Part 5, Table 6 for additional information). For systems collecting less than 40 samples per month: two or more of the
	DD ddddddanas		□Yes □No			samples (routine and for repeat) are positive for total coliform (= total coliform MCI, violation).
			Dies Dio	□kes □ko		
			□Yes □No	Dies Dvo	Y STATE OF THE STA	The criginal sample was E.coii positive and at least 1 repeat sample was
			∐Yes ∐∖vo	_%= □%•		positive for total collium (= <u>E.coli MCt. violetion</u>).
			□ves □vo	□/es □/v ₀		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repezt sample collection.
- Control of the Cont			□Yes □No	□/es □/ ₀₀		g and a second s
			∐Yes ∐No	□Yes □No		
			□Yes □No	□(es □Na	ľ	As required by 5-1.72, "Operation of a Public Water System," a copy of this form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			DY≃s Dvo	□Yes □Wo		
and the state of t			□Yes □No	□res □vo		
And the state of t				⊡Yes □No		
Sample Collector(s): S Name of NYSDOH Certific Did any MCL violation occ	ed Laboratory: <u>'S</u>	mith Laboratory	ło			
	pressure problem oc	cur? Did sourc	e water byp	ass an existin	g treatment process in	the system? If so, please explain.
√o			<u>-</u>			
7					-	
Comments: Installed new c	blorine pumo		· · · · · · · · · · · · · · · · · · ·			
Trouble 1,000 O	and the beautiful					
	· · · · · · · · · · · · · · · · · · ·			, , , , , , , , , , , , , , , , , , , 		

Water Systems Operation Report at with Chlorine and/ or Ultraviolet Radiation

Burea	u of Public W	ater Supply Pro	tection							hat Treat with Chlorine and/ or Olfraviolet Radiauon			
ubli	c Water Syst	em Name		10.10d 41y-y-b) h1.16dff		Reporting	Month/Year	Date Report Su	ibmitted	Source Type (s) Surface (Viscound SWUDI			
					:						Ground subsequent chlorin		
		Village of	Millbr	ook			2 0 1 1	08/08	/ <u>2</u> <u>0</u> <u>1</u> <u>1</u>		subsequent chloriu it subsequent chlori		
					Måtsher 13 1450 PP (1544 % 2449 14445) .	MM	YYYY	M M D D County	YYYY	Town, Village or			
ublic	Water System I	D						County		roun, mage of			
. 13 /	4 5	0 2 7	7 N					Dutcl	hess		Millbrool	<	
NY	<u> </u>	0 2 7	7 0							Trimo. Got			
			T					1 114:	raviolet Radiation	n / Other Tres	tment		
			<u> </u>		lorination			O iii	aviolet i adiam				
1	Source (s)	Treated Water	Gat	seaus	<u>Liquid</u>	Free	UV Unit						
DATE	In Use	Volume (1,000 gallons/day)	Cylinder	Chlorine	Hypochlorile added	Chlorine Residual	Active	Intensity Meter >70%	Sodium Hydro used (gallor		C-9 used (gallons)	,	
			Weight	Use (Lbs. /Day)	to creck (Gallons)	(mg/l)	(Yes/No)	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		'	,		
			<u> </u>			·		-	7.5	6.9	3.6		
1		330.0	 		10.0	1.3			2.3	7.2	1.2		
2		120.0 150.0	 	 		1.4			4.5	7.4	3		
3 4		295.0	 			1.5			9.0	7.0	7,2	<u> </u>	
5		155,0			10.0	1.0			2.3	7.1	1.2.	<u> </u>	
6		300.0				1,6		<u> </u>	5.3	7.0	3		
7		170.0				1.3		ļ	4.8	6.5	0.8		
8		325.0	<u> </u>	ļ	10.0	1.0		ļ	8.1	6.9 7,2	3.6 2.5		
9		295,0	ļ <u>-</u>			1,2			2.3 3.9	7.0	1.2		
10		130.0			14.0	1,0 0,8			5.2	7.3	3.6		
11		300,0 165.0			<u> </u>	1.0			2.9	7.5	1.8		
12 13		215.0	+			1.3			7.2	6.7	2.4		
14		255,0	1			1.2			7.2	7.4	. 3		
15		295.0			- 10.0	0,9		<u> </u>	9.8	7,5	2.4		
16		275.0	ļ		ļ	1.2		<u> </u>	6.0	7.3	0 -		
17		220.0	 	ļ		1.4			6.8 7.5	7.3	2.4		
18		320.0	- 	 		1.2		<u> </u>	3.0	7.4	1.8		
19		195.0 320.0	+	<u> </u>	18,0	1.5			9.4	6.7	1.2		
20 21		200,0		 	10.0	1.6			4,6	7.1	1.8		
22		240.0	1			1.2			1.9	7.2	4.8		
23		400.0			5,0	1.5			12.0	6.9	4.2	<u> </u>	
24		150,0				1.2			3.0	7,3	0.9	 	
25		290,0	 	ļ	15,0	1,0	ļ	<u> </u>	5.9	7.3 6.7	1.8		
26		155.0		<u> </u>		20			3.8 6.8	7.4	3	1	
27		320,0	-	 		1.2		+	3.8	7.3	1,2		
28		145,0 310.0	+-	1	10.0	1.0		 	8.3	7,5	3.6		
29 30		205.0	1	 	10.0	0.8			5.3	7.7	1.2	<u> </u>	
31	- ·	265,0	T			1,5			7.8	7.2	2.4		
Total		7510.0		1	102,0		1		178.2		71.7		
Aver.		242.3	YIIIII	1]	1.2	<u> </u>	<u> </u>	5.94		2.39	.1	
Chlo	rine Mix Ratio) = 	30	Gall	ons/ of		12	_ % chlorine add	led to	30	gallons of	water in crock	
Ren	orted by:		Scott	E. Osborr	1		Title	Area Coordinato	r	Certification Number: NY0034351			
							Date	8/8/2011		Operator Gra	ade Level:	ΠA	
Sig	nature:	······································	······							•			

Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
villbrook Golf & Tennis Clubhouse	7/1/2011	1	□res ☑ko	□Yes ☑No	0.1	
Highway Garage	7/12/2011	1	□res ☑wo	□ves ⊡No	1.0	Number of microbiological monitoring samples taken: 2 Did an M&R violation occur?
			□Yes □‰	□Yes □No		If "Yes," check reason (s) below: Actual number of samples is sewer than required.
		,	□res □No	□Yes □No		Did not collect/analyze repeat sample, Did not collect/analyze for E, coll for positive total colliform from routine/repeat sample.
			Ofes On	□res □No		Did an MCL violation occur?
			□Yes □No	□Yes □Wo		☐ (See ☐ No ☐ Fig. 2 Page 2 Page 2 Page 2 Page 2 Page 2 Page 3 P
			□Yes □Vo	□Yes □Vo		additional information). For systems collecting tess than 40 samples per month: two or more of the samples (routine and /or repeat) are positive for total coliform (= total coli
			Over Div	D/s Dvo	,	MCL violation).
	**III	, "	Dies Dio	Dres Dvo		· .
			□kes □ko	Dres Dro		The original sample was E.coli positive and at least 1 repeat sample was
and the same of th			□Yes □No	□/es □/o	,,,,,,,,	positive for total cofform (= <u>Ecol MCL violation</u>).
A STATE OF THE STA		□res □to □res □to		Reminder. System must collect a minimum of five (5) routine microbiologic		
			□/es □//o	□Yes □No		monitoring samples during the month following a repeat sample collection
			∏fes ∏%	□Yes □No		As vacarized by \$1.02 (Co., and the party of
S. P. C.	The state of the s		Dres Dvo	□/e	4	As required by S-1.72, "Operation of a Public Water System," a copy of the form shall be sent to your local health department by the 10th calendar de of the next reporting period.
			□/es □\to	⊡res □No		•
			Dres D#	□Yes □No		
			DYes DNo	Dres Dvo		
mple Collector(s): <u>M</u> me of NYSDOH Certifie I any MCL violation occi	d Laboratory: S	mith Laboratory	ło		·	
an emergency or low p	ressure problem oc	cur? Did sourc	e water byp	ass an existîn	g treatment process in	the system? If so, please explain.

Water Systems Operation Report

Burea	Vater Supply Pro	otection			For Systems that Treat with Chlorine and/ or Ultraviolet Radiation							et Radiation			
Publi	c Water Sys	tem Name	àddici bennnenerebe		rysigan y fedd few residenci — i thi f le imet in	Reporting	з Мог	ith/Yea	ar	Date Report Su	ıbmitted			Source Type (s	
1	•											∏Surl		Ground	☐GWUDI
		Village of	Millbr	ook		<u>0</u> 8/	2	0 1	<u>1</u>	09108	/ <u>2</u> <u>0</u> <u>1</u> <u>1</u>			subsequent chlorit	
ļ	a parte piece soni l'Aimbé de Part vons	d-n-met-140444 1995 Electrobible 1 121 17 18	right of the second of the	njy100044221717FF0114P021	[Popp 61 plane 24 r landouw porter and r mail	MM	Υ	ΥY	Υ_		<u> </u>		,	subsequent chlor	Ination
Public	Water System I	D					County Town, Village or City								
NY	<u>1</u> <u>3</u>	<u>0</u> <u>2</u> <u>7</u>	<u>7 0</u>							Dutel	ness			Millbroo	k
				Ci	nlerination		T			Ultraviolet Radiation / Other Treatment					
].			Ga	seous	Lieuid										
DATE	Source (s) In Use	Treated Water Volume (1,000 gallons/day)	Cylinder Weight	Chlorine Use (Lbs. /Day)	Liquid Hypochlorite added to crock (Gallons)	Free Chlorine Residual (mg/l)		JV Un Active Yes/N)	Intensity Meter >70%	Sodium Hydro used (gallor		pН	C-9 used (gallons)	
1		175,0				0.7					3.6		7.7	1.2	
2		305,0				0,5	ļ				3,4		6.8	3.6	<u> </u>
3		160,0				0.6	ऻ—				4.6		6.8	1.2	
4		300.0	ļ		10.0	0.5	 -				7.5 2.0		7.0 7.7	2.4	
5		275.0				1,5	┿				8.1		6.7	3	
6		265.0 195.0	 		10.0	0,9 1.4	-				5.5		7.6	2.4	
8		190,0			10.0	1.6	 				1.3		7.8	1.2	
9		160,0				1,0					4.9		7.2	1.8	
10		285.0			10.0	0,5					7.1		7.1	3	
11		280.0				1.0					1.5		7.8	2.4	<u> </u>
12		285.0				1.0	<u> </u>			,	7.5		7.1	1.2	<u> </u>
13		200.0				1.0					5.5		6.8	1.8	-
14		210.0	 			1.0	-				6.4		7.2	2.4	<u> </u>
15		225.0	<u> </u>	<u> </u>	20.0	0.3	╀				5.2 2.6		7.7 7.8	2.4 1.8	
16		215.0				1.2	╁				6.8		7.0	1.8	
17 18		160,0				0.8	+				3.4		7.7	1.2	
19		365.0	 		10.0	0.9	 				4.5		7.7	3	
20		155.0	1			0.9					3.3		7.7	1.2	
21		220.0				0.9					10.4		7.7	5.4	
22		150.0				0.7	1				4.9		7.2	1.2	<u> </u>
23		390.0	<u> </u>			0.5	ļ				7.5		7.2	3	<u> </u>
24		160.0			10.0	0.7					2.6		7,5	1.8	<u> </u>
25		280,0	 		4	0.7	+-				9.1 5.2		7.5 7.7	2.4 1.2	
26		200.0	 	 	10.0	0,9	├				<u>5,∠</u>		7.6	1.4	
27	 -	0.0 295,0		<u> </u>		1.0	+				9.1		1.0	3	
29		340,0	 			0,5	\dagger				5.9		7.0	3.6	
30		155.0	1			0.8					4.9		7.1	1.2	
31		288,0			10.0	0.5					4.9		7.2	3	
Total		6923,0			90.0		1				158,91			67.8	<u></u> .
Aver.		223,3				0.9					5.30			2.26	<u> </u>
Chlorine Mix Ratio = 30 Gallons/ of							12			% chlorine adde	ed to	30		gallons of v	valer in crock
Repo	rted by:		Scott E	, Osborn		Title Area Coordinator Certification Number:			umber:	NY0034351					
Sign	Signature:						Date			9/8/2011		Opera	ator Grad	e Level:	IIA

DOH 360CUV pg. 1 of 2 (8/04)

MILLIONIONOSICA	i Sampies an	u rree Ci	rorme r	esiuuai		
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
2 Front St.	8/2/2011	1	□xes ☑No	D∕es ☑‰	0.4	Number of microbiological monitoring samples taken: 2
52 County House Rd	8/17/2011	1	□Yes ⊡Yo	□res ⊡vo	0.4	Did an M&R violation occur?
			∐res □No	□Yes □Vo		If "Yes," check reason (s) below:
			□Yes □No	□Yes □Vo		Actual number of samples is fewer than required. Did not collect/analyze repeat sample, Did not collect/analyze for E. coli for positive total coliform from
			DYes D√o	∐Yes ∐No		routine/repeat sample,
						Did an MCL violation occur? □Yes ☑No
			∐res ∏no	□Yes □No		If "Yes," check reason(s) below (see also Part 5, Table 6 for additional information).
			□res □vo	Oves □‰		For systems collecting less than 40 samples per month; two or more of the samples (routine and /or repeat) are positive for total coliform (= total coliform MCL violation).
			□fes □No	⊡Yes ⊡vo		<u>мы.</u> уюнациј.
	- A District Address		∐Yes □No	∐Yes ∐No		
	and the state of t		□Yes □No	□Yes □No		The original sample was E.coii positive and at least 1 repeat sample was
				□Yes □No		positive for total coliform (= <u>E.coli MCL violation</u>).
	The state of the s		□lres □vo	□Yes □No		Reminder: System must collect a minimum of five (5) routine microbiological
			∐Yes □No	□Yes □No		monitoring samples during the month following a repeat sample collection.
in the second se			□res □No	∐res (_ho		
			Dives Dvo	Dies Die		As required by 5-1.72, "Operation of a Public Water System," a copy of this form shall be sent to your local health department by the 10th calendar day of the next reporting period.
	American American		□Yes □‰	□Yes □No		, ,,
			□Yes □Yo	□ves □vo		·
			□/as □/w	□res □No		
Sample Collector(s): J Name of NYSDOH Certif Did any MCL violation oc	ied Laboratory:	Smith Leboratory	No			
			······································			
Did an emergency or low No	pressure problem or	ecur? Did sour	ce water by	oass an existir	ng treatment process in	n the system? If so, please explain.
						
Comments: Could not acco	ess plant on 8/28 due t	o flooding from f	ne Hurricane.			

Water Systems Operation Report

Bureau of Public Water Supply Protection							4 04	·		d Source Type (5)			
Publi	c Water Syst	em Name				Reporting	Month/Year	Date Report Su	ibmitted	Surface Source Type (s)			
		Village of	Millbi	ook	el bi bilatophilakonanya h ok olokkisos p	09 / MM	2 <u>0</u> <u>1</u> <u>1</u> Y Y Y Y	1 0 / 0 7 M M D D	/ <u>2 0 1 1</u> Y Y Y Y	Purchase with Purchase w/ou	subsequent chlor at subsequent chlo	ination	
ublic	Water System II	Ď						County		Town, Village or	City		
VΥ	<u>1</u> <u>3</u>	0 2 7	<u>7 0</u>			•		Dutcl	hess	Millbrook			
				Cł	olorination			Ultr	aviolet Radiatio	on / Other Trea	tment		
		Treated Water	Ga	SBOUS	Liquid								
DATE	Source (s) In Use	Volume (1,000 gallons/day)	Cylinder Weight	Chlorine Use (Lbs, /Day)	Hypochlorite added to crock (Gallons)	Free Chlorina Residual (mg/i)	UV Unit Active (Yes/No)	Intensity Meter >70%	Sodium Hydro used (gallor		C-9 used (gallons)	Charles Annual Victoria	
1		215.0				1.0			3.3	6.7	1.2		
2		250,0				1.1			2.0	6.9	2.4		
3		330,0			,	1,0			0.0	6.5	3		
4		130.0				0.9			0.0	6,5	2.8		
5		200.0			15.0	0.7			0.0	6.6	1.2		
6		240.0				8,0			0.0	6.5	3		
7		235.0			10.0	0.7			0.0	6.5	1.8		
8		210,0				0.9			0.0	6.7	0	<u> </u>	
9		210.0			10.0	1.2		<u> </u>	0.0	6.6	0,		
10		240.0	ļ			1.3	<u> </u>		0,0	6.6	0		
11		240,0	ļ <u>.</u>			1.2			0.0	6.5	0		
12		220.0	<u> </u>			1.7	<u> </u>		5.3	7.5	1.8	- 	
13		220,0			15.0	1.5			4.9	7.3	1.8	-	
14		240.0				1.7			4.9	6.8 7.3	1.8	1	
15		195.0	-			1.4			6.2 5.5	6.8	1.8	 	
16		265.0				1.6			2.6	7,3	2.4		
17		290.0 180.0				1.2			4.5	7.4	2.4		
18		240.0			20.0	1.2			6.0	7.1	2.4		
19 20		215,0			20.0	2.0			3.8	7.5	2.4		
21		205.0				2.0			6.2	7.5	1.2	 -	
22		240.Ó	 			1.5			5.5	6.7	2,4		
23		215.0			15,0	1.0			3.3	7.3	2.4		
24		230.0		-		1.8			6.8	7.6	1.2		
25		165.0			.,,	1.6			4.5	6.7	2.4		
26		0.008				1.1			3.8	7.4	1.8		
27		280.0				1.0			0.0	6.9	4.2		
28		255,0			15.0	1.4			6.8	6.7	2.4		
29		295.0				1,8			8.3	6.7	2.4		
30		240.0	ļ		20,0	1.6			6.2	7.4	1.8	ļ	
31	277777		,,,,,,,,,			mm	<u> </u>				ļ		
tal .					120.0				100.4		56.8	<u> </u>	
er.		233.0				1.3_		<u></u>	3.35		1.89	<u> </u>	
hlori	ne Mix Ratio	-	30	Gallo	ons/ of		12	% chlorine adds	ed to	30	gallons of	water in crock	
epoi	ted by:	·	Scott E	. Osborn			Title	Area Coordinator		Certification Number: NY003435			
Signature:						Operator Grade Level: IIA							

DOH 360CUV pg. 1 of 2 (9/04)

IVLICTODIOIOGICA	i pampies an	u rree Ch	dorine e	cesionar		
Sample Location	Date of Sample	Sample Type 1.Rouline 2.Repeal	Total Coliform Positive	E.coli Posllive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
17 Russell Knolls	9/7/2011	1	□res ☑No	□įres ⊠No	0.4	Number of microbiological monitoring samples taken: 2
15 Alden Acres	9/14/2011	1	Dies (Jivo	□res ☑vo	0.7	Did an M&R violation occur?
			□res □%	□/es □/vo		If "Yes," check reason (s) below:
				□Yes □No		Actual number of samples is fewer than required, Did not collect/analyze repeat sample, Did not collect/analyze for E, coll for positive total colliform from
		-				routine/repeat sample.
			□res □Vo	□/es □/vo		Did an MCL violation occur?
			□Yes □Vo	□kez □ko		
			□/es □‰	□Yes □No	·	additional information). For systems collecting less than 40 samples per month: two or more of thesamples (routine and /or repeat) are positive for total coliform (= total coliform
	"		∐Yes □No	∐Yes ⊡vo		MCL_vtotation).
			□Yes □No	⊡Yes □No		ι
			[]Yes □No	□res □No		The original sample was E.coli positive and at least 1 repeat sample was
			% <u></u> %	□Yes □No		positive for total coliform (= <u>E.coli MCL, violation</u>).
			□l⁄es □No	□res □w		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
			□res □ho	D/es D/∞		
			□Yes □No	∐Yes ∏v₀		As required by 5-1.72, "Operation of a Public Water System," a copy of this
			□Yes □No	□Yes □¥o		form shall be sent to your local health department by the 10th calendar day of the next reporting period.
	-		∐Yes ∐No	□;es □#•		
			Dres Dvo	□fes □No		
			∐Yes ∏Vo	□Yes □No		
Sample Collector(s):		ott Osborn Smith Laborator	/			
Did any MCL violation o	ecur? If so, please de	scribe:	No			
Did an emergency or low	r pressure problem o	ccur? Did sou	rce water by	pass an existi	ng treatment process i	n the system? If so, please explain.
				•		
Comments:						
· · · · · · · · · · · · · · · · · · ·						
						•

Water Systems Operation Report

Bureau of Public Water Supply Protection								rui Syste	For Systems that Treat with Chlorine and/ or Ultraviolet Radiation				
ubli	c Water Syst	em Name	- MINISTER 1 1 1 1 1 1 1 1 1	TO THE PERSON NAMED IN COLUMN	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	Reporting	Month/Year	Date Report St	ubmitted	Source Type (s)			
	,	Village of	Millbı	ook		10/ MM	2 0 1 1 Y Y Y Y	11/ <u>0</u> 7 M M D D		Purchase with	Ground subsequent chlor it subsequent chlor		
npile	Water System I	D	***************************************	**************************************	wood to the state of the state	194 191		County		Town, Village or	Cîty		
NY	<u>1</u> <u>3</u>	0 2 7	<u>7</u> <u>0</u>					Dutc	hess	Millbrook			
			<u> </u>	CI	niorination			<u>l</u> Ultr	aviolet Radiation	on / Other Trea	tment		
		Treated Water	Ga	seous	Liquid	1	-		[
DATE	Source (s) In Use	Volume (1,000 gallons/day)	Cylinder Weight	Chlorina Use (Lbs. /Day)	Hypochlorite added to crock (Gallons)	Free Chlorino Residual (mg/i)	UV Unit Active (Yes/No)	Intensity Meter >70%	Sodium Hydro used (gallor		C-9 used (gallons)		
1		255.0				1.4			6.4	7.2	2.4		
2		265,0				1,5			3.3	7.2	3		
3		330.0				1.4			9.0	6.5	3		
4		220.0			28.0	1.8			6,0	7.0	2.4		
5		365,0		<u> </u>		1.8			9.8	6.9	3	 	
6		170.0	<u> </u>		20,0	1.2	<u> </u>		3.3	7.4	2.4		
7		200,0	<u> </u>			1.2			1.6	7,4	0.6		
_B		255.0				1.2	ļ		6.5	7.3	2.4 3		
8		190,0			00.0	1.2			5,2 3,3	7.5	1.2	 	
10		255.0 155.0			20.0	2.0	<u> </u>		4.6	6.5	1.8		
12		275.0				1.8			6.5	7.4	2.4		
13		155.0				1.8			3.3	7.3	1.2		
14		315.0			10.0	1.7			8.8	7.2	2.4	· ·	
15		125.0				1.6	-		2.6	7.4	1.8		
16		170,0				1,6			3,6	7,5	1.8		
17		270.0				1,2			6.5	6.7	2.4		
18		155,0			15.0	1.8			4,6	7.4	1.8		
19	·····	460.0				2.2			3.9	7.3	4.2		
20		140.0	ļ			1.8			4.2	6.6	1.2		
21		210.0	ļ <u> </u>		15,0	1.7	 		5.5	7.1	1.8		
22		240.0				1,8			5.6	7.3	2.4		
23		170.0	<u> </u>			1.2			4.6 6.2	6.5	1.2 2.4	-	
24 25		245.0 230.0				1.3			2.9	7.3	2.4		
26		150.0			20.0	1.8			5.2	6.9	1.8		
27		210.0	<u> </u>			2.0			4.6	7.2	1,2		
28		220.0				1,6			4.9	7.2	2.4		
29		55.0				1.4			3.9	7.2	0,9		
30		270,0				1.2			6.2	7.2	2.7		
31		260.0			10.0	0.6			4.9	6.8	3		
otal		6985.0			130.0				157.5		66.6		
ver.		225.3				1.6	L		5.25		2.22		
Chlorine Mix Ratio = 30 Gallons/ of						12	% chlorine adde	ed to	30	gallons of	water in crocl		
Repo	rted by:		Scott E	. Osborn	*****	<u></u>	Title/	rea Coordinator	· · · · · · · · · · · · · · · · · · ·	Certification Number: NY0034351			
Signature:						Date	11/7/2011			le Level:	IJА		

DOH 3600UV pg. 1 of 2 (9/04)

Microbiologica	l Samples an	d Free Ch	dorine E	kesidual		
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
39 North Ave	10/11/2011	1	⊡∀es ⊡No	□res ☑No	0.4	Number of microbiological monitoring samples taken: 2
3272 Franklin Ave	10/18/2011	1	□Yes ☑No	∐res ☑Wo	1.1	Did an M&R violation occur?
			Dyes DNo	□Yes □No		If "Yes," check reason (s) below: Actual number of samples is fewer than required.
			□Yes □No	□Yes □Wo		Did not collect/analyze repeat sample. Did not collect/analyze for E. coll for positive total collicium from routine/repeat sample.
			□res □vo	□kez □Nº		Did an MCL violation occur?
			□Yes □No	□Yes □No		☐Yes ☑No If "Yes," check reason(s) below (see also Part 5, Table 6 for
			∐fes □No	□Yes □\vo		additional information). For systems collecting less than 40 samples per month; two or more of the samples (routine and for repeat) are positive for total coliform: (= total coliform
			□kes □Vo	∐Yes ∏vo		MCI, violation).
-		SALES AND SALES	□Yes , □Vo	∐Yes ∏No		<u></u>
	-		□⁄es □vo	□Yes □No		The original sample was E.coll positive and at least 1 repeat sample was
			□Yes □No	∐Yes ∏vo		positive for total coliform (= <u>E.coll MCL violation</u>).
			 	∐Yes ∏vo	_	Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
https://doi.org			∐Yes ∏No	□res □No		
			∐res □No	□kes □vo		As required by 5-1.72, "Operation of a Public Water System," a copy of this
	and the state of t		Dives Dvo	∐kes □ko		form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			□Yes □No	Dives Dw		,
		·	∐Yes ∏No	Dives Divo		
			□Yes □No	Dives Divo		
Sample Collector(s): 1 Name of NYSDOH Certif Did any MCL violation oc	led Laboratory:	Smith Laboratory	No			
		·····				
NT_	pressure problem o			pass an existin	ng treatment process in	1 the system? If so, please explain.
Comments: Power outage	during heavy snowsto	rm. Generator ra	n plant for 2 d	ays with no pro	oblems,	

Water Systems Operation Report

Bureau of Public Water Supply Protection								For Systems that Treat with Chlorine and/ or Ultraviolet Rad					
Publi	c Water Syst	tem Name		, <u>, , y,</u> a by in Laneix	***************************************	Reporting	Month/Year	Date Report St	ubmitted	Source Type (s)			
	•			_						Surface Ground GWUDI			
	,	Village of	Millib	ook		111	2011	12/09	/ <u>2</u> <u>0</u> <u>1</u> <u>1</u>		urchase with subsequent chlorination urchase w/out subsequent chlorination		
			144531507555547+7911	***************************************		MM	Y Y Y Y		YYYY			rination	
oi)du ^c	Water System I	Ď			_			County		Town, Village or I	City		
									-		R Milliana a	la.	
NY	<u>1</u> 3	<u>0</u> <u>2</u> <u>7</u>	<u>70</u>					Dutc	ness		Millbroo	K	
										<u> </u>			
			Ţ	Cł	niorination			Ultr	raviolet Radiatio	on / Other Treat	ment		
}			69	seous	Liquid	1	<u>. </u>	1				[
	Source (s)	Treated Water Volume (1,000			Liquiu	Free	UV Unit	Intensity Meter	Cadium Usdra	wide	C-9 used		
DATE	In Use	gallons/day)	Cylinder	Chlorine	Hypochlorite added	Chlorine Residual	Active	>70%	used (gallor	ns) pH	(gallons)	1	
			Weight	Use (Lbs. /Day)	to crock (Gallons)	(mg/l)	(Yes/No)	1 70%	1 2300 (9850)	~	(34)		
								ļ					
1		195.0				2.0			5.2	6.7	1		
2		155,0	<u> </u>	 	16.5	1.7	<u> </u>	 	5.5	7.2	1,5 2	 	
3		260,0	 -	 	10.0	1.8	 	 	9.5 6.8	7.5 6.9	1		
4		180,0	-			2.0	 	 	3.5	7.2	1	-	
5		150,0	-	 		1.8			7.5	7.4	2.5		
6 7		270.0 175.0	-		15,0	1.6			5.3	6.9	1.5		
В .		145.0	 		10.0	1,8			5.5	7.2	1.5		
9		290.0	 			1.5			7.5	7.0	1,5		
10		150,0				1.7			4.5	6.9	1.8		
11		295.0			15.0	1.7			0.5	7.5	2		
12	·····	160,0				1.6			13.5	7.5	1.5		
13		185.0				1.6	<u> </u>		6.8	7.4	1.5		
14		255.0				1.3			7.0	7.3	2.5		
15		150.0				1.5			3.0	7.5	1	 	
16		265,0	ļ			1.5	ļ		7.5	6.8	2		
17		170.0	ļ		20.0	1.3	<u> </u>	<u> </u>	6.0	7.5	1.5		
18		200,0	 	<u> </u>		1.6		 	3.5 5.2	7.6	1.5	<u> </u>	
19	· · · · · · · · · · · · · · · · · · ·	190.0	 			1.4			10.0	7.7	2	 	
20		265.0 175,0	1			1.0			4.0	7.2	1.25	-	
21 22		150.0	 		15,0	0,9	1		4.9	6.6	1.25		
23		260.0				0.8			11.5	7.0	2.5		
24		145.0	Ī			1.3			4.0	7.5	2		
25		195.0				1.2			6.5	6.6	1.8		
25		240.0				1.2			10.0	7.2	1.5	<u> </u>	
27		205,0				1.0			3.0	7.6	2.5		
28		255.0		<u> </u>		1.1		 	7.5	6.5	2.5		
29		35.0	<u> </u>		15.0	1,3	ļ <u></u> -		11.5	7.8	2.5	-	
30		205.0	 			2.0		<u> </u>	0.0	8.5	0	—	
31			11/1/11	 			 	 	186.53		49.6		
Fotal		5970.0			90,0		1	 	6.22		1,65		
ver		199.0		d	<u> </u>	1.5		J	1 0.24		1 1,00	. 1	
Chlor	rine Mix Ratio	, æ	30	Gallo	ons/ of		12	% chlorine add	ed to	30	gallons of	water in crock	
Repo	orted by:		Scott I	E. Osborn			Title	Area Coordinator	<u> </u>	Certification Number: NY0034351			
Sign	nature:	_ 		<u></u>			Date	12/9/2011	· · · · · · · · · · · · · · · · · · ·	Operator Grad	e Level:	IIA	

ĐOH 360CUV pg. 1 pf 2 (8/04)

Sample Location	Date of Sample	Sample Type 1.Roufine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	
3424 Franklin Ave	11/3/2011	1	□Yes ☑No	□res ☑No	1.7	Number of microbiological monitoring samples required: 2
10 Reservoir Dr	11/9/2011	1	□Yes ☑No	∐Yes ☑No	0.8	Number of microbiological monitoring samples taken: 2 Did an M&R violation occur? Kes Evo
			Dres Div		V.4	If "Yes," check reason (s) below:
						Actual number of samples is fewer than required, Did not collect/ansiyze repeat sample.
			∐Yes ∐Vo	□res □no		Did not collect/arralyze for E. coli for positive total coliform from routine/repeat sample.
			□Yes □No	⊡/es □40		Did an MCL violation occur?
		-	∐Yes □No	□Yes □\\		☐res ☐no If "Yes," check reason(s) below (see also Part 5, Table 6 for
			□/es □‰	□Yes □Vo		additional information). For systems collecting less than 40 samples per month: two or more of the samples (routine and for repeat) are positive for total collion.
	`		⊡Yes ⊡vo	□Yes □No		MCL violation).
			□Yes □No	⊡res □No	,	
en non non non non non non non non non n	A COLUMN A C		□res □vo	Dies Dire		The original sample was E.coli positive and at least 1 repeat sample was
			□Yes □No	∐/es <u> </u> /v₀		positive for total coliform (= <u>E.coli MCI, violation</u>).
			□res □no	□Yes □No		Reminder: System must collect a minimum of five (5) routine microbiological
			∏res □‰	_\@ □\@		monitoring samples during the month following a repeat sample collection.
			□Yes □No	□Ves □No		As required by 5-1.72, "Operation of a Public Water System," a copy of this
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	□xes □No	□Yes □No		form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			□res □Vo	□/es □/v₀		•
			Dies Die	□kez □nº		
		-		□Yes □No		
nmple Collector(s); <u>h</u>	ed Laboratory: 5	Smith Laboratory				
d any MCL violation oc	cur? If so, please des	eribe: <u>N</u>	ło			

d an emergency or low	pressure problem oc	cur? Did sourc	e water byp	ass an existin	g treatment process in	the system? If so, please explain.
* •						
mmenis:				······································		
	·					

Water Systems Operation Report

Bureau of Public Water Supply Protection								For Systems that Treat with Chlorine and/ or Ultraviolet Radiation					
Publi	c Water Sys	tem Name				Reporting	Month/Year	Date Report Su	ıbmitted	Source Type (s)			
		ren e	R ####	1 .							Ground	∭GWUDI	
		Village of	Millor	OOK			2011	01/09	12012		subsequent chlorin it subsequent chlori		
)	,,	***************************************		[+]=+===1+1+1+1+1+1+1+1+1+1+1+1+1+1+1+1+1	MM	YYYY		YYYY			(Iqubi)	
Public	Water System i	D						County		Town, Village or City			
NY	1 3	<u>0</u> <u>2</u> <u>7</u>	<u>7 0</u>		٠			Dutcl	hess	Millbrook			
			1	GI	niorination			l Ultr	aviolet Radiatio	on / Other Tres	tment		
			Ga	seous	Liquid	r						1	
DATE	Source (s) In Use	Treated Water Volume (1,000 gallons/day)	Cylinder Weight	Chlorine Use (Lbs. /Day)	Hypochlorite added	Free Chlorine Residual (mg/l)	UV Unit Active (Yes/No)	Intensity Meter >70%	Sodium Hydro used (gallor		C-9 used (gallons)		
1		320.0	-			0.4			15.0	6.7	4.8	ĺ	
2		295,0			10.0	1.6			9.1	6.7	2,4		
3		10.0	<u> </u>			1.4			0.5	7,2	0.2		
4		260,0				1.4			5,5	7.2	2.7		
5		215,0			1	1.1		<u> </u>	7.1	6.6	1.8	ļ	
6		230.0	ļ		<u> </u>	1.2	<u> </u>]	7.9	7.0	2.4	<u> </u>	
7		130.0	 			1.2		<u> </u>	4.5 3.8	7.6	- 1.2 2.4	1	
-8		140.0	 -		10.0	1.0			6.4	7.6	2.4		
9		260.0				0.8			6.2	7.6	1.8	-	
10		230,0 215.0	-			0.9			7.5	7.6	3		
11		240.0		 		1.2			7.8	7.1	2.4		
13		50,0				1.2			1.3	7.6	0.6		
14	***************************************	220.0				1.0			5.9	7.1	1.8	<u> </u>	
15		250.0			15.0	0.9			8.5	7.0	2.1	<u> </u>	
18		220.0				1.0		<u> </u>	6.8	7.7	2.1	 	
17		220.0	ļ			1,3			8.3	7.4	2.4		
18		135.0			 	1.0			4.6 3.3	7.8	1.8	-	
19	<u></u>	140.0	 		1	1.2	<u> </u>	 	8.6	7.0	2.4		
20		265 <u>,0</u> 230.0	 	 	 	1.0			6.4	7.7	1.8		
21 22		220,0	<u> </u>		15.0	1,2			8.3	7.5	2.4		
23		225,0	<u> </u>	<u> </u>		1.5			6.0	7.9	2.4		
24		240.0				1.4			8.3	7.7	1.2		
25		55,0				1.0			2.3	7.9	0.6		
26		215.0			ļ	1.1			3.8	7.9	2.1		
27		190.0	 			0.9			14.3	7,0	3.8	 	
28		275.0	 	 	-	2,0		 	0,7 2.1	8.5 6.5	1.2		
28	<u> </u>	185.0	 		,	0.3			2.6	7.8	1.2		
30		195.0	 	 		0.8			2.6	7.6	2.4	<u> </u>	
31 Total		250,0 6325,0	1111111	 	50.0	<i>Millio</i>			185.95		61.6		
		204.0			1	1.1			6.20		2,05		
	ine Mix Ratio		30	Gall	ons/ of		12	% chlorine add		30		vater in crock	
Repo	rted by:		Scott I	. Osborn	<u> </u>		Title	Area Coordinator	-	Certification l	Number:	NY0034351	
Sign	nature:						Date	1/9/2012		Operator Grad	de Level:	IIA, C, D	

DOH 360 CUV pg. 1 of 2 (9/04)

Mucioniologica	i Sampies an	urreetn	norme i	kesiduai		
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chiorine Residual (mg/l)	
3374 Franklin Ave	12/6/2011	1	□res ☑No	□res ☑wo	1,2	Number of microbiological monitoring samples required: 2 Number of microbiological monitoring samples taken: 2
3265 Franklin	12/13/2011	1	∐res ŪNo	∐Yes ☑Wo	0.4	Did an M&R violation occur? ☐Yes ☑No
				□Yes □No		If "Yes," check reason (s) below:
				D/cs D/v		Actual number of samples is fewer than required, Did not collect/analyze repeat sample, Did not collect/analyze for E. coli for positive total coliform from
			□Yes □Vo	□%es □%o		routine/repeat sample.
	***	A POST AND A STATE OF THE STATE	□Yes □Vo	_k≈ _k°		Did an MCL violation occur? ☐Mas ☑No If "Yes," check reason(s) below (see also Part 5, Table 6 for
AND			□/es □No	⊡≮es ⊡√o	***	additional information). For systems collecting less than 40 samples per month two or more of the
	an year		∐fes ∐No	□Yes □Vo		samples (rouline and for repeat) are positive for lotal coliform (= total coliform <u>MCL</u> , violation).
			□Yes □No	□res □No		
			Dves Dvo	□Yes □No		The original sample was E.coli positive and at least 1 repeat sample was
			□res (□vo	□Yes □No		positive for total colliform {= <u>E.coli MCL violation</u>).
	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		⊡Yes ⊡No	□/es □//o		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
			□Yes □No	DYes Dvo		
			Dres Dvo	□Yes □Wo		As wearing by E 1 H2 (Company Company Company)
			□Yes □No	□Yes □No	ļ	As required by 5-1.72, "Operation of a Public Water System," a copy of this form shall be sent to your local health department by the 10th calendar day of the next reporting period.
	77		∐Kes ∏No	Dres DNo		,
			∐Yes ∏No	□Yes □Wo		·
·		1	Dres Dxo	Dres Dvo		
Sample Collector(s): Name of NYSDOH Certifi	ed Laboratory: S	imith Laboratory eribe: <u>N</u>	io			
		<u>-</u>		····		
Oid an emergency or Iow	pressure problem oc	eur? Did sourc	se water byp	ass an existin	g treatment process in	the system? If so, please explain.
			······			
Comments:						
				·····		

Water Systems Operation Report

Bureau of Public Water Supply Protection								For Systems that Treat with Chlorine and/ or Ultraviolet Radiation					
Publi	c Water Sys	tem Name	**(************************************	444EPP\$ 145E44EPP	Commissional	Reporting	Month/Year	Date Report Su	ubmitted	Source Type (s)			
										Surface Ground GWUDI			
		Village of	Millbi	ook		01/	2 0 1 2	02/06	/ 2 <u>0 1 2</u>	Purchase with subsequent chlorination			
						мм	YYYY	<u>0</u> 2 / <u>0</u> <u>6</u> M M D D	YYYY	Purchase w/ou	it subsequent chlor	Ination	
Public	Water System	Ď	1442 pag pag 1 7 20 1 2 3	ar yl gib il ba lly fil jarri 1	ERNESE INCOMESSACIONAL PROPERTIES			County		Town, Village or	City		
į								Į.					
NY	1 3	0 2 7	7.0					Dutcl	hess		Millbroo	k	
į	<u>. </u>	<u> </u>						1					
					1-45			1 Ufr	aviolet Radiatio	n / Other Tree	tment		
[]				Ų.	nlorination			· ·	TAIOIOL I CAGIALIC	7/17 Oknor 1100	T		
	Source (s)	Treated Water	Ga	seous	Liquid		* * * * * * * * * * * * * * * * * * * *		j	l			
	In Use	Volume (1,000		Chlorine		Free Chlorine	UV Unit Active	Intensity Meter			C-9 used		
DATE		gallons/day)	Cylinder Weight	Usa	Hypochiorite added to crock (Gallons)	Residual (mg/l)	(Yes/No)	>70%	used (gallor	18) "''	(gallons)		
			, vergin	(Lbs. /Day)	,	(mgr)	(11-11-17						
1	,.,.,	170,0		ļ	10.0	0.8			9.1	6.8	1.2		
2		230.0				1.0			6.2	7.6	2.4		
3		165.0				1.0			2,6	7.8	1.2		
4		190.0				1.2			5.3	6.5	1.8		
5		240.0			15.0	8.0			6.8	7.2	2.4	<u> </u>	
6		180,0				1.2			1.5	8.0	0.6	ļ - <u></u>	
7.		260.0				1.0			1.5	7.8	2,4		
В		150.0		<u> </u>		1.2			1.5	7.6	2.4		
8		265.0				1.2			8.3	7.7	1.2		
10		280.0		ļ:		1.1			9.8	7.4	2.7	 	
11		100.0				1,0			1.5	7.9	0.9		
12		220.0				0.9	<u> </u>		1.9	7.7 6.5	2,4	 	
13		170.0		ļ	15.0	0.7			11.3	6.5 6.5	2.4		
14		275.0				0.6			5.2	6,9	0.6		
15		150.0	 	 		0.9			7.2	7.0	2.7		
16		260.0 220.0				1.1			2.6	7.9	2.7		
18		190.0		 		1,1			5.9	6.5	1.2		
19		210,0	†			1.0			6.2	7.7	2.4		
20		150.0	†		15.0	1.1			3.4	7.0	1.2		
21	· · · · · · · · · · · · · · · · · · ·	275.0		-		0.9		•	6.8	7.2	3		
22		190.0				1.1			4.2	7.0	1.2		
23		270.0				1.0			8.1	7.5	3.6		
24		135.0				.1.2]	4.2	8.0	1.2	_	
25		295.0	<u> </u>			0,9	<u> </u>		2.6	7.9	3	<u> </u>	
26		150.0	<u> </u>	<u> </u>		1.2			5.2	6.6	1.8		
27		205.0	 	<u> </u>	15.0	0.8		 	3.0	7.1	2,4	1	
28		230.0				1.0		-	3.3	7.1 6.8	2,4	 	
29		225.0	 -		 	1.0			6.1	6.8	2.1	 	
30		225.0	+	 	 	1.1			3.3	7.7	1.2		
31		150.0	111111	4	70.0				152.51		61.2		
Total							 	<u> </u>	5.08		2.04		
Aver.	WHITHING 2012 YILLIA					1.0	1		,				
Chlo	Chlorine Mix Ratio = 30 Gallons/ of						12	% chlorine add	ed to	30 gallons of water in crock			
Repo	orted by:		Scott	E. Osborn	i		Title	Area Coordinator	Γ	Certification Number: NY0034351			
	nature:						Date	2/6/2012		Operator Grad	de Level:	IIA, C, D	

DCH 360CUV pg. 1 of 2 (9/04)

Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
34 Russell Knolls	1/4/2012	1	⊡res ☑No	⊡res ☑No	0.7	Number of microbiological monitoring samples taken: 2
3292 Franklin	1/12/2012	1	□Yes ②No	□res ⊡vo	1.0	Did an M&R violation occur?
			∏res □No	□res □No		If "Yes," check reason (s) below: Actual number of samples is fewer than required.
			□res □No	□Yes □No		Did not collect/analyze repeat sample. Did not collect/analyze for E. coll for positive total collform from routine/repeat sample.
			□Yes □No	□Yes □No		Did an MCL violation occur?
····			□Yes □\%	□Yes □No		∏r'es
			□(es □No	□Yes □Vo		additional information). For systems collecting less than 40 samples par month: two or more of the samples (routine and for repeat) are positive for total coliform (= total colif
			□Yes □Na	□res □No		MCL violation).
			Dres Dvo	□Yes □No		
			Dres Dio	□\e □\n		The original sample was E.coII positive and at least 1 repeat sample was
			Dres Dvo	Dres □No		positive for total coliform (= <u>E.coli MCL. violation</u>).
			□res □No	□Yes □Vo		Reminder: System must collect a minimum of five (5) routine microbiologic
			□/es □No	□Yes □No		monitoring samples during the month following a repeat sample collection.
			□r'es □ro			Jan. 4. 11. 8488.86
,			⊡Yes ∐No	Dres Dvo		As required by 5-1.72, "Operation of a Public Water System," a copy of th form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			Dres □vo	□Yes □No		
		Ì	D∕es Dvo	D/es D/w		
			⊡res ⊡vo	Dies Die		
ople Collector(s): ne of NYSDOH Certif any MCL violation of	ied Laboratory:	Smith Laboratory	ío			
		· 				1
an emergency or low	pressure problem oc	eur? Did sourc	e water byp	ass an existin	g treatment process in	the system? If so, please explain.
, , , , , , , , , , , , , , , , , , ,						
ments: Installed walks	way over stream to acc	ess bunkers.				
	_					

Water Systems Operation Report

Bureau of Public Water Supply Protection									For Syst	ems mat rreat	eat with Chlorine and/ or Ultraviolet Radiation			
ubl	c Water Syst	em Name			311111111111111111111111111111111111111	Reporting	Month/	Year	Date Report Si	ubmitted	Source Type (s)			
			× 21111			□ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □								
		Village of	Millbr	ook	•				03/08		Urchase with subsequent chlorination Urchase w/out subsequent chlorination			
		M1114446114		***************************************	agan punganagaammendadi Indodisess	MM	ΥY	ΥY		YYYY			подол	
прнс	Water System I	D							County		Town, Village or	City		
	<i>3</i> 1	0 0 7	7 0						Dutc	haee		Millbroo	k	
VΥ	<u>i</u> 5	<u>0</u> <u>2</u> <u>7</u>	7 0						Dulo	1000		IMINIO		
		·····	I						1	1 (2% - 47 - 67				
ĺ				Cl	nlorination				Uit	raviolet Radiatio	on / Other Trea	ment		
	Source (s)	Treated Water	Ga	seous	Liquid	_ :								
DATE	In Use	Volume (1,000 gallons/day)	Cylinder Weight	Chlorine Use (Lbs. /Day)	Hypochlorite added to crock (Gallons)	Free Chlorine Residual (mg/l)				Sodium Hydro used (gallor		C-9 used (gallons)		
1		305.0	-		<u> </u>	0,9				4.9	7.7	3		
2		140,0				1,0				4.1	7.2	1.8		
3		215.0				8.0				4.5	7.8	1.2		
4		225.0				0,6				3.8	7.1	2.4		
5		225.0				0.5	<u> </u>			2.3	7.0	2.7		
5		215.0			15,0	8,0	<u> </u>		<u> </u>	5.9	6.7	1.5	 	
7		245.0	<u> </u>			0.7				4.9	7.4	1,8	,	
В		175.D	-			1.0				3.6	8.0	1.5		
9		200.0	ļ		15.0	1.1	<u> </u>			5.2	7.0	0.9	-	
10		205.0	 	ļ		0.9				3.3 5.3	7.8	2.4		
11		175.0	 		<u> </u>	1.2				2.0	7.3	1.5		
12		210.0 220.0	 	<u> </u>		1.3	ļ			8.1	7.0	3		
13		245.0	 			1.2				4.9	7.7	- 1.8		
15		180.0	1			1.5				6.5	7,9	1.5		
16		205.0				1.3				8.0	7.9	1.75		
17		250,0			8,0	0.8				6.1	7.3	2.4		
18		140.0				1.0				. 1.1	7.2	1.2		
19		275.0				0.4				2.6	7.3	2,1		
20		205.0				0.7				6.0	6,5	1.8	ļ	
21		130.0		ļ <u>.</u>		8.0				3.0	7.2	9		
22		245,0	<u> </u>	ļ		0.2			<u></u>	6.0	7.0	1.5		
23		190.0	 	ļ	44.4	0.5			<u> </u>	1.5 3.8	7.7	1,8	 	
24		230.0			10.0	0.5	 		 	5.3	6,5	2.4	 	
25 ne		150.0 . 310.0	 			0.5				7.5	7.5	3		
26 27		140.0	1			0.7	<u> </u>			2,0	6.6	3.6		
28		300.0				0.8				8.1	7.0	0.6		
29		120,0				0,7				2.9	7.5	. 0.6		
30														
31			7.6.			*******	<u></u>			<u> </u>			<u> </u>	
itai		6070.0			48.0					133.05		63.85	<u></u>	
ver,		209.3		<u> </u>		0.8	<u> </u>		l	4.44		2.13	<u> </u>	
hlor	ine Mix Ratio	=	30	Gallo	ons/ of		12		% chlorine adde	ed to	30	gallons of v	vater in crock	
tepo	rted by:		Scott E	E, Osborn		Title Area Coordinator Certification Number: NY00					NY0034351			
	•								3/8/2012		Operator Grad			

DOH 350CUV pg. 1 of 2 (8/04)

Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required:
39 North Ave	2/1/2012	1	□Yes ☑No	□Yes ☑No	0.4	Number of microbiological monitoring samples taken:
Library	2/8/2012	1	Ores (7%)	∐Yes ☑No	0.2	Did an M&R violation occur? ☐Yes ☑No
			□/es □/b	∐Yes ∐vo		If "Yes," check reason (s) below: Actual number of samples is fewer than required.
	•	THE PARTICULAR PROPERTY OF THE PARTICULAR PROPER	□/es □\o	Dies Die		Did not collect/analyze repeat sample. Did not collect/analyze for E, coll for positive total coliform from routine/repeat sample.
			∐Yes ⊡No	□\es □\o		Did an MCL violation occur?
			D/es D/w	□kez □#P		. □Yes ☑No If "Yes," check reason(s) below (see also Part 5, Table 6 for
			[Kes []%	□Yes □No		additional information). For systems collecting less than 40 samples per month: two or more of samples (routine and /or repeat) are positive for total colliform (= total c
			□res □vo	□Yes □Wo		MCL violetion).
-			Dres Dvo	□Yes □No		
			□Yes □No	□/es □vo		The original sample was E.coli positive and at least 1 repeat sample wa:
			□Yes □No	□\\æ □\\		positive for total coliform (= <u>E.coli MCL violation</u>).
			□res □vo	∐Yes ∐No		Reminder: System must collect a minimum of five (5) routine microbiolo
			□Yes □Vo	_\n= _\n0		monitoring samples during the month following a repeat sample collection
			□/es □/b	□/≈ □/ ₀		
			DYes (DNo	□Yes □No		As required by 5-1.72, "Operation of a Public Water System," a copy of form shall be sent to your local health department by the 10th calendar of the next reporting period.
			□Yes □No	□res □v6	,	
			D/es DNo	□Yes □‰		
			DYes D¥o	□Yes □No		
ole Collector(s): of NYSDOH Certi		Smith Laboratory	No			
		<u></u>				
a emergency or low	pressure problem o	ecur? Did sour	ce water byp	ess an existir	ng treatment process in	the system? If so, please explain,
					- All P	

Water Systems Operation Report For Systems that Treat with Chlorine and/ or Ultraviolet Radiation

Public Water System Name					Reporting	Month/Year	Date Report Si		-Source Type (s)					
					•					□Surface ☑Sround □SWUDI				
		Village of	Millb	ook			<u>2 0 1 2</u>	04/10	/ <u>2 0 1 2</u>		subsequent chlori			
- mann	and Color I from the comme to see the	III 1981 istaan maarija Helli III Ielen				MM	YYYY		YYYY		Purchase w/out subsequent chlorination			
Public	Water System I	lD						County		Town, Village or City				
RIV	1 2	0 2 7	7 0					Dutc	hace	Millbrook				
NY	1 2	1 3 0 2 7 7 0						Duit	11000		Million	14		
-				C	hlorination			Uite	raviolet Radiatio	on / Other Trea	tment			
		Treated Water	Ga	seous	Llquid	1		<u> </u>			Γ	T :		
	Source (s)	Volume (1,000				Free	1		Codium Livden	vida	C-9 used			
DATE	In Use	gallons/day)	Cylinder	Chlorine	Hypochlorite added	Chlorine Residual			Sodium Hydro used (gallon		(gallons)			
		ŀ	Welght	(Lbs. /Day)	to creck (Gallons)	(mg/l)	_		useu (galioi:	13)	(gaions)			
				,,							Į	<u> </u>		
1		200.0	ļ			0.6			5.2	7.8	1.5	1		
2		230.0				0.6			3.7	7.7	1.8	 		
3		150.0				0.5			2.3	7.8	1.2			
4		310.0	ļ			0.5			3.9	7.1	2.4			
5		135.0	 		19.0	0,7			3,8	6.9 7.8	1.2			
6		230.0				0,8			5.6 3.8	8.2	1.8			
7 8		200.0			<u> </u>	0,9		 	5.3	7.9	2.4			
9		220.0				1.0			4.5	7.8	1.2			
10		145.0	ļ ———			0,9			2.2	7.9	1.2			
11	********	255.0	<u> </u>	-		0.6			4.9	7.9	3			
12		190.0				0.8			3.9	7.7	2.4			
13	······································	210.0				0.7			4.5	7.9	1.5			
14		240.0				0,9			3.8	7.9	2.1			
15		300.0				0.8		<u> </u>	3.0	8.0	2.4			
16		115.0			5.0	0.7			3.0	7.0	1.2			
17		180,0				0.8			2.2	7,2	1.2			
18		370.0				0.6			8.3	7.2	3.6			
19		130.0				1.0			3.0	7.9	1.2			
20		180.0				8,0	<u> </u>		7.5	8.0	2.4	 		
21		280.0			10.0	0.9			0.0 4.5	7.9	1.2			
22		305,0	 		·	0.7	 	1	3.0	8.0 7.4	1.2			
23 24		130,0 150.0				0.7			3.0	7.4	1.2	1		
25		320.0				0.6			7.5	7.7	3	<u> </u>		
26		140.0				0.7			1.5	7.9	1,2	1		
27		270,0				0.7			6.2	7.3	1.8			
28		170,0				0.7			3.6	7.8	1.8			
29		190.0			22.0	0.5			3.3	7.9	2,4			
30		245,0				1.2			1.5	7.8	1.2			
31	THE	190,0	aner			1.0			4.5	6.8	2,4	<u> </u>		
otai					56.0				123		57.3	 		
war.		211.8				0.8	L		4.10		1.91	<u></u>		
Chlori	ine Mix Ratio	=	30	Gallo	ons/ of		12	% chlorine adde	ed to	30	gallons of v	vater in crock		
₹epo	rted by:		Scott E	. Osborn			Title	Area Coordinator	 .	Certification N	lumber:	NY0034351		
Sign	ature:					i	Date	4/10/2012	· ·	Operator Grad	e Level:	liA		

DOH 366CUV pg. 1 of 2 (9/04)

Microbiologica	l Samples an	d Free Ch	lorine I	Residual		
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	
Stewart's	3/6/2012	1	□res ☑no	□res ⊡No	0,2	Number of microbiological monitoring samples required: 2 Number of microbiological monitoring samples taken: 2
63 Old Rt 82	3/7/2012	į	[]Yes [⊒\vo	∏Yes ☑No	0.7	Did an M&R violation occur?
			□res □‰	□res □vo		If "Yes," check reason (s) below: Actual number of samples is fewer then required.
			Dres DNo	□Yes □No		Did not collect/analyze repeat sample, Did not collect/analyze for E. coll for positive total coliform from routine/repeat sample,
			□Yes □No	□Yes □No		Did an MCL violation occur?
		***	Dkez Dko	Dres Dvo		☐Yes ☐No If "Yes," check reason(s) below (see also Part 5, Table 6 for
			∐res ∏vo	□Yes □No		additional information). For systems collecting less than 40 samples per month; two or more of the samples (routine and for repeat) are positive for total collionm. (= total collionm.)
			□fes □vo	Ors Ow		MCL violation).
	- CHIERDANA		Drés ⊡vo	□res □no		<u> </u>
	-		□res □w			The original sample was E.coli positive and at least 1 repeat sample was
No.			□/es □//o	□/es □vo		positive for total coliform (= <u>E.coli MCL violation</u>).
			O/es Ow	□res □vo		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
			∐Yes ⊡No	□/es □No		mountaine samples during the month tomowing a repeat sample confection.
,			□Yes □Vo	D/es D/w		As required by 5-1.72, "Operation of a Public Water System," a copy of this
			DYes Dvo	□Ves □Vo		form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			□res □No	D%s D%		
	and the second		□Yes □No	Dies Die		
	State of the state		⊡res ⊡No	□Yes □No		
Sample Collector(s): _ I Name of NYSDOH Certifi Did any MCL violation acc	ed Laboratory:	Smith Laboratory	No			
Did an emergency or low	pressure problem oc	cur? Did sour	ce water byg	oass an existin	ig treatment process in	n the system? If so, please explain.
Comments:						
	-41.					

Water Systems Operation Report For Systems that Treat with Chlorine and/ or Ultraviolet Radiation

Public Water System Name													Source Type (c)			
ublic \	Water Syst	em Name				Reporting Month/Year Date Report Submitted							<u></u>		Source Type (s) GWUDI
	,	Villaga of	አ <i>ለ</i> ያብሔ	-0014					, .		_	/ o o / -	Daw	_	Ground	
		Village of	ICHINI	OOK			/ <u>2</u>	0	1 2	05/0	0 5 / 0 8 / 2 0 1 2 Durchase with subsequent chlorination M M D D V Y Y Y Durchase w/out subsequent chlorination					
	ater System I)			M M	<u>Y</u>	Y	ΥY						#IGHO!!	
ablic Ave	ater System H	ע						County Town,						wn, Village or City		
VΥ	<u>1</u> 3	0 2 7	7 0			Dutchess							Millbrook			
																-,
			hlorination			Ultraviolet Radiation / Other Treatment										
١,	`auraa (a)	Treated Water	Gas	Seous	Lkquid											
DATE	Source (s) In Use	Volume (1,000 galions/day)	Cyllader Welght	Chiorine Use (Lbs. /Day)	Hypochlorite added to crock (Gallons)	Free Chlorina Residual (mg/li)			į			Sodium Hydro used (gallor		pl-l	C-9 used (gallons)	
7		260,0		-		0.5						7.5		7.7	3	
2		150.0				6.0	I					3.0		7.7	1.2	
3		245.0				0.8						2.0		7.5	1.8	
4		190.0				0.9						4.6		7.8	1.8	
5		160,0				8,0	1_				_	3.3		7.8	1,2	
6		165.0			10,0	0.7	↓_			ļ		3.8		7.6	2.4	ļ
7		280.0				0,5	_			ļ	-	4.5		7.2	3.6	
8		320.0				0.6						8.8		7.3	2.4	
9		255.0			<u> </u>	0.7	+-			ļ		2.3 6.2		7.6	2,4 1.8	
10		205.0				0,8					\dashv	<u>0.∠</u> 2.6		7.2 7.7	2.4	
12		195.0 240.0				0.7	+-				ᅱ	3.3		8.0	1.2	
13		· 185.0			·	0.7	+				_	1.5		7.8	2.4	
14		305.0				0.7	+				_	1.8	$\neg \neg$	7.2	2.4	
15		265.0				0.8	1				┪	7.5		7.3	3	
16		230.0			15.0	0.9						4.2		7.8	1.8	
17		130.0	-			1.1						2,3		7.5	0.6	
18_		255.0				0,9						2.3		7.9	2.1	
19		175.D				1.0				<u></u>	_	5 <u>.5</u>		7.2	1.5	
20		155.0				0.9	ļ				_	2.3		7.9	3.6	
21		300.0				0.5				<u> </u>	_	3.8		7.6	1.2	
22		125,0				0.6	╁				-	2.6		7.5	0.6	
23		280.0				0,5	-			 	4	1.6.		7.4	2.1	
24		170,0				0.9	+				-	3.0 4.2		7.3 7.1	1.2	
25		145.0			<u> </u>	0.7	+				-	6.4		7.8	1.5 3	
26 27		110.0			15.0	0.6	╫			 	-	3.0		7.6	1.2	
28		145.0	-		10.0	0.8						5.6		7.5	1.2	
29		320.0				0,7	\top				7	6.5		7.6	3	
30	İ	115,0				0,6	1				1	2.0		7.9	1.2	
31																
itat //		6335,0			40.0							117.95			58.8	
ver. 🕖		211.2				0,9						3.93			1.96	<u> </u>
hlorine	Mix Ratio	= <u>;</u>	30	Gaild	ons/ of		12	!		% chlorine ad	lde	d to	30		gallons of v	vater in crock
Reported by: Scott E. Osborn				. Osborn		Title Area Coordinator Certification Number: N				NY0034351						

DOH 360CUV pg. 1 of 2 (9/04)

TATTCLODIDIOSICS	i Sampies an	a rree Ci	norme i	kesidual		
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	
42 North Ave	4/11/2012	1	∐Yes ☑No	_(es (2%)	0.8	Number of microbiological monitoring samples required: 2 Number of microbiological monitoring samples taken: 2
32 Front St	4/17/2012	1	□tres ☑No	□res ☑wo	0.7	Did an M&R violation occur?
			□Yes □\%	□/es □No		If "Yes," check reason (s) below:
			□Yes □No	□res □w		Actual number of samples is fewer than required. Did not collect/analyze repeat sample. Did not collect/analyze for E. coll for positive total coliform from
			□Yes □No	□res □vo		routine/repeat sample.
,			□kez □ko	∐res ∏vo		Did an MCL violation occur?
			∐Yes ∏vo	□Yes □No		If "Yes," check reason(s) below (see also Part 5, Table 6 for additional information). For systems collecting lass than 40 samples per month: two or more of the
			□Yes □No	□res □rio		samples (routine and /or repeat) are positive for total colliform (= total colliform MCL violation).
,			□res □vo	∏res □ro		
-		-		□Yes □Vo		The original sample was 5 coll positive and at least 4 const county was
			□Yes □Vo	□Yes □Vo		The original sample was E.coli positive and at least 1 repeat sample was positive for total coliform (= <u>E.coli MCL violation</u>).
			Dies Dio	D/es D‰		Reminder: System must collect a minimum of five (5) routine microbiological
	SOOD VA		Dres Dvo	Dies Die		monitoring samples during the month following a repeat sample collection.
30	200		Ores Ow			According to F 1 H2 H2
			□Yes □No	□Yes □No	1	As required by 5-1.72, "Operation of a Public Water System," a copy of this form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			∐res ∏No	□res □‰		
·			□res □No	□res □re		
			DYes □No	Yes □No		
Sample Collector(s): Mame of NYSDOH Certific	d Laboratory: S	mith Laboratory cribe: <u>N</u>	lo			
oid an emergency or low p Vater leak repaired on 4/13/1		zur? Did sourc	e water byp;	ess an existing	g treatment process in	the system? If so, please explain.
			·			·
omments:						

Water Systems Operation Report

***************************************																		et Radiation
ublic	: Water Syst	em Name			Reporting	Mon	th/Year	۱ ا	Date R	eport	Su	bmitte	d	<u> </u>		Source Type (s		
									Į.						Dun		Bround	
	,	Village o	f Millbr	ook		<u>Q 5</u> /	2	<u>0</u> <u>1</u>	2	<u>0</u> 6	/ <u>0</u>	<u>6</u>	121	112			ubsequent chlorin	
				****************	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	мм	Y	ΥY			<u>D</u>	D	Υ \	YY	-		subsequent chlor	IMUUII
iplic /	Water System II	D			•				ľ	County					Town,	Village or C	lity	
											т.	.4 _ 1-					Millbroo	l,
VΥ	<u>1</u> 3	0 2 7	<u>70</u>								יורו	ICI	ness				Mundia	r.
														<u> </u>	<u> </u>			
op				CI	nlorination							Ultr	aviolet	Radiati	on / Ot	her Treat	ment	
			Gar	seous	Liquid		-		Т	*******		1						
	Source (s)	Treated Water Volume (1,00	*		Liquid	Free							Codin	m Hydri	nvida		C-9 used	
ATE	in Use	gallons/day)		Chlorine	Hypochlorite added	Chlorine Residual						ļ		d (gallo		pН	(gallons)	İ
~	-		Weight	Use (Lbs. /Day)	to creek (Gallons)	(mg/l)			- 1			1		- 13	,			
							<u> </u>		_								4.0	
1		180,D				0.9	-		_					3,8 5.2		7.7	1.8 2.4	
2		265,0		<u> </u>		0.6	-		-					2.0		7.4 7.7	0.6	1
3		115,0	_	 		0.8	╁		\dashv					3.0		7.7	1.2	
4		150.0	╅	 		0.7	├-		\dashv			-		3.8		7.4	2.4	
5		270.0	_	 		0.5 0.6	 		-			-		2.0		7.3	1,2	
В		145,0		 		0.8	\vdash		\dashv		,			5.2		7.0	2.4	
7		280,0 150,0		l	·	0.7	1		_	<u> </u>				2.3		7.8	1.2	
8		150.0				0.7								3.0		7.7	0.6	
10		290.0		1		1.4	1	••••••						3.8		7.5	2.4	
11		130.0			22.0	1.5								3.0		7.7	0.6	
12		185.0				2,0								4.6		7.2	1.8	
13		250.0				1.7								4.2		7.5	1.8	
14		185,0			<u> </u>	- 1.2	_							2.9		7.6	2.4	
15		125.0				2,5	<u> </u>		_				ļ <u>.</u>	1.3		7.8	3.6	ļ
16		270.0				0,2	ļ							0.0		7.3	2,1	<u> </u>
17		300,0			<u> </u>	0.8	—						 	6.4 1.1		6.7 7.5	1.2	i
18		120.0		 	15.0	1.0	-						<u> </u>	3.0		7.3	2.4	
19		240.0		 	<u> </u>	1,2	┼─		-1				 	4.5		7,2	2.4	
20		310,0	- 		 	1.0	╀╴		-				-	3,8		7.0	1.2	
21		150.0		 		0.6	╁		-1					0.8		7.6	0,3	1
22		75.0 285.0		-		0.7	+-		一				<u> </u>	5.2		7.2	2.1	
23 24		210.0		1		1.0	1							3.4		7.7	1.8	
25		195,0	1		15,0	1.0							<u> </u>	1.9		7.6	1.2	
28	·····	160.0	<u> </u>			1,2								3.0		7.4	1.8	ļ <u>.</u>
27		285.0				1.0								6.8		7.2	2.4	
28		190.0				1.0	<u> </u>							3.9		7.2	1.2	ļ <u>-</u>
29		315.0				1.4	<u> </u>							3.9		7.5	2.4	-
30		155.0		<u> </u>		1.0	 						ऻ	3.0	 -	6.9	1.8	
31		195.0	- 77.77		15.0	1.0	_						 	3.8		7.5	1.8	<u> </u>
otal		6335.0		4	67.0		1							104.6			52.5	
ver.		204.4	VIIII	4		1.0							<u> </u>	3.49			1.75	<u> </u>
Chlor	ine Mix Ratio	1=	30	Gall	ons/ of		12			% chl	orine :	adde	ed to _		30	l	gallons of	water in crock
₹еро	rted by:		Scott	E. Osborn)		Titls	·	£	rea Co	oordin	ator		_	Cert	ification N	lumber:	NY0034351
	nature:						Date			2/2	2012				Oner	ator Grad	le Level:	IJA, C, D
	ISHTED.							·		- C1 - C1					-1			

DOH 350CUV pg. 1 of 2 (9/04)

TATICI ODIOIOSICA	r pampies am	u vice Ci	norme r	residual		
Sample Location	Date of Sample	Sampte Type 1.Routine 2.Repeat	Total Coliform Positive	E.cali Positive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
Highway Dept	5/1/2012	1	□res ⊡vo	∐res ☑No	0,3	Number of microbiological monitoring samples taken: 2
15 Alden Acres	5/8/2012	1	□res ⊡no	Tres Eno	0,3	Did an M&R violation occur?
		-	⊡res ⊡No	□res □va		IF "Yes," check reason (s) below: Actual number of samples is lewer than required.
			∐Yes ∐No	□res □vo		Did not collect/analyze repeat sample. Did not collect/analyze for E. coli for positive total coliform from
			∐Yes ∐No			rouline/repeat sample.
	·····		□'¢≎ □' 10	□res □No		Did an MCL violation occur?
			□Kes □No	□Yes □Vo		☐res ☑No If "Yes," check reason(s) below (see also Part 5, Table 6 for
			□res □No	□Yes □No		additional information). For systems collecting less than 40 samples per month; two or more of the ூளரிச்ச (routine and for repeat) are positive for total coliform (= total coliform)
			□/es □\vo	□res □vo		MCL violation).
			□yes □ye	□res □No		
	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	-	□res □vo	□res □vo	·	The original sample was E.coil positive and at least 1 repeat sample was
			Dres DNo	□Yes □No		positive for (olal coliform (= <u>E.coll MCt. violation</u>).
			⊡Yes □No	□Yes □No		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the menth following a repeat sample collection.
_			□res □w	Dres DNo		monoring statepes aware are mount to so that a report statepe solitorion.
			□Yes □No	□/es □/v ₀		As required by 5-1.72, "Operation of a Public Water System," a copy of this
·			D/es D/o	Ores Ovo		form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			□fes □No	Dkez Dvo		
,			□Yes □No	□res □No		
			□/≈ □/•	⊡res ⊡No		
Sample Collector(s): Name of NYSDOH Certif		t Osborn Smith Laborator	·			
Did any MCL violation of	ccur? If so, please de	escribe:	No			
Did an emergency or low	pressure problem c	ccur? Did sou	rce water by	pass an existi	ng treatment process i	n the system? If so, please explain.
	,					
Comments:						

Water Systems Operation Report

sureau or Public	Water Supply Pr	otection					For Syst	ems that Treat	with Chlorine ar	id/ of Oldaviol	er Kadiation
ublic Water Sy	stem Name	Proposed Farmaneses	##>\$\$\J#1 []###### lat	Matthern jaran in and jumph 194 pi	Reporting	Month/Year	Date Report Su	ıbmitted		Source Туре (
	Village of	Millfor	ook		0.6.7	2 0 1 2	07/05	12012	Burface	Ground Subsequent chlori	SWUDI
	Village of	rattir(D)	OOK		MM	YYYY		YYYY	Purchase w/ou	=	
blic Water System	[D				1 163 167		County		Town, Village or	City	
IY <u>1</u> <u>3</u>	<u>0 2 7</u>	7 0					Dutcl	hess		Millbroo	k
*								<u> </u>			
				hlorination	,		Ulti	raviolet Radiatio	on / Other Treat	ment	
Source (s)	Treated Water	Gas	eous	Liquid	Free]					
In Use	Volume (1,000 gallons/day)	Cylinder Weight	Chlorine Use (Lbs. /Day)	Hypochlorile added to crock (Gallons)	Chlorine Residual (mg/l)		-	Sodium Hydro used (gallor		C-9 used (gallons)	And the state of t
1	214.0				1.0			2.3	7.5	1.2	
2	201.0		,		1.0			3.0	7.1	1.8	
3	165.0				1.2			2.6	7.3	1.2	
4	240,0				0,5			5.3	6.7	1.8	
5	185.0				1.0	1		3.4	7.6	1.2	
8	270.0	1			8,0			4.5	7.3	2.4	
7	170.0				0.9			_1.2	7.5	1.2	
a	150.0	.ļ		<u> </u>	8,0			3.0	6,5	1.2	
9	275.0	ļ			1.2			4.5	6.6	2,4	
10	185.0	 -			1.0			3.0 4.5	6.9 7.4	1.2	
11	310.0	<u> </u>			1.0	-		4.5	6.9	1.8	
12 1	5.0	-			3.3			0.7	8,5	0.6	
(3	260.0	ļ			0.2			1.1	8.5	1.8	
15	275.0 160.0	-		15.0	0.7	·		1.9	6,8	0,6	
16	290.0			10.0	1.3			1.1	6.7	1.8	
17	240.0				1.2			3.0	6.6	1.8	
18	205.0			1	1.0			0.4	7.0	1.2	
19	265.0				0,9			2.1	7.0	1.8	
20	215,0				1.0	<u></u>		2.3	7.0	1.2	ļ <u> </u>
21	285,0				0,9			7.1	7.0	2.4	
22	160,0			15.0	0,9			2.3	7.0	0.6	
23	220.0				1.1			1.5	6.6	1.2	
24	225.0	 			1.0			1.9	7.5	1.2	1
25	160,0				1.3			. 1.1	7.0	1.2 2.4	
26	265.0				0.9			0.8 2.3	7.0	1.2	
27	210.0				0.8			9.1	6.9	1.2	1
28 29	190.0 250.0			15,0	1.8			7.5	8.5	0	1
30	230,0			10,0	1.5			3.0	6.8	0	
11	230,0				1						
al //////////	6465.0			45,0				91		42	
er. /////////	215.5				1.1			3.03		1.40	
hlorîne Mix Rati		30	Gallo	ons/ of		12	% chlorine adde	ed to	30	gallons of v	vater in crock
teported by:		Scott E	. Osborn			Title/	Area Coordinator	·	Certification N	umber:	NY0034351

DOH 360CUV pg. 1 of 2 (9004)

TATICA ODIOIORICA	i Sampies an	o rree Cr	norme e	cesiquai		, , , , , , , , , , , , , , , , , , ,
Sample Location	Date of Sample	Sample Type 1.Rouline 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chilorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
Stewart's	6/13/2012	1	∷res ⊠No	□Yes ☑No	0.3	Number of microbiological monitoring samples taken: 2
Highway garage	5/20/2012	1	∐Yes ⊡No	Dres ⊠w	0,3	Did an M&R violation occur?
			Dres D‰	□res □vo		If "Yes," check reason (s) below:
			□Kes □Vo	D. D.		Actual number of samples is fewer than required. Did not collect/analyze repeat sample.
				Dres Dvo		Did not collect/analyze for E. coll for positive total collform from routine/repeat sample.
	200		∐Yes ∏No	⊡res □No		Did an MCL violation occur?
			□Kes □No	□/es □ko		☐Nes ☑No If "Yes," check reason(s) below (see also Part 5, Table 6 for
			□Yes □No	□Yes □No		additional information). For systems collecting less than 40 samples per month; two or more of the samples (routine and for repeat) are positive for total colliform. (= total colliform
Paradelline			Dies Dvo	Dres Dw		MCL violation).
			□res □va	□res □No		
and the second s			Dres D‰		-	The original sample was E.coil positive and at least 1 repeat sample was
	T. T. T. T. T. T. T. T. T. T. T. T. T. T		□Yes □Vo	□Yes □No		positive for total colliform (= <u>E.coll MCL violation</u>).
			Dres Dwo	□Yes □Vo		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
			∐Yes ∏∜o	□res □ko		
			Dyes Dye	D/es D/o		As required by 5-1.72, "Operation of a Public Water System," a copy of this
			□res □No	□/es □‰		form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			□/es □No	∐Yes ∏to		
TO THE PERSON NAMED IN COLUMN				□Yes □No		
T STATE OF THE STA			□res □vo	□(es □(v)		
Sample Collector(s): _I Name of NYSDOH Certifi Did any MCL violation occ	ed Laboratory: <u></u>	Smith Laboratory eribe; <u>t</u>	40			
Did an emergency or low	pressure problem oc	cur? Did sour	ce water byp	ass an existîn	g treatment process in	the system? If so, please explain.

Comments: Pump#1 failed	to run on 6/13 causing	low storage ala	rm. Resel pur	no controls an	d all systems running nor	mal. Collected POC samples.
						

Water Systems Operation Report For Systems that Treat with Chlorine and/ or Ultraviolet Radiation

ublic Water Syst	tem Name				Reporting	Month/Year	Date Report St	ubmitted	Purchase w/out subsequent chlorination		
	. en -	a #2106.	. .							•	
	Village of	Millibi	OOK			2012	08/07	12012			
 	}54mmbay),cf4rpv44if1859v44rv4p1999	*******		tici nakki. dhares i waxayayaha (e l e juj q ju j	MM	<u>Y- Y Y Y</u>	·	YYYY			nnauon
ublic Water System I	ID					•	County		Town, Village or	City	
WY <u>1</u> <u>3</u>	<u>0</u> <u>2</u> <u>7</u>	<u>7 0</u>					Dutc	hess		Millbroo	k
			CI	hlorination			l Ulfi	raviolet Radiation	n / Other Trea	tinent	
	Treated Water	Ga	SEOUS	Liquid	r						
Source (s)	Volume (1,000			Liquia	Free	ļ		Sodium Hydro	wide	C-9 used	
In Use	gallons/day)	Cylinder Weight	Chlorine Use (Lbs. /Day)	Hypochlorile added to crock (Gallons)	Chlorine Residual (mg/l)			used (gallor		(gallons)	
1	300.0				0,5			2.3	6.8	3	
2	205,0				0.9			1.0	6.8	1.2	
3	270.0				0.7			1.3	6.9	1.8	<u> </u>
4	, 175.D				0.6		•	0.7	6.8	1.2	<u> </u>
5	280.0				· 0.7			4.9	6.8	2.4	
6	185.0				0.7			2.3	7.1	1.2	
7	260.0				0.7			3.8	7,0	3	
8	295.0		_,		1.0			4.9	6.8	1.2	
9	280.0				1.0			5.2	7.0	2.4	1
10	-205.0			ļ. <u></u>	0.7	-		2.9	7.1	2,4	1
11	295.0	 			0.5			5.2 4.9	7.2	1.2	
12	200.0			<u> </u>	0.5			5.3	7.4	1.8	
13	320.0 275.0				0.5	ļ		3.0	7.1	1.2	
15	225,0	-			0.6			2.6	6.5	2.4	
16	285.0	-	· · · · · · · · · · · · · · · · · · ·		0.5			6.5	7.4	2.1	1
17	205,0				0.7			3.9	7.4	1.5	
18	220.0				0.8			3.9	7.5	2.4	
19 .	285.0				0,2			6.2	6.5	1.8	
20	150.0				0.5			6.5	7.4	3	<u> </u>
21	205.0				0.7			2.9	7.6	1.5	
22.	335.0	<u> </u>			0.4	ļ. 		6.8	6.5	2.1	
23	135,0				0.5			1.5	6.7	1.2	
24	` 235.0				0,6			4.5	7.4	1.2	
25	165.0				0,8			1.9 5.3	7.5 7.0	1.8	-
26	190.0				0.4			9.3 4.1	7.0	0.6	1
27	220.0				1.2			5.3	7.5	2.4	
28	290.0 145.0				1.1			4.5	7.0	1.2	
30	165.0			111	1.0			1.9	7.5	1.2	1
31	330.0				1.0			5.6	7.5	1.8	T
otal ////////	7330.0							121.6		55.2	
ver. ////////					0,7			4.05		1.84	
Chlorine Mix Ratio		30	Gallo	ons/ of		12	% chlorine adde		30		vater in crock
Reported by:		Scott E	, Osborn			Title A	rea Coordinator		Certification h	lumber:	NY0034351
reported by.											

DON 350000 pg. 1 of 2 (9/04)

Micropiologica	i Sampies am	urice Ch	TOT III E I	Lesiduai		
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Colform Positive	E.coil Positive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
Library	7/11/2012	1	□res ☑wo	Da Zw	0.2	Number of microbiological monitoring samples taken: 2
Garden Center	7/25/2012	1	□tes ☑tho	□res ⊡vo	0.4	Did an M&R violation occur?
			□Yes □Vo	□res □‰		If "Yes," check reason (s) below; Actual number of semples is fewer than required.
						Did not collect/enalyze repeat sample.
			□Yes □\vo	□Yes □vo		Did not collect/analyze for E, coll for positive total colliform from routine/repeat sample.
			□Yes □No	□Yes □vo		Did an MCL violation occur?
			□Yes □\vo	□Yes □No		☐res ☑No If "Yes," check reason(s) below (see also Part 5, Table 6 for additional information).
		***	□Yes □Wo	□res □‰		For systems collecting tess than 40 samples per month; two or more of the samples (routine and for repeat) are positive for total coliform (= total coliform
			□Yes □No	□\.ce □\/°		<u>MCL</u> , violation).
			Dres Dvo	□res □vo		
			□Yes □No	□Yes □Vo		The original sample was E.coli positive and at least 1 repeat sample was
			□Yes □Vo	□xe □1/0		positive for total coliform (= <u>E.coli MCI, violation</u>).
	7		□v≈ □v∘	□res □vo		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
			□Yes □Yo	□Yes □Wo		
			□Yes □No	DYes D√o		As required by 5-1.72, "Operation of a Public Water System," a copy of this
			□Yes □No	DYS DVo		form shall be sent to your local health department by the 10th calendar day of the next reporting period,
			∐Yes ∏\io	□Yes □‰		
			□Yes □No	□kez □‰	,	·
			□Yes □Wo			
		-				
Sample Collector(s):	Doug Bright					
Name of NYSDOH Cert	ified Laboratory:	Smith Laborator	ry			
Did any MCL violation (occur? If so, please d	escribe:	No	.		
Bid on amercanan or lo	w nrescure arablem	angur? Did on	irre wafer hi	rngsg an evict	ing treatment araceco	in the system? If so, please explain.
THE SECOND OF IT.	a bressure honem	occur Day sot	ace make by	Pann HII PVISI		· · · · · · · · · · · · · · · · · · ·
Comments: Bunker repa	ir work in progess.					

Water Systems Operation Report

	au oi rudiic v	Vater Supply Pro	Official	######################################	hiranan 1000 ka 1000 ka 1000 ka 1000 ka 1000 ka 1000 ka 1000 ka 1000 ka 1000 ka 1000 ka 1000 ka 1000 ka 1000 ka						FOT:	Syst	ems in	at i reat	with C	inlorine ai	nd/ or Ultravio	let Radiation
ubl	ic Water Sys	tem Name	•	Reportir	ng Mor	ith/Ye	ar	Date !	Repor	t St	ubmitte	₽ď	<u> </u>		Source Type I			
		Village of	Millb	rook		<u>08</u> M:M				0 9 M M		<u>6</u> D		<u>0 1 2</u> Y Y Y	I —	rchase with:	Bround subsequent chlori t subsequent chlo	
blic	Water System I	D	as bu see our de 146077788	***************************************	Printefeton (rasistitämineesteliji) ja	145 101		<u> </u>		County		<u></u>		1 1		Village or	······	
										_					·		•	
ďΥ	<u>1</u> <u>3</u>	0 2 7	<u>7</u> <u>0</u>								Dι	utc	hess				Millbroc	k
				CI	hlorination					-		Ulfi	raviolet	Radiatio	on / O	ther Treat	ment	
	Course (a)	Treated Water	Ga	seous	Líquid													
ATE :	Source (s) in Use	Volume (1,000 gallons/day)	Cylinder Weight	Chlorine Use (Lbs, <i>I</i> Day)	Hypochlorile added to crock (Gallons)	Free Chlorine Residual (mg/l)								m Hydro d (gallor		pН	C-9 used (gallons)	-
1		180.0				1.7	 							1.0		7.5	1.2	
<u></u>		225.0		,		1.3	1							5.3		6.9	2.4	
3		280,0			15,0	1.1								6.0		7.5	1.2	
4		155,0				2.0								4.0		7.2	2.4	
5		295.0				2.0								8.3		7.0	2.4	
5		315,0	<u> </u>			1.1	\bot							6.0		7.4	2.4	
_		215.0			5,0	1.4							<u> </u>	3,8		7.2	1.5	<u> </u>
		200,0	ļ		15.0	1,8								3.9		7.7	1.2	
_		200,0				1.4	_							4.5		7.2	0.6	
٥		295,0				1.2						_		4.5		7.1	2.4	ļ
1		170.0				1.2								4.1		6.7	1.2	
2		345.0				1.5	-					_	-	8.1		6.6	2.4	
3		175.0			15.0	1,5	-							4.2		7.0	1.2	
4		255.0				2.2	+							2.6		7.1 7.0	1.8 1.8	
5		265,0 4				1.5 1.5								5.9 3.3		7.0	1.0	
6 7	· · · · · · · · · · · · · · · · · · ·	150.0 176.0			15,0	1,5	+							2.3		7.2	1.2	
8		280.0			10,0	1.5				*****				2.3		7.2	1.2	
9		215.0				1.8	1							1.6		6.5	2.4	
0		230.0	·			1.4	1							5.2		6.5	2.4	
1		285.0				1.1	1		_			-	_	6.5		7.0	2.4	
2		265.0				1.0								2.6		7.2	1.8	
,		205.0			15,0	1.0								5.9		6.5	1.8	
4		232.0				2.1								3.0		7.3	1.2	
5		193,0				1.9								3.0		7.2	1.2	
5		365.0				1.5								2.6		7.4	3.6	
7		175.D				0.5	-							4.6		6.6	1,2	
3		185.0			15.0	0.5	_		.				·	5.2		7.2	0,6	
<u> </u>		315.0				1.2	 							5.2		7.1	2.1	
<u> </u>		270.0				1.1			_					8.3		5.7	1.5	
4		270.0			12.0	1.0	_		_					2,3		7.3	1.8	
-	HHHHA				107.0		4		_			\dashv		136.1			53.7	
ior	ine Mix Ratio	238.1	30	Galio	ns/ of	1,4	12			% chic	nine a	dde	ed to	4.54	30		1.79 gallons of v	vater in crock
po	rted by:		Scott E	. Osborn			Title		A	rea Co	ordina	itor		_	Certi	fication No	 ımber:	NY0034351
														_	_			
gr	ature:						Date			9/6/	2012				Opera	itor Grade	Level:	IIA, C, D

DOH 380CUV pg. 1 of 2 (9/04)

Microbiologica	il Samples an	d Free Cl	llorine l	Residual		
Sample Location	Date of Sample	Sample Type 1,Routine 2,Repeat	Total Coliform Positive	E.colf Positive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
3278 Franklin Ave	8/2/2012	1	□res ☑No	□Yes ☑No	0.6	Number of microbiological monitoring samples taken: 2
Stewart's	8/9/2012	1	□Yes ☑‰	□res ☑No	0.6	Did an M&R violation occur?
			Dres Dro	□Yes □Vo		If "Yes," check reason (s) below: Actual number of samples is fewer than required.
			□res □no	□Yes □No		Did not collectionallyze repeat sample. Did not collectionallyze for E, coll for positive total colliform from routine/repeat sample.
			□res □‰	□kes □ko		Did an MCL violation occur?
			Dres Dvo	D/es D‰		☐/es ☑No IF "Yes," check reason(s) below (see also Part 5, Table 6 for
			□res □vo	□res □ko		additional information), For systems collecting less than 40 samples per month: two or more of the samples (rouline and for repeat) are positive for total collform (= total collform
			□Yes □Vo	Öres Dvo		MCL violetion).
			□res □vo	□res □No		
			□res □w	□\e □\•	,	The original sample was E.coli positive and at least 1 repeat sample was
			□res □‰	□Yes □No		positive for total coliform (= <u>E.coli MCL violation</u>).
			⊡res ⊡vo	□/es □‰		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
			∏res □tto	□Yes □No		
	The state of the s		□Yes □No	∐Yes □No	-	As required by 5-1.72, "Operation of a Public Water System," a copy of this
			⊡Yes □vo	Dres Dro		form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			∏res □vo	Dres Dro		
			□Yes □\to	□Yes □No		
	TO THE STATE OF TH	r	□res □ro	D,4≈ D/∞		·
Sample Collector(s): Name of NYSDOH Certif Did any MCL violation of	led Laboratory:	Smith Laboratory scribe: _	No			
				~~		
Did an emergency or low No	pressure problem o	ccur? Did sour	ce water by	pass an existir	ng treatment process in	the system? If so, please explain.

Comments: Bunker repair	work in progess, DOH	Inspection on 8/2	29.			
			· · · · · · · · · · · · · · · · · · ·			

Water Systems Operation Report at with Chlorine and/ or Ultraviolet Radiation

Burea	u of Public W	ater Supply Pro	tection			_				FOF Syst	tems that Treat	with Ch	iorine an	IC/ OF UILIAVIO	et Radiation
Public	c Water Syst	em Name				Reportin	g Mor	ith/Yez	ır	Date Report S	ubmitted	<u> </u>		Source Type (
									į			Durfa		Bround	□ GWUDI
	,	Village of	Millbr	ook		09.	1 2	<u>0</u> 1	2	10/09	/ <u>2 0 1 2</u>			subsequent chlori	
				_L	ainteing) byskis legi loorabisers- lese	MM	Y	ΥY	Y	MM DD	YYYY	 		subsequent chlo	nnauon
Public'	Water System II	> .								County	•	Town, V	illage or C	City	
NY	<u>1</u> <u>3</u>	<u>0</u> <u>2</u> <u>7</u>	<u>7 0</u>							Dutc	hess			Millbroo	k
				CI	niorination		Τ			l Uif	traviolet Radiati	on / Oth	er Treati	ment	
l			Gar	eous	Liquid	1	┼-	•		-	1				T
DATE	Source (s) In Use	Treated Water Volume (1,000 gallons/day)	Cylinder Weight	Chlorine Use (Lbs. /Day)	Hypochlorite added	Free Chlorine Residual (mg/l)					Sodium Hydroused (gallo		pН	C-9 used (gallons)	
-		· 210,0	_			1.0	1-				2,3		7.2	2.4	
2		295,0			,	0.6	1				1.5		7.5	1.8	
3	· · · · · · · · · · · · · · · · · · ·	235.0				0.7					2.0		6.5	0.9	
4	-	220.0				0,5					5.9		6.6	1.5	
5		285.0				0,7				ļ <u></u>	8.5		7.3	3.6	
e		220.0		_	15.0	1.7					5.2		7.5	0.3	
7		- 235.0				0.5	_				3.8		6.9	2.4	<u>``</u>
8		210.0		<u> </u>		. 1.0					4.5		6.7	2,4	
9		260.0				1.0	-				2.6		7.2	0.6	
10		295.0	ļ	ļ	<u> </u>	0.9	-				7.1		6.8 7.4	1.8	
11		175.0	 	<u> </u>		1.2				· · · · · · · · · · · · · · · · · · ·	4.1 8.5		6.9	1.8	
12		290.0	 		15.0	0,8	+				7.0		7.8	2.4	
13		340.0	-			0.7				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	4.5		6.6	1.8	
14		140.0 305.0	 		<u> </u>	0,5	+-				6.0	-	7.3	1.2	
15 18		225.0			15,0	0.5		-		······································	6.0		7.7	1.5	
17	·-·	245.0	 			0,8	1-				8.3		7.0	1.5	
18		125.0				0.7	1				3.8		7.8	0.3	
18 .		295.0				0.5					3.0		7.0	2,1	
20		260,0				0.7					10.0		6.5	1.2	
21		205.0				0,6	<u> </u>				2.6		7.3	1.2	-
22		310.0 -				0,5					3.0		7.2	2.4	
23		150,0	L		<u> </u>	0.5	-				6.1		7.1	0.3	
24		290.0		ļ	<u> </u>	0,6	_				5.9		7.9	2.4	
25		330.0		 		1.3					1,5		7.8 8.1	2 <u>.4</u> 3	
26		130.0	<u> </u>			1.1	+				3.3		7.7	0.6	
27		265,0	 		450	0.8	+				7.5		7.0	2.4	
28		250.0			15.0	2.5 1.5	+				4.5		7.5	0.3	
29 30		165.0 220.0	<u> </u>			1.4	1				4.5	-	7.5	1.2	
30		4.61.11				1 1,4	1				1.5				
Total		7160.0			60.0		7				154.5			48.9	
Aver.		238.7				0.9					5.15			1.63	
	ine Mix Ratio		30	Galli	ons/ of		12			% chlorine add	led to	30		galions of	water in crock
Repo	rted by:		Scott F	E. Osborn			Title			Area Coordinato	r	Certifi	ication N	lumber:	NY0034351
Sigr	ature:		<u>.</u>				Date			10/9/2012	· 	Operat	tor Grad	e Level:	IIA, C, D

DOH 360CUV pg. 1 of 2 (B/D4)

l Samples an		ļ	T		
Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	
9/6/2012	1	□Yes ☑No	□res ⊡No	2.2	Number of microbiological monitoring samples required: 2 Number of microbiological monitoring samples taken: 2
9/11/2012	1	∐res (∑No	□res ②vo	0.2	Did an M&R violation occur? □res ☑no
		□res □No	□Yes □No		If "Yes," check reason (s) below: Actual number of samples is fewer than required.
		□kee □no	□Yes □Vo		Did not collect/analyze repeat sample. Did not collect/analyze for E. coll for positive total coliform from routine/repeat sample.
		□Yes □Vo	□res □vo		Did an MCL violation occur?
		∐kez ∐n⊅	□Yes □No		☐Yes ☐No If "Yes," check reason(s) below (see also Part 5, Table 5 for
		∐Yes ∏No	∏Yes ∏No		additional information). For systems collecting less than 40 samples per month; two or more of the samples (couline and /or repeat) are positive for total colliform (= total colliform
		□/es □1/o	□Yes □Vo		MCI, violation).
		□fes □No	∏res □No		
		⊡res ∏vo	D/≈ D/∞		The original sample was Ecoll positive and at least 1 repeat sample was
-		∐vies ∐vo	□Yes □No		positive for total cottom (= <u>E.cott MCL violation</u>).
700000000000000000000000000000000000000		□Yes □No	∐res ∐vo		Reminder: System must collect a minimum of five (5) routine microbiological
		□Yes □No			monitoring samples during the month following a repeat sample collection.
		□/es □/w	□Yes □No		As required by 5-1.72, "Operation of a Public Water System," a copy of this
		∐fes ∐No	Dves Dvo	Ī	form shall be sent to your local health department by the 10th calendar day of the next reporting period.
a de la composição de l		□Yes □Yo	□/es □//o		
		∐kes □ko	□Yes □No		
		□Yes □No	□Yes □No		
ed Laboratory: <u>§</u> eur? If so, please des	eribe: <u>A</u>	lo			
pressure problem oc	cur? Did sourc	e water byp	ass an existing	g treatment process in	the system? If so, please explain.
vork in progess, Repla	ced eyewash bot	lles at plant w	ilh new ones. (Chlorine crock has been o	covered.
	9/6/2012 9/11/2012 Doug Bright ed Laboratory: Secur? If so, please des	Date of Sample 1.Routine 2.Repeat 9/6/2012 1 9/11/2012 1 Doug Bright ed Laboratory: Smith Laboratory cur? If so, please describe: A	Date of Sample 2.Repeat Coliform Positive 2.Repeat 9/6/2012 1	Date of Sample 2.Repeat Coliform Positive Positi	Date of Sample 1.Routine 2.Repeat Coliform Positive Pres Chlorine Residual Positive Positive Pres Chlorine Residual Positive Positive Pres Chlorine Residual Positive Pres Chlorine Positive Pres Chlorine Residual Positive Pres Chlorine Residual Positive Pres Chlorine Positive Pres Chlorine Residual Positive Pres Chlorine Residual Positive Pres Chlorine Positive Pres Chlorine Residual Positive Pres Chlorine Residual Positive Pres Chlorine Positive Pres Chlorine Residual Positive Pres Chlorine Pres

Water Systems Operation Report at with Chlorine and/ or Ultraviolet Radiation

urea	u of Public W	rater Supply Pro	tection	Elekadyályybil lesflensz	***************************************				<u>11</u>			Willi Ordoni	ie ai	d/ or Ultraviole	
ubli	c Water Syst	em Name				Reportin	g Mor	th/Yea	r	Date Report Su	ibmitted	Surface		Source Type (s Ground) □swudi
	,	cello	R ASSIL									. —		enpania Enpania	
		Village of	MHIN	OOK		10	1 2	<u>u</u> 1	Ž	1 1 / <u>0</u> <u>8</u> M M D D	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			subsequent chlori	
	Water System I	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		******	.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	M M	<u> </u>	YY		County	1 1 1	Town, Villag			
up#~	trace Oystonen	-	٠											-	
۷Y	<u>1</u> <u>3</u>	<u>0</u> <u>2</u> <u>7</u>	<u>7</u> <u>0</u>							Dutcl	hess	,		Millbroo	k
				CI	niorination					' Ulti	raviolet Radiati	on / Other	reat	ment	
	Course (c)	Treated Water	Gas	seous	Liquid	_	1								
DATE	Source (s) In Use	Volume (1,000 galions/day)	Cylinder Weight	Chlorine Use (Lbs. /Day)	Hypochlorite added to crock (Gellons)	Pree Chlorine Residual (mg/l)					Sodium Hydro used (gallo		Н	C-9 used (gallons)	
1		240,0	 			1,0					6.5			1.2	
2		270.0				0.9					6.5			1,2	<u> </u>
3		180.0			15.0	8.0					5.3			1.8	<u> </u>
4		250,0	<u> </u>	<u> </u>		0,9	4-]		6.0			1.5	
5		205.0	<u> </u>	<u> </u>		0.7	+-				5.3			1.8 0.6	
5		175.0	 	ļ		0,5					6.8 4.9			2.1	1
7		275.0	ļ			0.5					4.5			1,5	
8		215.0	 	-		0.7	_		_		5.3			1.5	
9		245.0 310.0	 	<u> </u>	15.0	0.6	\top				5.6			2.1	
1D 11		160.0	 		10.0	1,0					2.6			0.6	
12		265,0	1	1		8,0					4.5			1.8	
13		185.0				1.0					4.5			1.2	-
14		230,0		-		1.0					3.9			1.8	
15		225.0	ļ		15.0	1.1				<u></u>	1.3			1.2	ļ
16		185.0			ļ	0.8					1.5 6.4			0.6 3	
17		235.0	1	 		1.0	-	_,			1.5			1.2	
18		150.0	 	 		1.1	+-				1.9			1.8	
19		220.0	<u> </u>	 		0.9					2.3			1.2	
20		205.0 150.0	1	1		0.8	_				2.3			1.2	
21		285.0	 		1	0.8					6.2			1.8	
23		130.0				1.0					2.9			0.6	
24		215.0				0.6					2.3			1.8	ļ
25		215.0	<u> </u>		15,0	1.0					3.3			1,2	
28		135.0				1.5	4				4.5			1.2	
27		150,0	<u> </u>			1.0				<u></u>	3.0 6.0			1.2 1.5	1
28		260.0		 	 	0.5	╁	· · · · · · ·			0.7			0.9	
29		115.0	 	-		0.9	-				2.6	_		1.2	- f
30		280.0	-	 	-	0.7					6.0			1.2	
31 Total		225.0 6535.0	111111		60.0	Will.	7				126,5			43.5	
Aver.		210.8				0,8					4.22			1,45	
	rine Mix Ratio		30	Gali	ons/ of		12			% chìorine add	ed to	30		gallons of v	water in crock
	orted by:		Scott	E. Osborn			Title	- -	_ !	Area Coordinato	r	Certifical	ion N	lumber:	NY003435
					· · · · · · · · · · · · · · · · · · ·								_		
Sia:	nature:						Date	3		11/8/2012		Operator	Grad	ie Level:	IIA, C, D

DOH 360CUV pg. 1 of 2 (9/04)

Microbiologica	l Samples an	d Free Ch	lorine I	Residual		
Sample Location	Date of Sample	Sample Type 1,Rouline 2,Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
3285 Franklin Ave	10/3/2012	1	∐Yes ☑No	□/es ☑No	0.5	Number of microbiological monitoring samples taken: 2
5 Washington Ave	10/10/2012	1	∐Yes ☑No	□res ☑vo	0.4	Did an M&R violation occur?
			Ches Dvo	□res □vo		If "Yes," check reason (s) below:Actual number of samples is fewer than required.
			□res □No	□/es □/w		Did not collect/analyze repeat sample. Did not collect/analyze for E. coil for positive total coliform from routine/repeat sample.
			□Yes □Vo	Dies Die		Did an MCL violation occur?
			□fes □No	Dv≈ Dv₀		☐yes ☐No If "Yes," check reason(s) below (see also Part 5, Table 6 for
***			□Yes □No	□Yes _{□No}		additional information). For systems collecting less than 40 samples per month: two or more of the samples (routine and for repeat) are positive for total coliform (= total coliform
				∏res _{∏vo}		MCL violation).
			□kes □kò	∐Yes ∐Yo		
		A Permanental Annual	□Yes □Vo	□\r= □\r ₀		The original sample was E.coli positive and at least 1 repeat sample was
		A CONTRACTOR OF THE CONTRACTOR	□Yes □No	□/es □(o	1	positive for total coliform (= $\underline{E.coli}$ MCL violation).
		TO COLOR OF THE PARTY OF THE PA	□res □vo	∐Yes ⊡‱		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
		er recommende en en en en en en en en en en en en en	□res □ro	□Yes □No		
			∏Yes □No	∏res □No		As required by 5-1.72, "Operation of a Public Water System," a copy of this
			Dres Dvo	Dres Dvo		form shall be sent to your local health department by the 10th calendar day of the next reporting period.
		A COMPANY OF THE PERSON OF THE	∐Yes □No	□Yes □W		
				□res □No		
			_Yes □No	□Yes □No		
Sample Collector(s): Name of NYSDOH Certif Did any MCL violation or	led Laboratory:	Smlth Laboratory scribe: <u>t</u>	40			
Did an emergency or low	pressure problem o	cur? Did sour	ce water by	oass an existin	g treatment process in	n the system? If so, please explain.
						•
Comments: <u>Bunker repair</u>	work in progess. Repa	ired water leak a	29 Alden Pla	ce.		

NEW YORK STATE DEPARTMENT OF HEALTH

Water Systems Operation Report

Bureau of Public Water Supply Protection

For Systems that Treat with Chlorine and/ or Ultraviolet Radiation

Public Water System Name						Reporting	Month/Year	Date Report Submitted			Source Type (s)	
Village of Milibrook							2 <u>0</u> 1 2 Y Y Y Y	12/10 MM DD	/ <u>2 0 1 2</u> Y Y Y Y	urchase with	/Ground subsequent chlor at subsequent chlo	
Public Water System ID						ММ		County	<u> </u>			
NY 1 3 0 2 7 7 0							Dutchess			Millbrook		
	[CI	nlorination			Ultraviolet Radiation / Other Trealment				
				seous		1						1
DATE	Source (s) In Use	Treated Water Volume (1,000 gallons/day)	Cylinder Welght	Chlorine Use (Lbs. /Day)	Liquid Hypochiorite added to crock (Gallons)	Free Chlorina Residual (mg/l)			Sodium Hydro used (gallor		C-9 used (gallons)	- The state of the
1		149.0				0,8			2.6	7.5	1.8	<u> </u>
2		180.0			10.0	0.5			0.7	7.4	0.6	
3		245.0				0.5			3.8	7.0	1.8	
4		145.0				0.5			3.6	7.4	1.2	
\$	_	280.0				0.4			7.2	7.0	1.8	
6		245.0				0.5			2.9	7.5	1.2	
7		75.0				0.7			1.5	7.5	0.6	
.8		230.0	ļ			0.6			2.6	7.6	2.4	
9		135.0				0,8			4.5	7.3	2.4	,
10		215.0				0.5			0.8	7.0	1.2	
11		205.0			,	0,5			5.2	7.3	2,4	
12		200,0	ļ		5,0	0.5		`	3.9	7.5	1.2	
13		240.0				0.6			1.3 2.9	7.5 7.0	0.3	1
14		115.0			45.0	0.9			2,9	7.4	2.1	-
15		265.0 150.0			15,0	1.0	<u> </u>		3.8	7.6	1.2	1
16 17		145.0				1.2			2.3	7.1	1.2	
18	· · · · · · · · · · · · · · · · · · ·	265.0				1.4			3.3	7.2	0.9	
19		160.0				1.3			4.5	6.9	1.5	
20		270,0				0,8			4.5	7.5	2.4	
21		140.0			10.0	0,8			2.3	7.4	0.6	
22		135.0				0.5			2.3	7.2	0.6	
23		240.0				0.5			4.5	7.3	1.8	
24		190,0				1.0		<u> </u>	3.0	7.1	1.2	<u> </u>
25	<u> </u>	160,0				0.9			4.2	7.4	0.6	
26		285.0				0.7			3.9	7.6	1.8	
27		145.0		<u> </u>		0,7			2.3	7.0	1.2	
28		230.0				0.6			4.9	7.7	1.2	
20		175.0			44 -	1,1			2.9	7.8	0.9	
30		145.0			19.0	0.7			2,6	7.6	0.9	
31_		57E0 0			60.0				97.7		41.4	
Total Aver.		5750.0 191.7			00.0	0.7			3.26		1.38	
Chlor	ine Mix Ratio		30 Scott E	Gallo	ons/ of		12 Title	% chiorine adde	ed to	30 Certification N	gallons of	water in crock NY0034351
	nature:				-		Date	12/10/2012	 	Operator Grad	e Levei:	IIA, C, D

DOH 350CUV pg. 1 of 2 (9/04)

iviicrodiologica	I Setta pios an	Sample Type	Total			Population Served: 1,450
Sample Location	Date of Sample	i.Routine 2.Repeat	Coliform Positive	E.coll Positive	Free Chlorine Residual (mg/l)	Number of microbiological monitoring samples required: 2
Highway garago	11/2/2012	1	□res ☑No	Die Die	0.3	Number of microbiological monitoring samples taken: 2
3274 Franklin	11/6/2012	1	□res ☑vo	□Yes 197Vo	0,6	Did an M&R violation occur?
	•		□yes □vo	□Yes □No		If "Yes," check reason (s) below:
					<u> </u>	Actual number of samples is fewer than required, Did not collect/analyze repeat sample.
			□res □no	□Yes □No		Did not collect/analyze for E. coli for positive total coliform from routine/repeat sample.
			□res □vo			Did an MCL violation occur?
			□Yes □‰	□Yes □No		☐/es- ☑No If "Yes," check reason(s) below (see also Part 5, Table 6 for
			□res □No	□Kez □Vo		additional information). For systems collecting less than 40 samples per month; two or more of the samples (routine and /or repeat) are positive for total coliform (= total coliform
			□res □to	□Yes □Vo		MCt_violation).
			□Yes □\vo	□res □No		
			□/es □No	□l/es □l/w		The original semple was E.coli positive and at least 1 repeat sample was
			□Yes □No	□Yes □Vo		positive for lotal coliform (= <u>E.coli M.Cl. violation</u>).
			Dres Dio	□Yes □No		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
			□Yes □‰	□/es □v₀		monto, mg dangas dang da monto, awarang a specie compe
			□Yes □No	□tes □‰		As required by 5-1.72, "Operation of a Public Water System," a copy of this
		A STATE OF THE STA	□/es □No	□lifes □life	-	form shall be sent to your local health department by the 10th calendar day of the next reporting period.
			□Kes □Vo			
			□res □No	□/es □// ₀		
			□Yes □\o	□res □vo		
Sample Collector(s): Name of NYSDOH Cert Did any MCL violation	ified Laboratory:	Smith Laborator	ry No			
			p			
Did an emergency or lo	w pressure problem	occur? Did sot	irce water b	ypass an exist	ing freatment process	in the system? If so, please explain.
No	<u> </u>				-	
				-···		
Comments: Installed nev	w precast concrete top	s for West Side t	unkers.			
					. ,4	

NEW YORK STATE DEPARTMENT OF HEALTH

Water Systems Operation Report

3urea	au of Public V	ater Supply Pro		(1) to copy page 18 miles 1 com	rjappjan rena se renoearmedsja i kunkesu:			<u>-</u>		· · · · · · · · · · · · · · · · · · ·	ems that Treat	wiin Chlon	ne ar	nay of Ultraviole	Radiation
Public Water System Name						Reporting	Mon	th/Year	r	Date Report Submitted Source Type (s)					
Village of Millbrook							<u>2</u> Y	Ω 1 Υ Υ	Y	0 1 / 0 Z M M D D	/ <u>2 0 1 3</u>	urchase	with w/ou	Greund subsequent chlorina t subsequent chlorin	
Public Water System ID									County		Town, Villa	ge or t	City		
NY 1 3 0 2 7 7 0							Dutchess Millbrook			ζ					
Chlorination Ultraviolet Radiation / Other Tre							Treat	ment							
	_	Treated Water	Gas	eous	Liquid										
DATE	Source (s) In Use	Volume (1,000 galions/day)	Cylinder Weight	Chiorina Use (Lbs. /Day)	Hypochiorite added to crock (Galions)	Free Chlorins Residual (mg/l)					Sodium Hydro used (gallor		Н	C-9 used (gallons)	
1		215,0				0.6					1.5	7	.2	1.2	
2		210.0				0.9					2.0		.8	1.8	
3		155,0				1.0					3.6	7	.4	0,9	
4		185.0				6.7					2.9		.0	1.5	
5		225.0				0.9					3.9		.3	1.5	
6		195.0				1.0		-			3.9		.3	2.1	
7		220.0				0.8	 				3.0		.1	1.2	
8		145.0			<u> </u>	0.8	├—				4.5		.8 .9	1,2 1.8	
9		275.0	<u> </u>		<u> </u>	0.5	-				5.2 3.3		.4	1.2	
10		150.0 270,0	ļ			1.0	╁		-		5.5		.4	1.2	
11 12		160.0	1			0.8	 				2.9		4	1.2	
13		220.0				0.8	 			<u>,</u>	3.3		.4	1.8	
14	-	210.0			19.0	0,8	1				1.5		.0	1.2	
15		145.0				1.0					1.5	7	.0	0.6	
16		235.0				1.1	1				2.0	7	.0	1.8	
17		180.0				1,0	<u> </u>				3.5		.7	1.2	
18		180.0	<u> </u>		<u> </u>	0.9	ļ				3.3		.4	1.2	
19		265.0				0,9	 -			•	4.2		,4	1.2	
20		135,0	<u> </u>			0.9	 				3.2		.4	1.2	
21		215.0	 			0.B	-				3.0 5.3		.9 .9	1.2	
22		215.0	 			0.7	┼				2.9		.6	1.2	· · · · · · · · · · · · · · · · · · ·
23 24		140,0 315,0			15.0	0.7			_		3.8		.7	2.4	
25		125.0	1			0.6					2.0		.9	0,3	
26		150.0				0.8					3.3		.3	0.9	
27		285,0				0.9					4.6		.3	1.8	
28		135.0				0.8					2.3		.0	1.2	
29		305,0				0.7	<u> </u>				3.8		.0	2.4	
30		345.0				1.5	ļ	<u></u>			6.5		.0	2.4	
31		0,091	THE P		<u> </u>	1.0	ļ -		-		2.3	7	.4	1.2	
oteľ	31 38 1 BARAILE	6365.0		<u></u>	34,0		1				104.5 3.48			43.2 1.44	
wer. Chio	ine Mix Ratio	205.3	30	Gallo	ons/ of	0.8	12			% chlorine adde		30			ater in crock
Repo	orted by:		Scott E	. Osborn			Title	·····-	F	rea Coordinator	Certificat	Certification Number: NY0034351			
Sim	nature:						Date			1/7/2013		Operator	Grad	e Level:	IIA, C, D
-18	MALON CO.									.,,,,,,,,			J		

DOH 36000V pg. 1 of 2 (9/04)

MICLODIOIOGICA	i dambies su	u rree Cl	uorine l	residual		
Sample Location	Date of Sample	Sample Type 1.Routine 2.Repeat	Total Coliform Positive	E.coli Positive	Free Chlorine Residual (mg/l)	Population Served: 1,450 Number of microbiological monitoring samples required: 2
Library	12/6/2013	1	□yes ⊌yo	□res ⊡No	0.2	Number of microbiological monitoring samples taken: 2
32 Front Street	12/12/2013	1	□Yes ②No	□res ☑vo	0,5	Did an M&R violation occur?
		-	□res □No	□Yes □vo		If "Yes," check reason (s) below:
			□Yes □No	□res □No		Actual number of samples is fewer than required. Did not collect/enalyze repeat sample.
						Did not collect/analyze for E. cell for positive total colliform from routine/repeat sample.
			□Yes □No	∐Yes ∏No		Did an MCL violation occur?
			Die Die	Dtes Dvo		∐Yes ENo If "Yes," check reason(s) below (see also Part 5, Table 6 for
denomina sural			 	□vez □v°		additional information). For systems collecting tess than 40 samples per month: two or more of the
			□Yes □No	□Yes □No		samples (routine and /or repeat) are positive for total coliform (= total coliform MCL violation).
A A STATE OF THE S			□res □ro	∐Yes □No		
The state of the s		:	□Yes □No	Dres D%		The original sample was E.coli positive and at least 1 repeat sample was
			∏res ∏vo	□Yes □No		positive for total coliform (= <u>E.coll MCL violetton</u>).
			Diez Dio	□res □w		Reminder: System must collect a minimum of five (5) routine microbiological monitoring samples during the month following a repeat sample collection.
			∐Yes ∐No	□kez □No		
de de la companya de		- 100 - 100				As required by 5-1.72, "Operation of a Public Water System," a copy of this
			□Kes □No	⊡Yes ⊡No		form shall be sent to your local health department by the 10th calendar day of the next reporting period.
**************************************			□les □lvo	□Yes □‰		
			□ks □ko	□Yes □Vo		
			□Yes □No	□res □No		
Sample Collector(s): <u>1</u> Name of NYSDOH Certif Did 2ny MCL violation oc	ied Laboratory:	Smith Laboratory	, No			
Did an emergency or low Yes, water main break at 34				oass an existin	ng treatment process in	n the system? If so, please explain.
Comments: Bunker repair	work in progess. Exha	ust fan in chlorin	e room installe	ed. Painting of	water pipes inside buildin	g In progress.
				TV1		

APPENDIX - C

	_
	_
	<u> </u>
	. 186 . – 186 ° 186 . – 186 . – 186 . – 186 . – 186 . – 186 . – 186 . – 186 . – 186 . – 186 . – 186 . – 186 . –



INSPECTION AND CLEANING OF THE 500,000-GALLON STEEL WATER STORAGE TANK

VILLAGE OF MILLBROOK MILLBROOK, NEW YORK

APRIL 20, 2010





INSPECTION AND CLEANING OF THE 500,000-GALLON RIVETED STEEL WATER STORAGE TANK

VILLAGE OF MILLBROOK MILLBROOK, NEW YORK

APRIL 20, 2010

SCOPE:

On April 20, 2010, Underwater Solutions Inc. completed an inspection of the 500,000-gallon riveted steel water storage tank to provide information regarding the overall condition and integrity and removed the sediment accumulation found on the floor of this structure.

EXTERIOR INSPECTION:

The entire exterior of this water storage tank (and all components) was inspected to include walls and coating, concrete foundation, anchor bolts, manway, ladders, roof and hatch.

Walls and Coating

The exterior wall panels, rivets and lap joints were inspected and appeared mostly sound, yet numerous coating chips, ranging from 1/8" to 1/2" in diameter, exist throughout approximately 5% of the lowest 20' of the tank.

These coating chips appear to be the result of objects striking the tank and expose the underlying steel while causing mild surface corrosion.

No fatigue, (pitting) of the steel was found within these areas having steel exposure at the time this project was completed.

The protective coating applied to these wall panel, rivet and lap joint surfaces shows decline in film thickness (nearly expired) due to weathering, resulting in blotch rusting showing through the coating throughout approximately 5% of all surfaces and all elevations of the tank.

Moderate mildew has accumulated throughout the lowest 20' of the tank, causing decline in the aesthetic value of the structure.

Concrete Foundation

A 15" wide by 5" tall concrete foundation was inspected and found sound and without obvious concrete fatigue throughout the circumference of the tank.

Anchor Bolts

Ten, 1-1/2" diameter anchor bolts extend up from the concrete foundation through chairs, riveted to the lowest row of wall panels located approximately 17" above the base of the tank.

Each anchor bolt has a nut properly secured in place while the protective coating applied to all chair, nut and bolt surfaces shows decline in film thickness, causing blotch rusting to show through the coating.

<u>Manway</u>

One, 24" by 18" inside diameter manway was inspected, penetrating the lowest wall panel, located approximately 31" above the ground.

The protective coating applied to this manway yields reduced film thickness (nearly expired) due to weathering, causing mild surface corrosion of all hardware.

This manway was found properly and securely bolted in place and was free of obvious leakage.

Ladders

A ladder extends from 14' above the ground up to the roof dome, supported to the tank wall with thirteen sets of riveted standoffs.

A fall prevention device is securely bolted to this ladder, remaining in good working condition at this time.

A second (rotating) ladder extends from the edge of the roof dome up to the center of the roof, supported to a phinial ball with one bolted bracket.

Each structure provides good safe access to the roof and is properly secured in place at this time.

Roof

All steel roof panels and rivets between panels were inspected and appeared sound, as no obvious metal fatigue, (pitting) was found.

The protective coating applied to these roof panel and riveted surfaces shows decline in film thickness (nearly expired) and poor adhesion value due to weathering. This condition has caused the primer and blotch rusting to show through the coating throughout approximately 10% of the roof dome surfaces.

Hatch

One, 24" by 24" inside diameter hatch provides access to the tank interior through the roof dome.

This hatch was found in good working condition and is properly secured with a lock, preventing unwanted access.

INTERIOR INSPECTION:

The entire interior of this water storage tank (and components) was inspected to include sediment accumulations, floor, manway, piping, walls and coating, overhead and aesthetic water quality.

Sediment Accumulations

A uniform layer of accumulated precipitate was found on all floor surfaces, averaging 1" in depth.

Upon completing this inspection, all floor surfaces were vacuumed.

Floor

After removing all accumulated precipitate, these steel floor panel and riveted surfaces were inspected and found appearing sound and free of obvious fatigue (pitting) of the steel.

The protective coating applied to these surfaces was found with good adhesion value, while heavy staining exists on all floor surfaces due to the accumulation of precipitate.

Manway

One, 26" by 21" outside diameter manway was inspected from the interior of the tank, penetrating the lowest wall panel located approximately 30" above the floor.

This manway is properly and securely bolted in place and without obvious leakage at this time.

Piping

Three pipes were inspected within this structure.

The first pipe inspected, penetrates the floor located approximately 16" in from the tank wall, having a 12" inside diameter and stands 6" tall.

Flow was entering the tank through this pipe at the time of this inspection.

The second pipe inspected, penetrates the floor located approximately 15" in from the tank wall, having a 6" inside diameter. This pipe extends up, supported to the wall with two sets of riveted brackets, prior to terminating approximately 20' above the floor.

The third pipe inspected, penetrates the tank floor located approximately 15" in from the wall, having a 6" inside diameter and stands 4" tall.

No flow was detected within the second or third pipe at the time this project was completed.

All piping was found without obvious obstructions at the time of this inspection.

Walls and Coating

All interior wall panel and riveted surfaces were inspected beginning at the floor and by spiraling the circumference of the tank up to the water surface.

These interior wall panels and rivets are sound, yet the protective coating applied to these surfaces has failed (expired) throughout all elevations of the walls.

Coating blisters, found throughout approximately 20% of all wall panel and riveted surfaces, exist due to adhesion loss, while approximately 25% of these coating blisters have ruptured, exposing the underlying steel and causing mild surface corrosion at this time.

No obvious metal fatigue (pitting) of the steel was witnessed, while mild staining exists on all wall surfaces extending from approximately 8' below the junction where the roof and walls meet.

<u>Overhead</u>

All overhead panels and rivets were inspected from the water surface.

These overhead panels and rivets appeared sound, as no obvious metal fatigue, (pitting) of the steel was seen at the time of this inspection.

The protective coating applied to these overhead surfaces was found with reduced film thickness, (expiration), resulting in blotch rusting showing through the coating throughout approximately 20% of these surfaces.

Aesthetic Water Quality

The aesthetic water quality within this tank was found to be good.

This condition allowed our visibility during this inspection to be unlimited.

CONCLUSION:

It is the opinion of Underwater Solutions Inc. that that although this riveted steel water storage tank appears mostly sound and free of obvious leakage, it requires rehabilitation within the near future, as the exterior and interior coating systems have failed (expired).

The exterior wall panels, rivets and lap joints appear sound and without obvious fatigue, (pitting) of the steel, yet the protective coating applied to these surfaces was found with decline in film thickness (nearly expired) due to weathering. This condition has resulted in blotch rusting showing through the coating throughout approximately 5% of these wall panel and riveted surfaces and all elevations of the tank.

A moderate mildew accumulation exists throughout the lowest 20' of the tank, causing decline in the aesthetic value of the structure.

Numerous coating chips, ranging from 1/8" to 1/2" in diameter exist throughout approximately 5% of the lowest 20' of the tank and exposes the underlying steel due to objects striking these surfaces.

All roof dome panels and rivets were found without fatigue (pitting) of the steel at the time this project was completed.

The protective coating applied to these roof panels and rivets shows decline in film thickness (nearly expired) and poor adhesion value due to weathering. This condition has caused the primer and blotch rusting to show through the coating throughout approximately 10% of the roof dome.

We recommend re-coating all exterior wall and roof panel and riveted surfaces in an effort to protect and maintain the integrity of the steel and improve the overall aesthetic value of the tank.

All components affixed to this structure are properly installed, yet the tank was found without a vent or an overflow.

We recommend installing a vent and an overflow in an effort to allow proper ventilation and direct water away from the tank should the water level exceed the tank's capacity.

All interior floor panels and rivets appear sound and remain with good adhesion value of the protective coating at this time.

The coating applied to all interior wall and overhead surfaces of this structure has failed (expired). Numerous coating blisters have ruptured, exposing the underlying steel and causing mild surface corrosion due to adhesion loss. No obvious fatigue, (pitting) of the steel was seen at the time of this inspection.

We recommend removing the existing coating and re-coating all interior surfaces of this structure using an A.N.S.I. / N.S.F.61 approved coating for use in structures containing potable water. This rehabilitation should be completed within the immediate future, as continued exposure of the steel will result in metal fatigue, (pitting) and eventually result in failure.

All piping within this structure remained securely in place and free of obvious obstructions at the time this project was completed.

Upon completing this inspection, all floor surfaces were vacuumed.

As always, we recommend re-inspection and cleaning of all water storage facilities in accordance with A.W.W.A. Standards and local guidelines.

UNDERWATER SOLUTIONS INC.

William T. Cornish, President

This report, the conclusions, recommendations and comments prepared by Underwater Solutions Inc. are based upon spot examination from readily accessible parts of the tank. Should latent defects or conditions which vary significantly from those described in the report be discovered at a later date, these should be brought to the attention of a qualified individual at that time. These comments and recommendations should be viewed as information to be used by the Owner in determining the proper course of action and not to replace a complete set of specifications. All repairs should be done in accordance with A.W.W.A. and/or other applicable standards.

WTC/rad




Exterior Wall Panels, Rivets And Lap Joints With Coating Failure, Blotch Rusting And Mildew




Exterior Wall Panels, Rivets And Lap Joints With Coating Failure, Blotch Rusting And Mildew




Exterior Wall Panels, Rivets And Lap Joints With Coating Failure, Blotch Rusting And Mildew




Exterior Wall Panels, Rivets And Lap Joints With Coating Failure, Blotch Rusting And Mildew




Exterior Wall Panels, Rivets And Lap Joints With Coating Failure, Blotch Rusting And Mildew




6 Exterior Wall Panels, Rivets And Lap Joints With Coating Failure And Blotch Rusting



Exterior Wall Panels, Rivets And Lap Joints With Coating Failure And Blotch Rusting



Exterior Wall Panels, Rivets And Lap Joints With Coating Failure And Blotch Rusting




Exterior Wall Panels, Rivets And Lap Joints With Coating Failure And Blotch Rusting




Concrete Foundation Found Sound 10



One Of Ten Anchor Bolts With Blotch Rusting




Manway




Ora Of Two Laddows

One Of Two Ladders




Roof Panel And Riveted Surfaces Appearing Sound, Yet With Coating Failure And Blotch Rusting



Roof Panel And Riveted Surfaces Appearing Sound,
Yet With Coating Failure And Blotch Rusting




Roof Panel And Riveted Surfaces Appearing Sound, Yet With Coating Failure And Blotch Rusting




Roof Panel And Riveted Surfaces Appearing Sound, Yet With Coating Failure And Blotch Rusting






Layer Of Precipitate 20




Layer Of Precipitate



Layer Of Precipitate 22



23 Layer Of Precipitate





Floor Panel And Riveted Surfaces Appearing Sound, 25 Yet Found Heavily Stained After Cleaning



Floor Panel And Riveted Surfaces Appearing Sound, 26 Yet Found Heavily Stained After Cleaning



Floor Panel And Riveted Surfaces Appearing Sound, Yet Found Heavily Stained After Cleaning



Floor Panel And Riveted Surfaces Appearing Sound, Yet Found Heavily Stained After Cleaning



Floor Panel And Riveted Surfaces Appearing Sound, Yet Found Heavily Stained After Cleaning



Manway






Piping 32







34 Piping







36 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining



37 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining




Interior Wall Panels And Rivets With Failed Coating,
Surface Corrosion And Staining




Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining



40 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining




41 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining



42 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining



43 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining



Interior Wall Panels And Rivets With Failed Coating, 44 Surface Corrosion And Staining



Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining




Interior Wall Panels And Rivets With Failed Coating,
Surface Corrosion And Staining




Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining



48 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining



Interior Wall Panels And Rivets With Failed Coating,
Surface Corrosion And Staining



Interior Wall Panels And Rivets With Failed Coating,
50 Surface Corrosion And Staining




51 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining




52 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining




53 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining




54 Interior Wall Panels And Rivets With Failed Coating, Surface Corrosion And Staining



Interior Wall Panels And Rivets With Failed Coating,
Surface Corrosion And Staining




Interior Wall Panels And Rivets With Failed Coating,
56 Surface Corrosion And Staining



57 Overhead Panel And Riveted Surfaces Appearing Sound, Yet Having Blotch Rusting



Overhead Panel And Riveted Surfaces Appearing Sound, Yet Having Blotch Rusting



59 Overhead Panel And Riveted Surfaces Appearing Sound, Yet Having Blotch Rusting



O Discharge During Cleaning

		Manager Committee of the Committee of th		Year Agreement Name of the Control o		NONNisona passo
	•					
						\mass.
		e e				
						-
			•			
						- Continuence

					•	
						·
						WAR.
	0					

						Timber:

						Services
		-				
						-
						harped-

APPENDIX - D

		_
		<u> </u>
		_
	4	
		_
		_
		1

MARCUS J. MOLINARO COUNTY EXECUTI'E



MICHAEL C. CALDWELL, MD, MPH COMMISSIONER

COUNTY OF DUTCHESS

DEPARTMENT OF HEALTH
DIVISION OF ENVIRONMENTAL HEALTH SERVICES

Certified Mail #7004 0750 0000 0456 0602

July 16, 2013

Laura Hurley, Village Mayor Village of Millbrook P.O. Box 349 Millbrook, N.Y. 12545

Re.

Milibrook Village - Public Water Supply Inspection

Federal ID# 1302770 Town of Washington

Dear Ms. Hurley:

On June 27, 2013, this Department conducted its regular inspection of the above-referenced facility to determine compliance with Part 5 of the New York State Sanitary Code. Accompanying me and providing input was your New York State certified operator, Scott Osborn of VRI. Based on our records, your water system currently serves approximately 1400 people through 720 service connections. Please provide updated information to this office as appropriate.

- Monthly operation reports indicate an average daily usage of approximately 200,000 gallons per day.
- Three (3) infiltration galleries located adjacent to the treatment building serve as water sources for this facility. At this time, the safe yield of each gallery is unknown. Aquifer pump testing performed in November of 1997 indicated a stabilized flow rate of 58 gallons per minute.
- Raw water flows by gravity to a 45,000 gallon clear well located below the treatment building where it
 is injected with a sodium hypochlorite solution for disinfection, caustic soda for pH control and zinc
 orthophosphate for corrosion control. This tank provides storage for future use as well as adequate
 chlorine contact time. Two galleries combine in a small wet well before entering the clear well.
- Alternating booster pumps send water to a 500,000 gallon elevated storage tank which "floats" on the system, accepting water only when there is no demand in the distribution system. The tank provides storage volume as well as adequate pressure for most of the distribution system.
- Alarms are provided for high/low storage levels as well as power and communication failure. The
 onsite generator is exercised weekly and was briefly turned on during the inspection.
- The distribution system is flushed once a year in May.

The following items were discussed during the inspection and are re-iterated here as documentation for the New York State Department of Health, Bureau of Public Water Supply Protection program.

1. After reviewing monthly operation reports and monitoring results submitted to this Department since our last inspection, it appears the system was capable of meeting the demands placed upon it. The sodium hypochlorite solution added was able to meet disinfection requirements and laboratory results for all system monitoring were able to meet quality standards for drinking water. The chlorine residual at the plant was 0.7 ppm at the time of inspection. In addition, monthly operation reports as well as sample results were provided to this Department in an acceptable and timely manner. A surveillance bacteriological sample was taken at the highway garage during the inspection. A chlorine residual was present and results were satisfactory.

	223 Main Str. ct, Beacon, New York 12508 • (845) 238-4801 • Fax (845) 838-4824 131 County House Road, Millbrook, Ne. York 12545 • (845) 677-4001 • Fax (845) 677-4020
2 85 Civic Center P	iaza - Suite 106, Poughkeepsie, New York 12601 • (845) 486-3404 • Fax (845) 486-3545 • TTY (845) 486-3417
	HealthInfo@dutchessny.gov
	www.durchessnv.gov

- 2. During the inspection, it was observed that the meter pit has been equipped with a sump pit and pump to help keep this area dry. However, due to the heavy rainfall recently, groundwater was entering the pit faster than could be discharged at the time of inspection. When rainfall dissipates, the pump can be properly set and this issue should be resolved. Please keep this office updated on your progress with this issue.
- 3. It was noted during the inspection that some maintenance items mentioned in the previous inspection have been attended to. Piping within the treatment building (bottom floor) has been repainted, the eyewash solution has been replaced, an exhaust fan has been installed in the chlorine storage room and openings in the chlorine crock was completely covered.
- 4. Since the previous inspection, the bunkers adjacent to the plant have been fully repaired and are again operational. It is noted that it appears similar work may be required at the bunkers on the opposite side of the stream running through the property. The area surrounding one of these bunkers has been excavated for evaluation. This area is ponding water and is considered a possible source of contamination. Please fill in the excavation no later than September 30, 2013. VRI and representatives of this Department will further evaluate the structural integrity of these bunkers at next year's inspection to determine if additional work is required.
- 5. It appears your elevated 500,000 gallon storage tank needs painting. It is strongly recommended this work be performed as soon as possible.
- 6. Based on the results of recent MPA testing, this office has determined the source water for this supply to be under the influence of surface water. Therefore, you have 18 months from the date of this letter to install an adequate filtration system. Please be advised engineering plans must be submitted to the New York State Department of Health as well as this office for review and approval prior to installation. If you wish to further discuss this matter, please contact this office to set up a conference.
- 7. Copies of the 2012 Annual Water Quality Reports (AWQR) and certification were received by this Department on time and accepted. As a reminder, the certification document must be provided to this office no later than September 1, 2013. Please be advised the 2013 AWQR must be provided to this Department and all consumers no later than May 31, 2014 and a copy of the AWQR certification form must be provided to this Department by September 1, 2014. It is recommended to submit a rough draft of the report to this Department by February 28th to allow sufficient review time.

I would like to thank Scott Osborn for his assistance during the inspection. Please keep this office updated on any changes associated with the operator, village officials, phone numbers and addresses. If you have any questions regarding this correspondence, or if I can be of further assistance, please contact me at (845) 486-3404.

Yours very truly,


Daniel J. Kéeler Public Health Engineer

Environmental Health Services

DJK/ams

CC;

Scott Osborn, VRI File (1302770)



MICHAEL C. CALDWELL, ND, NEW COLLESCOPER

COUNTY OF DUTCHESS DEPARTMENT OF HEALTH

Certified Mail # 7004 0750 0000 0457 4593

September 4, 2012

Laura Hurley, Village Mayor Village of Millbrook P.O. Box 349 Millbrook, N.Y. 12545

Re:

Millbrook Village - Public Water Supply Inspection

Federal ID# 1302770 Town of Washington

Dear Ms. Hurley:

On August 29, 2012, this Department conducted its regular inspection of the above-referenced facility to determine compliance with Part 5 of the New York State Sanitary Code. Accompanying me and providing input was your New York State certified operator, Scott Osborn of VRI. Based on our records, your water system currently serves approximately 1400 people through 720 service connections. Please provide updated information to this office as appropriate.

- Monthly operation reports indicate an average daily usage of approximately 200,000 gallons per day.
- Three (3) infiltration galleries located adjacent to the treatment building serve as water sources for this facility. At this time, the safe yield of each gallery is unknown. Aquifer pump testing performed in November of 1997 indicated a stabilized flow rate of 58 gallons per minute.
- Raw water flows by gravity to a 45,000 gallon clear well located below the treatment building where it is injected with a sodium hypochlorite solution for disinfection, caustic soda for pH control and zinc orthophosphate for corrosion control. This tank provides storage for future use as well as adequate chlorine contact time. Two galleries combine in a small wet well before entering the clear well.
- Alternating booster pumps send water to a 500,000 gallon elevated storage tank which
 "floats" on the system, accepting water only when there is no demand in the distribution
 system. The tank provides storage volume as well as adequate pressure for most of the
 distribution system.
- Alarms are provided for high/low storage levels as well as power and communication failure. The onsite generator is exercised weekly and was briefly turned on during the inspection.
- The distribution system is flushed once a year in May.

The following items were discussed during the inspection and are re-iterated here as documentation for the New York State Department of Health, Bureau of Public Water Supply Protection program.

- 1. After reviewing monthly operation reports and monitoring results submitted to this Department since our last inspection, it appears the system was capable of meeting the demands placed upon it. The sodium hypochlorite solution added was able to meet disinfection requirements and laboratory results for all system monitoring were able to meet quality standards for drinking water. The chlorine residual at the plant was 1.1 ppm at the time of inspection. In addition, monthly operation reports as well as sample results were provided to this Department in an acceptable and timely manner.
- 2. During the inspection, it was observed that some deficiencies from the previous inspection have been corrected. A suitable means of crossing the stream to access the infiltration gallery located southeast from the treatment building. In addition, monitoring wells have been properly sealed to protect the aquifer from contamination and all bunkers in infiltration gallery #3 have been cleared of any brush growing in this area.
- 3. It was noted during the inspection that some maintenance items need attention. Piping within the treatment building (bottom floor) needs repainting, the eyewath solution has expired and must be replaced, an exhaust fan must be installed in the chlorine storage room and openings in the chlorine crock must be completely covered. These issues must be properly addressed no later than October 31, 2012 to avoid a violation and please indicate the work complete on the appropriate monthly operation report. In addition, standing water within the meter pit is above the bottom of the water main and a suitable means of removing this water must be employed. It appears a sump pit may need to be installed. Please demonstrate the water is being removed at next year's inspection.
- 4. According to your operator, certain high points within the distribution system experience low pressure. This Department is requesting this issue be investigated to determine exact pressures within connections (i.e. upstairs bathroom tap) at these elevations. Such areas include homes directly near the storage tank, the Millbrook High School and a residence at the top of the hill on Nine Partners Road. Please submit pressure readings no later than December 31, 2012 to avoid a violation. You may wish to contact this office to accompany your operator during this investigation.
- 5. It appears your elevated 500,000 gallon storage tank needs painting. It is strongly recommended this work be performed as soon as possible.
- 6. As you are aware, the Village has been undergoing a study to determine if the infiltration galleries are under the direct influence of surface water. This office in consultation with the New York State Department of Health has required microscopic particulate analysis (MPA) be performed from the stream and two raw water sources during wet and dry weather periods. Following this sampling, a determination will be made as to whether the sources are under the influence of surface water. Due to the fact that excavation has already begun around the bunkers and the presence of surface water within the open excavation, it is believed that MPA testing at this time may produce data not representative of the actual raw water. Therefore, it was agreed during last year's inspection that bunker work be performed as soon as possible and be completed prior to the start of the first MPA. Although some work was completed on this project since the previous inspection, repair work has not been completed and MPA testing has yet to be completed. As this work was required to be completed by November 2011, this is hereby a violation of 5-1.71(a). Bunker repair work must be completed no later than October 31, 2012. Please contact this Department upon completion to discuss the most desirable times for MPA wet/dry weather sampling. Please be advised failure to meet this deadline may result in formal administrative action.

- 7. Copies of the 2011 Annual Water Quality Reports (AWQR) and certification were received by this Department on time and accepted. Please be advised the 2012 AWQR must be provided to this Department and all consumers no later than May 31, 2013. A copy of the AWQR certification form must be provided to this Department by September 1, 2013. It is recommended to submit a rough draft of the report to this Department as soon as possible to allow sufficient review time.
- 8. Part 5-1.52 addresses your facility's monitoring requirements for quality control. The attached sampling schedule has been provided as a general guide only. It is the responsibility of the supplier and not this Department to make sure that all monitoring is performed according to the methods, procedures, and time periods indicated in Part 5 of the New York State Sanitary Code. Sampling frequency is based on maximum contaminant and action levels and therefore, the frequency is subject to change pending sample results. A violation will be issued for failure to comply with the sampling requirements and due dates.

I would like to thank VRI's personnel for their assistance during the inspection. Please keep this office updated on any changes associated with the operator, village officials, phone numbers and addresses. If you have any questions regarding this correspondence, or if I can be of further assistance, please contact me at (845) 486-3404.

Yours very truly

Daniel J. Keeler

Public Health Engineer

Environmental Health Services

DJK/ams

cc: Scott Osborn, VRI (w/ enclosures)

Michelle Kelley → File 097-0024622 (w/ enclosures)

SDV/IS/State Water Sample Schedule Report MILLBROOK VILLAGE PWS ID: NY1302770

Due Contaminant (Group)/ 2012 Sample Location/Frequency Last Compliance Results Sample Requirements Coliform, Total (TCR) \square Location: Distribution System 2 Samples must be collected every month. Frequency: 2 Samples Monthly A positive total coliform (TC+) sample requires notifying the health department and collecting repeat distribution system samples within 24 hours. Unless otherwise directed by the health department, source (or raw) water before any treatment, from all active wells, must also be sampled within 24 hours. Part 5-1.52 Table 9A - Disinfection Byproducts Location: DISTRIBUTION SYSTEM ID: DS199 Samples last Next sample must be collected between 7/1 Frequency: 1 Sample Yearly collected: 8/17/2011 and 9/30 within a single year by 9/30/2012 Sample Point: DISTRIBUTION DBPMAX Sample Point No.: DBPMAX Sample Point Type: MR-Maximum Residence Time Stage 1 Disinfection By-Products: A sample must be obtained from a sampling point reflecting the meximum residence time in the distribution system during the warmest month of the year. Samples taken in July, August, or September will be accepted for compliance. Zinc Location: DISTRIBUTION SYSTEM ID: DS199 Samples last 1 Sample must be collected each calendar Frequency: 1 Sample Quarterly collected: 4/11/2012 quarter. Sample Point: DISTRIBUTION IOC Sample Point No.: IOC-DS Sample Point Type: DS-Distribution System Asbestos Location: DISTRIBUTION SYSTEM ID: DS199 Next sample must be collected by 12/31/2016 Frequency: 1 Sample Every 9 years Sample Point: DISTRIBUTION ASBESTO Sample Point No.: ASB Sample Point Type: DS-Distribution System Nitrate Location: DISTRIBUTION SYSTEM ID: DS199 Last Sample Collected Next sample must be collected between Frequency: 1 Sample Yearly on or Before: 4/11/2012 1/1/2013 and 12/31/2013 Sample Point: ENTRY POINT NITRATE Sample Point No.; RTNO Sample Point Type: EP-Entry Point Part 5-1.42 - Lead and Copper Location: DISTRIBUTION SYSTEM ID: DS199 10 Samples Collected Next 10 samples must be collected between Frequency: 10 Samples Every 3 years on or Before: 9/22/2011 6/1 and 9/30 within a single year by 9/30/2014 Sample Point: DISTRIBUTION PBCU Sample Point No.: PBCU Sample Point Type: DS-Distribution System This PWS is currently on a reduced monitoring frequency of every 3 years. Public water supplies on reduced monitoring must sample between 6/1 and 9/30 of the given year. Part 5-1.52 Table 12 - Radiological Location: DISTRIBUTION SYSTEM ID: DS199 Samples last Next sample must be collected by 12/31/2013 Frequency: 1 Sample Every 6 years collected: 11/7/2007

9/4/2012 DUTCHESS COUNTY DEPARTMENT OF HEALTH
MILLBROOK VILLAGE - NY1302770 Page 1

SDWIS/State Water Sample Schedule Report MILLBROOK VILLAGE PWS ID: NY1302770

Due Contaminant (Group)/ Sample Requirements 2012 Sample Location/Frequency Last Compliance Results Sample Point: ENTRY POINT RAD Sample Point No.: RAD Sample Point Type: EP-Entry Point Part 5-1.52 Table 8B - Primary Inorganic Chemicals Location: DISTRIBUTION SYSTEM ID: DS199 Samples last Next sample must be collected by 12/31/2013 collected: 9/21/2010 Fraquency: 1 Sample Every 3 years Sample Point: ENTRY POINT IOC Sample Point No.: IOC-EP Sample Point Type: EP-Entry Point Part 5-1.52 Table 9B - Principal Organic Chemicals Location: TREATMENT PLANT ID: TP199 2 Samples Collected Next 2 samples must be collected between on or Before: 6/20/2012 1/1/2013 and 12/31/2013 Frequency: 2 Samples Yearly Sample Point: RAW IG199 & IG299 CO Sample Point No.: RAW1 Sample Point Type: RW-Raw Water Source Sample Point: RAW IG399 Sample Point No.: RAW2 Sample Point Type: RW-Raw Water Source Part 5-1.52 Table 9C - Synthetic Organic Chemicals Location: DISTRIBUTION SYSTEM ID: DS199 Samples last Next sample must be collected by 12/31/2013 Frequency: 1 Sample Every 3 years collected: 12/7/2010 Sample Point: ENTRY POINT SOC Sample Point No.: SOC Sample Point Type: EP-Entry Point

September 20, 2011

Laura Hurley, Village Mayor Village of Millbrook P.O. Box 349 Millbrook, N.Y. 12545

Re:Millbrook Village - Public Water Supply Inspection Federal ID# 1302770 Town of Washington

Dear Ms. Hurley:

On September 15, 2011, this Department conducted its regular inspection of the above-referenced facility to determine compliance with Part 5 of the New York State Sanitary Code. Accompanying me and providing input was your New York State certified operator, Scott Osborn of VRI. During the inspection, I observed that your water system is properly operated and adequately maintained and currently serves approximately 1400 people through 720 service connections. Please provide updated information to this office as appropriate.

Dutchess County Department of Health

William R. Steinhaus County Executive

Michael C. Caldwell, MD, MPH Commissioner

Environmental Health Services

387 Main Street Poughkeepsie New York 12601 (845) 486-3404 Fax: (845) 486-3545



- Monthly operation reports indicate an average daily usage of approximately 200,000 gallons per day.
- Three (3) infiltration galleries located adjacent to the treatment building serve as water sources for this facility. At this time, the safe yield of each gallery is unknown. Aquifer pump testing performed in November of 1997 indicated a stabilized flow rate of 58 gallons per minute.
- Raw water flows by gravity to a 45,000 gallon clear well located below the treatment building where it is injected with a sodium hypochlorite solution for disinfection, caustic soda for pH control and zinc orthophosphate for corrosion control. This tank provides storage for future use as well as adequate chlorine contact time. Two galleries combine in a small wet well before entering the clear well.
- Alternating booster pumps send water to a 500,000 gallon elevated storage tank which
 "floats" on the system, accepting water only when there is no demand in the distribution
 system. The tank provides storage volume as well as adequate pressure for most of
 the distribution system.
- Alarms are provided for high/low storage levels as well as power and communication failure. The onsite generator is exercised weekly and was briefly turned on during the inspection.

The following items were discussed during the inspection and are re-iterated here as documentation for the New York State Department of Health, Bureau of Public Water Supply Protection program.

1. After reviewing monthly operation reports and monitoring results submitted to this Department since our last inspection, it appears the system was capable of meeting the demands placed upon it. The sodium hypochlorite solution added was able to meet disinfection requirements and laboratory results for all system monitoring were able to meet quality standards for drinking water. The chlorine residual at the plant was 1.4 ppm at the time of inspection. In addition, monthly operation reports as well as sample results were provided to this Department in an acceptable and timely manner.

- 2. During the inspection, it was observed several deficiencies have been corrected since the previous inspection. A new cover for the wet well has been installed, access hatches to infiltration gallery #3 were equipped with gaskets to provide a better seal, and manhole risers to infiltration gallery #3 had been appropriately repaired. In addition, the sump pump installed in the metering pit has been working to keep water out of the pit and signage has been provided in the treatment building indicating that the sink be used for sample use only and not hand washing.
- 3. The monitoring wells located on the property must be equipped with caps which provide a sanitary seal to prevent contamination of the aquifer. Please submit a specification of the cap proposed prior to installation. Said work must be performed no later than December 31, 2011.
- 4. During the inspection, it was noted that the area surrounding infiltration gallery #3 across the stream has mostly been kept clear as part of routine maintenance. The bunker furthest from the treatment building needs attention to reduce the brush growing in this area. Please perform this work no later than December 31, 2011 to avoid a violation.
- During the inspection, there was no access to the infiltration gallery located southeast from the treatment building. During previous inspections, the operator would use a 10-12" wide piece of wood as a plank to cross the stream. However, the water level was too high to use this device. This Department is requiring a suitable means of crossing this stream be provided such that required maintenance and inspections can be performed. This work must be completed no later than December 31, 2011.
- (6) It appears your elevated 500,000 gallon storage tank needs painting. This work should be performed as soon as possible. Your operator indicated during the inspection that piping within the treatment building is to be re-painted during the winter.
- As you are aware, the Village has been undergoing a study to determine if the infiltration galleries are under the direct influence of surface water. This office in consultation with the New York State Department of Health has required microscopic particulate analysis (MPA) be performed from the stream and two raw water sources during wet and dry weather periods. Following this sampling, a determination will be made as to whether the sources are under the influence of surface water. At the time of inspection, Bill Bright from Delaware Engineering was present to discuss this analysis as well as the repair work proposed for infiltration gallery bunkers located north of the treatment building. Due to the fact that excavation has already begun around the bunkers and the presence of surface water within the open excavation, it is believed that MPA testing at this time may produce data not representative of the actual raw water. Therefore, it was agreed that bunker work be performed as soon as possible and be completed prior to the start of the first MPA. Bunker repair work must be completed no later than October 31, 2011 and MPA wet weather sampling must be completed no later than November 30, 2011.
- 8. Copies of the 2009 and 2010 Annual Water Quality Reports (AWQR) and certifications were received by this Department on time and accepted. Please be advised the 2011 AWQR must be provided to this Department and all consumers no later than May 31, 2012. A copy of the AWQR certification form must be provided to this Department by September 1, 2012. It is recommended to submit a rough draft of the report to this Department as soon as possible to allow sufficient review time.
- 9. Part 5-1.52 addresses your facility's monitoring requirements for quality control. The attached sampling schedule has been provided as a general guide only. It is the responsibility of the supplier and not this Department to make sure that all monitoring is

performed according to the methods, procedures, and time periods indicated in Part 5 of the New York State Sanitary Code. Sampling frequency is based on maximum contaminant and action levels and therefore, the frequency is subject to change pending sample results. A violation will be issued for failure to comply with the sampling requirements and due dates.

I would like to thank VRI's personnel for their assistance during the inspection. Please keep this office updated on any changes associated with the operator, town officials, phone numbers and addresses. If you have any questions regarding this correspondence, or if I can be of further assistance, please contact me at (845) 486-3404.

Yours very truly

Daniel J. Keéler

Public Health Engineer

Environmental Health Services

DJK/ams

cc: Scott Osborn, VRI (w/ enclosures)

Michelle Kelley → File 097-0024622 (w/ enclosures)

April 23, 2010

Andrew J. Ciferri, Village Mayor Village of Millbrook P.O. Box 349 Millbrook, N.Y. 12545

Re:

Millbrook Village - Public Water Supply Inspection

Federal ID# 1302770 Town of Washington

Dear Mr. Ciferri:

On April 9, 2010, this Department conducted its regular inspection of the above-referenced facility to determine compliance with Part 5 of the New York State Sanitary Code. Accompanying me and providing input was your New York State certified operator, Scott Osborn of VRI. During the inspection, I observed that your water system is properly operated and adequately maintained and currently serves approximately 2100 people through 600 service connections. Please provide updated information to this office as appropriate.

William R. Steinhaus County Executive

Dutchess

of Health

County Department

Michael C. Caldwell, MD, MPH Commissioner

Environmental Health

387 Main Street Poughkeepsie New York 12601 (845) 486-3404 Fax (845) 486-3545



- Monthly operation reports indicate an average daily usage of approximately 200,000 gallons per day.
- Three (3) infiltration galleries located adjacent to the treatment building serve as water sources for this facility. At this time, the safe yield of each gallery is unknown. Aquifer pump testing performed in November of 1997 indicated a stabilized flow rate of 58 gallons per minute.
- Raw water flows by gravity to a 45,000 gallon clear well located below the
 treatment building where it is injected with a sodium hypochlorite solution for
 disinfection, caustic soda for pH control and zinc orthophosphate for corrosion
 control. This tank provides storage for future use as well as adequate chlorine
 contact time. Two galleries combine in a small wet well before entering the clear
 well.
- Alternating booster pumps send water to a 500,000 gallon elevated storage tank
 which "floats" on the system, accepting water only when there is no demand in the
 distribution system. The tank provides storage volume as well as adequate
 pressure for the distribution system.
- Alarms are provided for high/low storage levels as well as power and communication failure. The onsite generator is exercised every two weeks and was briefly turned on during the inspection.

The following items were discussed during the inspection and are re-iterated here as documentation for the New York State Department of Health, Bureau of Public Water Supply Protection program.

After reviewing monthly operation reports and monitoring results submitted to this
Department since our last inspection, it appears the system was capable of
meeting the demands placed upon it. The sodium hypochlorite solution added
was able to meet disinfection requirements and laboratory results for all system

monitoring were able to meet quality standards for drinking water. The chlorine residual at the plant was 2.0 at the time of inspection. In addition, monthly operation reports as well as sample results were provided to this Department in an acceptable and timely manner.

- During the inspection, it was observed that the cover for the wet well is acting as a rain collector, allowing infiltration of surface water when the cover is opened. This cover must be replaced with a lockable, sealable unit that diverts rainwater off the surface no later than July 1, 2010 to avoid a violation.
- 3. The status of several monitoring wells located on the property is unknown. If these wells are no longer being used, they must be properly abandoned no later than December 31, 2010. Please submit the appropriate permit applications prior to the start of work.
- 4. During the inspection, it was noted that the area surrounding the newer infiltration gallery across the stream was cleared of all brush and trees since the last inspection. Please keep this area clear as part of routine maintenance. To further protect the galleries from contamination, this department is requiring the bunkers which allow access to the source water be cleaned of debris and any cracks or spaces between the concrete risers repaired with an approved material. In addition, this department is requiring the bunkers' access hatches be provided with a sealable gasket. Please perform this work no later than July 1, 2010 to avoid a violation.
- 5. It was noted during the inspection that a sink within the treatment building discharges directly on a stone bed outside the building. This department is requiring a sign be posted above the sink that reads, "NO WASHING. FOR SAMPLE USE ONLY" as soon as possible. In addition, during the inspection I observed that there was no light in the chlorination room. Please provide a new light immediately. Indicate this work has been completed on your next monthly operation report to avoid a violation.
- It is strongly recommended that piping within the treatment building be painted as soon as
 possible. In addition, this department recommends a safer, more secure way of crossing
 the stream on this property. Currently, the operator uses a 10"-12" wide piece of wood as a
 plank to cross the stream.
- 7. It appears your elevated 500,000 gallon storage tank needs painting. Your operator indicated the village is planning to have the tank inspected and painted this year.
- 8. Copies of the 2008 Annual Water Quality Report (AWQR) and certification were received by this Department on time. Please be advised the 2009 AWQR must be provided to this Department and all consumers no later than May 31, 2010. A copy of the AWQR certification form must be provided to this Department by September 1, 2010. It is recommended to submit a rough draft of the report to this Department as soon as possible to allow sufficient review time.
- 9. Part 5-1.52 addresses your facility's monitoring requirements for quality control. The attached sampling schedule has been provided as a general guide only. It is the responsibility of the supplier and not this Department to make sure that all monitoring is performed according to the methods, procedures, and time periods indicated in Part 5 of the New York State Sanitary Code. Sampling frequency is based on maximum contaminant and action levels and therefore, the frequency is subject to change pending

Page 3 V. of Millbrook PWS April 15, 2010

sample results. A violation will be issued for failure to comply with the sampling requirements and due dates.

I would like to thank VRI's personnel for their assistance during the inspection. Please keep this office updated on any changes associated with the operator, town officials, phone numbers and addresses. If you have any questions regarding this correspondence, or if I can be of further assistance, please contact me at (845) 486-3404.

Yours very truly,

Daniel J. Keeler

Public Health Engineer

Environmental Health Services

DJK/kmk

cc: Scott Osborn, VRI (w/ enclosures)

Michelle Kelley-→Joseph Tagliavia, DCDOH-→File 097-0024622 (w/ enclosures)

Sampling Schedule

PWS: Millbrook Village Federal ID# 1302770 Population: 1400

Infiltration Galleries: 3

Service Connections: 651

Treatment Plants: 1

Distribution Systems: 1

ANALYTE	SAMPLE POINT	WSF	MONI #	TORING PERIOD FREQUENCY	LAST SAMPLE	VIOLATION	NEXT DUE
TCR	DIST	DS199	2	Monthly	1/12/2010	NO	2/28/2010
GWUDì (Temp. & Conduc	RAW fivity)	SOURCES &STREAM	1	Daily	N/A	NO	6/1/2010
LT2SWTR (E. Coli Enumerat	RAW ion)	EACH SOURCE	1	Every 2 Weeks	N/A	NO	6/1/2010
NITRATE	. EP	DS199	1	Annually	3/4/2009	NO	12/31/2010
IOC 8B IOC 8D	EP EP	DS199 DS199	1 2	Every 3 Years Quarterly	10/17/2007 2/2/2010	NO NO	12/31/2010 6/30/2010
soc	EP	DS199	1	Every 3 Years	7/18/2007	NO	12/31/2010
RAD	EP	DS199	1	Every 6 Years	3/15/2007	NO	12/31/2013
POC	RAW	DS199	1	Annually	7/21/2009	NO	12/31/2010
PBCU	DIST	DS199	1	Every 3 Years	9/2/2008	МО	9/30/2011
DBP STAGE 1 DBP STAGE 2	DIST DIST	DS199	1	Annually 40/30 WAIVER ISS	8/19/2009 SUED ON 3/31/2008	NO	8/30/2010
ASBESTOS	EP / DIST			WAIVER ISSUE	ED ON 1/29/07		

APPENDIX – E

			_
			_
			T
			_
			The state of
			_
			_

CT Time Calculations

3.2 Log Removal Credit with LT2 Cartridge Filter and we need 4 log removal to meet the LT2 requirements.

The proposed 150,000 gallon contact tank with mixing and or baffles, provides a baffle factor of .5, which equals which 75,000 gallons of contact time or 300 minutes CT with one pump @ 250 gpm and 150 minutes with two pumps @ 500 gpm.

One pump @ 250 gpm equals a CT of 300 minutes.

75,000 gal / 250 gpm = 300 minutes CT.

Two pumps @ 500 gpm equals a CT of 150 minutes.

75,000 gal / 500 gpm equals a CT of 150 minutes.

Using the EPA Guidance Manual Table C-1 Values for Inactivation of Giardia Cysts by Free Chlorine at 0.5° C or Lower

The system average chlorine concentration of 1.2 mg/L, pH of 7.5 and the low temp of 3° C

Using the above mentioned table 173 minutes of CT time / 1.2 mg/L chlorine = 145 minutes provides 2 log removal.

173/1.2 = 145 minutes will provide 2 Log Removal

Conclusion is that with the 3.2 log removal of the Cartridge filter and the 2 log removal by free chlorine the new system will provide a minimum of 5.2 log removal

			•		
	•				
					Nedman
					-

					Person
					-
				•	
					Things
				•	
-					*********
					· ·

					Northgro.
					-

					women
		•			Marrago:

Table C-1. CT Values for Inactivation of Giardia Cysts by Free Chlorine at 0.5°C or Lower

-	100	3.0	727	239	246	253	259	266	273	279	286	297	298	304	310	316														15.5			
Ľ		2.5	200	32	205	211	216	222	228	233	238	248	248	253	258	263																	
7.5 Ivatic	I Addition	2.0	22	159	164	169	173	177	182	186	191	198	199	203	207	211																	
pH=7.5 I on Inactivation	1 1 1 1 1	J. 5														. 1																	
2		0.5							50																								
		0.5	40	40	4	42	43	44	46	47	48	20	SS	2	25	23																	
	1	3.0	195	200	205	210	215	221	226	231	236	242	247	252	257	261			3.0	390	407	422	437	451	464	477	489	200	511	522	533	543	552
2		2.5	163	167	171	175	179	184	188	193	197	202	206	210	214	218		u	2.5	325	339	352	364	376	387	398	408	417	426	435	444	453	460
pH=7.0 Inactivation	Vallo	5.0	-	2		19	Ť.							23		174	0.0	Log Inactivation	2.0	260			100500					25.21					
pH=7.0	I I	5.5					1.00									131	9Hq	Inact	1.5	195													_
5	41	1.0														87		LG	1.0	130				_		_	-		_		178		
		0.5	33	33	32	35	36	37	38	39	39	9	41	42	43	44				. 99													
	1	3.0	163	169	172	176	180	184	189	193	197	201	205	209	213	217			3.0	329	342	354	365	376	387	397	407	417	426	435	444	452	ARO
,	1																		2.5	274													
5.	Inactivation	2.0	109	112	115	117	120	123	126	129	131	134	137	139	142	109 145 181	9	Inactivation	2.0	219											120201		
pH=6.5	Ilaci	1.5	82	2	86	88	06	92	95	26	66	101	103	105	107	109	PH=8	Inact	1.5	165													
-	얼셈	0.1																Log	_	. 011		-		_	2200						10.000		
		0.5	27	28	29	29	30	34	32	32	33	¥	8	35	99	38			0.5	22	22	29	6	63	65	99	89	2	71	73	74	22	77
		3.0	137	141	145	148	152	155	157	162	165	169	172	175	178	181			3.0	277	286	295	304	313	321	329	338	346	353	361	368	375	382
		2.5	114	118	121	123	127	129	131	135	138	141	143	146	148	151		_	2.5	231	238	246	253	261	268	274	282	288	294	301	307	313	218
9	activation	2.0	91	8	26	66	101	103	105	108	110	113	115	117	119	121	0	ivation	2.0	185	191	197	203	209	214	219	225	231	235	241	245	250	SEE
0	느	1.5	69	7	73	74	76	78	62	200	83	82	98	88	88	9	pH=8.0	Inact	5.	139	143	148	152	157	161	165	169	173	177	181	184	188	101
-	63 P	1.0	46	47	48	49	5.	22	52	54	22	29	57	58	29	9		Log	10	92 139 185 23	92	86	101	104	107	110	113	115	118	120	123	125	107
iy:		0.5	33	24	24	25	25	26	26	27	28	28	29	29	30	8			0.5	46	48	49	51	52	5	22	26	55	29	09	61	63	79
-	_		<=0.4	9.0	8	-	10	4	. 6	000		22	4	26	2.8	က		_		<=0.4	9.0	0.8	₹	1.2	4.	1.6	18	2	2.2	2.4	2.6	2.8	i
1	AHO		Ÿ															ATIO		V													
SINE	CONCENTRATION																3NE	CONCENTRATION															
CHLORINE	ONC	(mg/L)	e ⁵³														CHLORINE	SONC	(ma/	9													

Source: AVVVA, 1991.

		`
		·
		·
`		
		÷.
		-
		•
		No.

		ngu.

PRESS RELEASE

HARMSCO®

North Palm Beach, Florida December 2, 2013 Harmsco Filtration Products LT2 Pleated Cartridges

Pleated Cartridges

Meet Long Term 2 Requirements Today for Ground Water Under Direct Influence of Surface Water (GWUDI)

Now Available!



Harmsco® Filtration Products

is pleased to announce the availability of

LT2 Pleated Cartridges

for Public Drinking Water. These cartridges feature high flow capability, low initial pressure drop, lower overall operating cost, increased contaminant removal, and longer filter runs for fewer change-outs.

Features


- NSF-61 Listed filter media removes cyst-sized particles for safe, cyst-free drinking water
- Pleated media provides more surface area for longer filter life and increased particle removal
- Patented Dual Durometer end caps ensure positive sealing
- ✓ FDA Listed Materials: Manufactured from materials which are listed for food contact applications in Title 21 of the U.S. Code of Federal Regulations
- ✓ 100 GPM per cartridge at >3.6 log reduction

Municipal Hurricane® Systems

Certified: NSF/ANSI Standard 61 **Drinking Water System Components -**

Health Effects

Independently Tested



Harmsco® HC/170-LT2

Applications

- Surface Water Treatment Rule (SWTR) LT2
- Ground Water Under Direct Influence (GUDI)
- Municipal Drinking Water
- Reverse Osmosis Pre-filtration
- Food & Beverage Filtration
- Desalination Pre-filtration
- Commercial/Residential Drinking Water

Specifications

Filter Media:

FDA borosilicate with acrylic binder

End Caps:

Plastisol (pliable PVC)

Change Out: 25-30 PSI (1.72-2.07 Bar) ΔP

Flow Rate:

100 GPM (recommended)

Surface Area:

120 sq. ft.

Temperature*: 140°F(60°C) max.

pH: 3 to 11

Center Tubes:

Rigid PVC (perforated)

CLICK HERE TO VIEW ALL LT2 LISTINGS

Note: This publication is to be used as a guide. The data within has been obtained from many sources and is considered to be accurate. Harmsco does not assume liability for the accuracy and/or completeness of this data. Changes to the data can be made without notification. Temperature, Pressure, Flow Rates, Differential Pressures, Chemical Combinations and other unknown factors can affect performance in unknown ways. Limited Warranty: Harmsco warrants their products to be free of material and workmanship defects. Determination of suitability of Harmsco products for uses and applications contemplated by Buyer shall be the sole responsibility of Buyer. The end user/installer/buyer shall be liable for the product's performance and suitability regarding their specific intended applications. End users should perform their own tests to determine suitability for each application.



HARMSCO[®] Filtration Products

www.harmsco.com

* Temperature rating based on pressure and time under load.



	 ***************************************	Control of the Contro		
				_
•				
				•
				~
				~
				~
				~
				Ne

				<u></u>
				•••
				-
				Na.
				_

				Sur

				1000

APPENDIX - F

Floway two Stage Pump same model as existing pumps with with a smaller motor 760 RPM

ENCLOSED TYPE IMPELLER


EFFICIENCY CHANGE (NO. OF POINTS)

NUMBER OF STAGES

- 11/2

HORSEPOWER WILL BE AFFECTED BY CHANGE IN EFFICIENCY

PUMP DATA



NIA 7 3/4 7 1/4 7 3/4 4 7/8 5 3/4

Bowl Height (IN.) Bell DIA. (T) (IN.)

Bowl O.D.(IN.)

Impeller C-line(X)(IN.)

Eye Area (IN^A 2)

Strainer height (IN.)

Performance indicated based on cold water with specific gravity

NOTES

** Minimum submergence over lip of bell to prevent vortexing.

* Standard Construction.

Efficiency improvements are available in certain instances. Please contact the factory.

956 11

Min. Submergence (IN)**

Impeller Weight (LBS)

Thrust Bal Const. (K)

Thrust Constant (K)

Maximum Sphere (IN)

Shaft Dia.(IN)

Maximum Head (FT)*

4.7

NEW SUPPLY PUMS FROM THE EXISTING WET WELL TO THE FILTER BUILDING


	СССРЭЙНИК ТЕОРУИН РОПОРУРОЦИИ ПОПИТИТЕ ТОПИТИТЕ ПОПИТИТЕ В ТОТЕМА, ч у до грес
	· vena
	Name
	Ness
	4000

	Nessan
	May room
	Addato
	~plan
	марар
	Malion
	·

D 109440



VERTUAL TURBINE FUMP



ALTERNATIONS AND A

company: Delaware Engineering . Jame: MILLBROOK WATER

Date: 2/13/2015

PROPOSED NEW BOOSTER PUMPS

hurks

Pump:

Size: G9 - 2

Type: Close Coupled Cent. Synch speed: 3600 rpm

Curve: 11237TX Specific Speeds:

Dimensions:

Pump Limits:

Temperature: 225 °F Pressure: 200 psi g Sphere size: 0.375 in Speed: 3500 rpm Dia: 8.5 in

Impeller: 21172

Ns: ---Nss: ---

Power: ---

Eye area: ---

Suction: 2.5 in Discharge: 2 in

Enclosure: TEFC

Sizing criteria: Design Point

Search Criteria:

Flow: 250 US gpm

Head: 270 ft

Size: 30 hp

Fluid:

Water Density: 62.32 lb/ft3

Viscosity: 0.9946 cP

NPSHa: ---

Temperature: 68 °F

Vapor pressure: 0.3391 psi a Atm pressure: 14.7 psi a

Motor:

Standard: NEMA JM

Speed: 3600 Frame: 286JM

Data Point ----

Flow: Head: Eff:

273 ft 65.6%

250 US gpm

Power: NPSHr:

26.2 hp 15.2 ft

--- Design Curve ----

Shutoff head:

319 ft 138 psi

Shutoff dP: Min flow:

BEP: 66.4% @ 230 US gpm


NOL power:

31.7 hp @ 340 US gpm

- Max Curve -

Max power:

37.3 hp @ 370 US gpm



225F max temperature is based on standard construction. Alternate material/construction is available for temperatures to 500F.

Performance E	Evaluation:					
Flow US gpm	Speed rpm	Head ft	Efficiency %	Power hp	NPSHr ft	
300	3500	230	59.4	29.3	18	
250	3500	273	65.6	26.2	15.2	
200	3500	298	65	23	13.9	
150	3500	314	60.1	19.8	12.9	
100	3500	321	48.6	16.6	12.8	

•
·
·
·
•
·